

REPLACEMENT PARTS GUIDE

5D (TREM IIIA and TIER 2) Series Tractors - 5045D

ENGINE



PRIMARY AIR FILTER
[RE282286](#)
SECONDARY AIR FILTER
[RE282287](#)

Service after every 250 hours or annually, and as required per conditions.

OIL FILTER
[RE519626](#) (5964)
[RE507204](#) (5933, 5978)
(FOR INDIA MARKET)
[T19044](#) (FOR EXPORT MARKET)



Replace after initial 100 hours then every 250 hours or annually. If Plus-50™ II oil and John Deere™ filter is used interval may be extended to 500 hours.


FUEL FILTER
[RE60021](#)



Replace after every 500 hours.



HYDRAULIC



HYDRAULIC OIL FILTER
[RE45864](#)

Replace after every 400 hours change every 1200 hours or 3 years.

CAPACITIES

5D (TREM IIIA and TIER 2) Series Tractors - 5045D

CAPACITIES (Approximate):

Fuel Tank:

5D Tractors (Open Operator Station) 60 L (15.85 gal)

Cooling System:

5D Tractors 9.5 L (2.5 gal)

Engine Oil:

5D Tractors 8.5 L (2.25 gal)

Transmission and Hydraulic System:

5D Tractors (2WD)..... 38 L (10 gal)

Grease Axle 30 L (7.92 gal)

Oil Axle 32 L (8.5 gal)

REPLACEMENT PARTS GUIDE

5D (TREM IIIA and TIER 2) Series Tractors - 5045D

ENGINE



BRAKE DISK
[SJ18395](#)



CLUTCH DISK
[SJ29350](#) (TRACTION)
[RE242274](#) (PTO)



ALTERNATOR
[RE258846](#)



FAN BELT DRIVE
[SU63793](#) (LGTH = 1340 MM)
[R73784](#) (-021554)
 (LGTH = 1340 MM) (2100 RPM)
[SU38901](#) (021555-028903)
 (LGHT = 1300 MM) (2100 RPM)
[SU64566](#) (028904-)
 (LGTH = 1315 MM) (2100 RPM)



CAB



SEAT
[SJ34660](#) (POWER STEERING)
[RE258488](#) (BACK)
[RE73192](#) (BOTTOM)

AXLE



TIE ROD
[R225906](#) (POWER STEERING W/ SCV)
[RE192255](#) (SUB FOR RE234118) (POWER STEERING, 2WD)
[RE190506](#) (RH) (POWER STEERING, 2WD)
[RE190481](#) (LH) (POWER STEERING, 2WD)