

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

7460 Cotton Stripper

CAB

FRESH AIR FILTER
(STANDARD) – [AH115833](#)
(HEAVY DUTY) – [AH168783](#)

Clean every 50 hours. Replace as required.



CAB

RECIRCULATION AIR FILTER
– [AH115836](#)

Clean every 10 hours.
Replace as required.



HYDRAULICS

HYDRAULIC RESERVOIR
(S/N -030000) – [AE43494](#) (QTY 1)
(S/N -030000) – [AN220456](#) (QTY 2)
(S/N 030001-) – [AE43494](#) (QTY 1)
(S/N 030001-) – [AN220314](#) (QTY 1)

HYDRAULIC RETURN
– [T175002](#)

Replace after 400 hours.
(Click here for [capacity](#))



ENGINE

PRIMARY FUEL FILTER
(6068TN) – [RE508633](#)
(6068HN) – [RE541922](#)

Replace every 250 hours and as required.



ENGINE

FINAL FUEL FILTER
(6068TN) – [RE62419](#)
(6068HN) – [RE522878](#)

Replace every 250 hours and as required.



ENGINE

PRIMARY AIR FILTER
(S/N -030000) – [RE65880](#)
(S/N 030001-) – [AN221846](#)



SECONDARY AIR FILTER

(S/N -030000) – [RE34967](#)
(S/N 030001-) – [AN221847](#)

Replace every year
and as required.



ENGINE

OIL FILTER
(6068TN) – [DZ118286](#)
(6068HN) – [RE504836](#)

Minimum hours before first engine oil change is 100 hours. Extended engine oil change every 500 hours or annually, whichever come first. The extended 500 hour interval is only allowed if using Plus-50™ II oil with a John Deere filter and diesel fuel with sulfur content less than 15mg/kg (15ppm). If all conditions are not met, change oil and filter at 250 hours of operation.

(Click here for [capacity](#))



WATER FUEL SEPARATOR FILTER

(6068HN) – [R100369](#)



CAPACITIES

7460 Cotton Stripper

CAPACITIES (Approximate):

Cotton Basket:

.....22.88 m³ (808 cu. ft.)

Fuel Tank:

.....454 L (120 gal)

Cooling System:

.....33.1 L (8.75 gal)

Engine Crankcase including Filter:

.....27.44 L (7.3 gal)

Hydraulic and Hydrostatic Reservoir:

.....81.8 L (21.6 gal)

Hydraulic and Hydrostatic System:

.....117.3 L (31 gal)

Transmission:

.....13.6 L (3.6 gal)

Final Drive (Each):

.....1.9 L (0.5 gal)

Cleaner Gear Case:

.....1 L (0.2 gal)

[Return to Filter Overview](#)

