

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

6E Series - 1404 Tractors

CAB FRESH AIR FILTER [RE198488](#)

Service after every 250 hours. Change as required.

CAB RECIRCULATION AIR FILTER [RE195491](#) [SU41628](#) [SU41769](#)

Clean after every 250 hours and annually. Change as required.

ENGINE OIL FILTER [RE504836](#)

Change after first 100 hours and then every 500 hours. If PLUS-50 oil and a John Deere filter are not used, lower this service interval to 250 hours.

(Click here for [capacity](#))

ENGINE PRIMARY FUEL FILTER [RE546336](#)

FINAL FUEL FILTER [RE544394](#)

Replace after every 500 hours.

HYDRAULIC OIL FILTER [SJ11792](#)

Replace after first 100 hours then after every 500 hours.

(Click here for [capacity](#))

ENGINE PRIMARY AIR FILTER [AL172780](#) SECONDARY AIR FILTER [AL150288](#)

Replace after every 1000 hours or annually whichever occurs first. Change as required.

ENGINE WATER SEPARATOR [N378886](#)

Replace after every 500 hours.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

6E Series - 1404 Tractors

CAPACITIES (Approximate):

Fuel Tank:

..... 220 L (58.12 gal)

Crankcase including Filter Change:

Plus-50™ II

..... 15 L (3.96 gal)

Cooling System:

Cool-Gard™ II

..... 18 L (4.76 gal)

Transmission and Hydraulic System:

Hy-Gard™

..... 60 L (15.65 gal)

Mechanical Front Wheel Drive (MFWD) Axle:

Hy-Gard™

Axle Housing 5 L (1.32gal)

Wheel Hub (Each) 0.8 L (0.21 gal)

[Return to Filter Overview](#)

