

REPLACEMENT PART GUIDE

9030 Series Wheel Tractors 9230, 9330, 9430, 9530, 9630

FILTER OVERVIEW WITH SERVICE INTERVALS

ENGINE



PRIMARY AIR FILTER
[RE261960](#)

SECONDARY AIR FILTER
[RE230985](#)

Replace annually and as required.



OIL FILTER
(9230)

[RE509672](#)
(9330-9630)
[RE572785](#)

Replace after 100 hours and then every 250 hours. Initial oil and filter change is 100 hours maximum of operation. Scheduled interval can be extended to 375 hours if PLUS50™ oil and a John Deere™ filter are used.



(9230)
PRIMARY FUEL FILTER
SECONDARY FUEL FILTER
[RE525523](#) AVAILABLE ONLY AS KIT

(9330, 9430, 9530, 9630)
PRIMARY FUEL FILTER
[RE532952](#)

SECONDARY FUEL FILTER
[DZ112918](#)

Replace after 100 hours and then every 250 hours.



FUEL TANK VENT FILTER
[H216169](#)

Replace every after 1500 hours (Interval may vary according to operating conditions).



CAB

FRESH AIR FILTER, HEAVY-DUTY

[RE24619](#)

Clean every 250 hours and replace annually.

CARBON FRESH AIR FILTER
[RE199681](#)

Do NOT clean. Change annually, after 500 hours, or as required.



RECIRCULATION AIR FILTER
[RE187966](#)

Clean after every 250 hours and replace annually

ARBON RECIRCULATION AIR FILTER
[RE199682](#)

Do NOT clean. Change annually, after 500 hours, or as required.



TRANSMISSION

OIL FILTER

[YZ502378](#)

Replace after 100 and 750 hours, and then every 750 hours.



OIL FILTER

[RE174130](#)

Replace after 100 and 750 hours, and then every 750 hours.



HYDRAULICS

RESERVOIR OIL FILTER

[AT101565](#)

Replace after every 750 hours.



SCV OIL FILTER

[T175002](#) AG AND SCRAPER TRACTORS

Replace after 100 and 750 hours, and then every 750 hours.



OIL FILTER

[RE174130](#)

Replace after 100 and 750 hours, and then every 50 hours.



JOHN DEERE

Genuine Parts and Service

CLICK PART NUMBER TO BUY

*See operator's manual for additional details.

For company use. RX532593

Apr 2022. Release Date.

CAPACITIES

9030 Series Wheel Tractors 9230, 9330, 9430, 9530, 9630

CAPACITIES (Approximate):

Fuel Tank..... 1325 L (350 gal)

Cooling System including Overflow Tank:

Cool-Gard™ II

9230..... 47.5 L (12.5 gal)

9330-9430-9530-9630 53 L (14 gal)

Crankcase including Filter:

Plus-50™ II

9230..... 28 L (7.4 gal)

9330-9430 (SN 022000 -)..... 40 L (10.5 gal)

9330-9430 (SN - 021999)..... 42 L (11 gal)

9530-9630 (SN 022000 -)..... 56 L (14.8 gal)

9530-9630 (SN - 021999)..... 60 L (15.8 gal)

Transmission/Axle:

Hy-Gard™

24-Speed:

9230 & 9330..... 100 mm Axles Without PTO..... 140 L (37 gal)

9230 & 9330..... 100 mm Axles With PTO..... 144 L (38 gal)

9230, 9330 & 9430.... 110 mm Axles Without PTO... 144 L (38 gal)

9230, 9330 & 9430.... 110 mm Axles With PTO..... 148 L (39 gal)

18-Speed Powershift:

9230..... 100 mm Axles Without PTO..... 166.6 L (44 gal)

9230..... 100 mm Axles With PTO..... 170.8 L (45 gal)

9230, 9330 & 9430.. 110 mm Axles Without PTO.. 170.8 L (45 gal)

9230, 9330 & 9430... 110 mm Axles With PTO..... 174.5 L (46 gal)

9530 & 9630..... 120 mm Heavy-Duty Axles..... 87 L (23 gal)

Hydraulic System:

Hy-Gard™

Without Hitch - Standard 103 L (27 gal)

With Hitch - Standard 106 L (28 gal)

Without Hitch - High-Flow..... 113.5 L (30 gal)

With Hitch - High-Flow..... 117 L (31 gal)

REPAIR PART GUIDE

9030 Series Wheel Tractors 9230, 9330, 9430, 9530, 9630

ENGINE



TORSIONAL DAMPER
[RE586976](#) - 9.0 L
[RE530733](#) - 13.5 L



STARTER
[RE529661](#) - 9.0 L
[RE539584](#) - 13.5 L



FUEL INJECTION PUMP
[DZ124927](#) - 3703
[RE571640](#) - 9230R
[DZ124926](#) - 3712



A/C COMPRESSOR
[AH169875](#)



FAN DRIVE BELT
[R568198](#) - 9.0 L
[R239551](#) - 13.5 L



RADIATOR CAP
[AT322214](#)



ENGINE BLOCK HEATER
[RE42139](#) - 9.0L
[AR84185](#) - 13.5 L



AUX DRIVE BELT
[R230995](#) - 9.0 L
[R241746](#) - 13.5 L



WATER PUMP
[RE530194](#) 9.0L
[RE549117](#) 13.5 L



BELT TENSIONER
[RE582501](#) - 9.0L
[RE243154](#) 13.5 L



ALTERNATOR
[RE555751](#)



BATTERY
[TY25879B](#)



CAB



WIPER BLADES
[AL153661](#) - Front & Rear



INTERNAL REAR VIEW MIRROR
[AT186760](#)



EXTERNAL REAR VIEW MIRROR
[AL78021](#) - LH
[R134059](#) - RH



TECHNOLOGY MOUNTING SOLUTION
[BRE10141](#) - Accessory Mounting
[BRE10015](#) - Cell Point Mounting
[BRE10255](#) - Tablet Mounting



GAS CYLINDERS
[RE234992](#) - LH Door
[RE234166](#) - Rear Window

HITCH AND SCV



HITCH MAINTENANCE
[R253500](#) - Sway Block, RH
[R253501](#) - Sway Block, LH
[RE334228](#) - Rockshaft Position Sensor



SCV
[RE577560](#) - Breakaway Coupler
[R186598](#) - Snap Ring
[RE186600](#) - Seal Kit
[RE220072](#) - Power Beyond Coupler KIT



[RE151894](#) - Hydraulic Motor Return Kit



LIFT LINK PINS
[R272197](#) - Pin
[R107278](#) - Draft Link Ball Stud

