

SPECIFICATIONS

www.skidsteer.com

THE SKID STEER FOR THE UPWARDLY MOBILE.

250 Series II Skid Steer

- Patented vertical-lift system provides greater reach than conventional skid steers, for precise center load placement and quick, efficient truck loading.
- 64-hp John Deere 3029T high-torque, turbocharged engine with direct injection has exclusive wet-sleeve design, high-ring pistons, and precision joint-connecting rods. This easy-starting, durable engine is extremely fuel efficient.
- Large 12x16.5 tires and superior ground clearance of 9.6 inches means effective maneuvering with greater traction and floatation for operating in terrain where other skid steers can't.
- Quick-lift cab, removable side panels, and easy-access top and rear doors permit convenient maintenance and service.
- Superior 360-degree visibility results in greater productivity and safe operation. Unique boom arm design provides maximum bucket visibility.
- Steep 45-degree dump angle and high 35-degree bucket rollback make for more efficient load carrying and quicker cycle times.
- Available cab enclosure, air conditioner, and heater/defroster provide year-round climate control.
- Optional hydraulic Quik-Tatch™ latches/unlatches at the touch of a switch for convenient in-the-seat attachment switchover.
- Strong machine forces include — 5,500-lb. bucket breakout, 6,250-lb. operating weight, 4,725-ft.-lb. axle torque, and 3,600-lb. tipping load. Rated Operating Capacity (R.O.C.) is 1,750 lb. (2,100 lb. with optional counterweight).
- 115-in. hinge pin height easily clears 9-ft. truck sideboards for fast, efficient truck loading.

	250 Series II	Standard Equipment	Options/Accessories
Engine	John Deere	Adjustable Armrests, Patent Pending	Air Conditioning with Heater/Defroster
Model	3029T	Adjustable Foot Pedals	Auto Preheat
Displacement	179 cu. in. (2.9 L)	Air Heat Cold Start	Auto Shutdown with Alarm
Cylinders	3	Auxiliary Hydraulics	Backup Alarm
Horsepower	64.4 hp (48 kW) gross / 61 hp (45.5 kW) net	Convenient Front and Rear Tie Downs	Block Heater Kit
Rated Engine Speed	2,400 rpm	Deluxe Seat	Cab Enclosure
Fuel Capacity	15 U.S. gal. (91 L)	Four Grab Handles	Demolition Door Kit
Performance:		Front and Rear Work Lights	Dual Flashers Kit
SAE Rated Operating Capacity	1,750 lb. (794 kg)	Integral Cab Boom Locks	Floor Cover Plates
With Optional Counterweights	2,100 lb. (953 kg)	John Deere Manufactured Hydraulic Cylinders	Hand Controls
Tipping Load	3,600 lb. (1633 kg)	Meters/Gauges/Warning Lights	Heater/Defroster Kit
Breakout Force :		Patented John Deere Quik-Tatch	High-Flow Hydraulics
Foundry Bucket	5,500 lb. (2495 kg)	Patented Vertical-Lift Boom	Horn
Construction Bucket	3,900 lb. (1769 kg)	Quick-Pivot ROPS	Hydraulic Quik-Tatch
Ground Speed:		Rear Window	Hydraulic Self-Leveling Kit
Single Speed	6.8 mph (10.9 km/h)	Seat Belt with Auto Recoil	Quik-Tatch Weights
Maximum Axle Torque	4,725 ft.-lb. (6406 Nm)	Triple-Interlock Control System	Rear Weight Brackets
Operating Weight	6,250 lb. (2835 kg)	Turbocharged John Deere POWERTECH® Engine	Rearview Mirror Kit
Hydraulics:		Wet Disk Brakes	Shoulder Belt
Hydraulic Pressure	3,100 psi	8 pr. 12x16.5 SKS Tires	Side Window Kit
Hydraulic Pump:		55-Amp Alternator	SMV Sign
Standard Flow	17.6 gpm (66.6 L/min.)		Suspension Seat
High Flow	30.1 gpm (113.9 L/min.)		Top Window
Hydraulic Horsepower:			Vinyl Cab Enclosure
Standard Flow	31.8 hp (23.8 kW)		Warning Beacon
High Flow	54.2 hp (40.4 kW)		3-Inch Seat Belt
Transmission	Hydrostatic four-wheel drive		8-Button Handle
Dimensions:			12-Volt Receptacle Kit
Length without Bucket	102 in. (2591 mm)		
Length with Bucket	125.8 in. (3196 mm)		
Width without Bucket	69.9 in. (1775 mm)		
Height to ROPS	76.8 in. (1950 mm)		
Height to Hinge Pin	115.2 in. (2925 mm)		
Dump Reach:			
Heavy-Duty Foundry Bucket	28.1 in. (715 mm)		
Heavy-Duty Construction Bucket	35.1 in. (892 mm)		
Dump Angle (At Full Height)	45 degrees		
Bucket Rollback (At Ground)	35 degrees		
Wheelbase	42.3 in. (1075 mm)		
Ground Clearance	9.6 in. (244 mm)		
Angle of Departure	27 degrees		
Standard Tire Size	12x16.5 SKS, 8-ply rating		
John Deere Standard Warranty	1-year unlimited hours		

John Deere Worksite Pro™ Attachments

Ag Utility Grapple	Hydraulic Breakers	Snow/Utility Blades
Angle Brooms	Multi-Purpose Buckets	Three-Point Hitch
Augers	Pallet Forks	Tined/Brush Grapples
Backhoes	Pick-Up Brooms	Tooth Bars
Bale Spear	Power Rakes	Tracks
Cold Planers	Rotary Tillers	Trenchers
Construction, Foundry, Manure/Slurry, and Utility Buckets	Scrap Grapples	Vibratory Rollers

Due to various widths, not all attachment sizes offered are compatible with all 200 Series Skid Steers.

(Dimensions and specifications in accordance with SAE and ISO standards. Rated Operating Capacity with 72-in. Foundry Bucket and standard tires per SAE Standard J818.)



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.



JOHN DEERE