

REPLACEMENT PARTS GUIDE

9600 Self-Propelled Forage Harvester (S.N.620000 - 620999)

CAB

FRESH AIR FILTER [RE284091](#)

Clean after every 250 hours and replace as required.

RECIRCULATION AIR FILTER [L214634](#)

Clean after every 250 hours and replace as required.

HYDRAULICS

OIL FILTER [AXE27449](#) (ProDrive™ only)

Replace after the first 100 hours, then every 1000 hours.

HYDRAULIC RESERVOIR OIL FILTER [AXE27447](#)

Replace after every 1000 hours or two years, whichever occurs first.

POWER DISTRIBUTION GEAR OIL FILTER [AXE27449](#)

Replace after the first 100 hours, then every 1000 hours.

ENGINE

PRIMARY FUEL FILTER [DZ112918](#)

SECONDARY FUEL FILTER [RE539465](#)

Replace after every 500 hours and as required.

DIESEL PARTICULATE FILTER [DZ100175](#)

Replace after 4500 hours.



ENGINE



PRIMARY AIR CLEANER [HXE60966](#)

Clean as required and replace after every 1500 hours



CRANKCASE VENTILATION FILTER [RE550022](#)

Replace after every 1000 hours of operation



SECONDARY AIR CLEANER [HXE60967](#)

Replace with each primary air cleaner change.



FUEL LINES [H216169](#)

Replace after the first year, then every 4500 hours or three years, whichever occurs first.



OIL FILTER [RE572785](#)

Replace after first 100 hours, then every 250 hours. If Plus-50™ II oil is used interval may be extended to 500 hours.



DIESEL EXHAUST FLUID (DEF) TANK VENT FILTER [H216169](#)

Replace after the first year, then every 4500 hours or three years, whichever occurs first.

CAPACITIES

9600 Self-Propelled Forage Harvester (S.N.620000 - 620999)

CAPACITIES (Approximate):

Fuel Tank:

..... 1100 L (396 gal)

DEF Tank:

..... 43 L (11.4 gal)

Cooling System (Complete):

Cool-Gard™ II

..... 110 L (29.1 gal)

Engine with Filter:

Plus-50™ II

..... 58 L (15.3 gal)

Transmission (PBS):

GL-5

..... 9.6 L (2.53 gal)

Transmission (ProDrive™):

Hy-Gard™

..... 16 L (4.22 gal)

Final Drives (Each):

GL-5

..... 7 L (1.85 gal)

Additive Dosing System Capacity:

Reservoir (high-volume) 360 L (95 gal)

Reservoir (low-volume)..... 30 L (8 gal)

Central Lubrication System Capacity:

Reservoir8 KG (17.6 lb)

Two-Wheel Drive Rear Axle:

GL-5

Wheel Hub 0.5 L (0.13 gal)

Four-Wheel Drive Rear Axle:

GL-5

Differential (Heavy Duty)..... 17L (4.5 gal)

In Motor Housing 1 L (0.26 gal)

Reduction Gear 0.7 L (0.19 gal)

Hydraulic System:

Hy-Gard™

Hydraulic Oil Reservoir..... 50 L (13.2 gal)
(Without High Flow Dump Option)

Hydraulic Oil Reservoir..... 70 L (18.5 gal)
(With High Flow Dump Option)

Right Feedroll Gearbox 6.7 L (1.77 gal)

Left Feedroll Gearbox 1.55 L (0.41 gal)

Header Gearbox (Heavy Duty) 0.92 L (0.24 gal)

Power Distribution Gear Lubrication System:

Hy-Gard™

Reservoir..... 22 L (8.7 gal)

Complete circuit 27 L (7.13 gal)

Brake System (PBS Transmission):

DOT3 or DOT4

Brake Fluid 1 L (0.26 gal)

Water Tank Capacity:

..... 20L (5.3 gal)

Additive Dosing System Capacity:

Reservoir (High volume)..... 360 L (95 gal)

Reservoir (Low volume)..... 30 L (8 gal)

Air Compressor System Capacity (Optional):

Reservoir 40 L (10.6 gal)

Air Conditioning System:

Refrigerant2700 or 2900 g (6.0 or 6.5 lb)

REPLACEMENT PARTS GUIDE

9600 Self-Propelled Forage Harvester (S.N.620000 - 620999)

FEED ROLLS

STEEL BAR

- [HXE93575](#) (UPPER)
- [HXE100097](#) (LOWER)
- [HXE134996](#) (FILLER BAR)
- [Z74127](#) (SCREW)
- [Z74128](#) (NUT)

Made of heavy-duty, induction hardened stainless steel.

LOWER FRONT FEED ROLL KIT

- [BXE10742](#)
- 12 reversible bars and screws.

CUTTERHEAD

CUTTERHEAD KNIVES

- [HXE185151](#) (GRASS)
- [HXE185153](#) (CORN)

Tough tungsten carbide coating for high quality cutting, longer wear life and lower engine power demands.

KNIFE FIXING PARTS

- [HXE119923](#) (COVER)
- [HXE143972](#) (KNIFE BOLT)

Secure hold and controlled retraction due to defined hardening, high-quality steel and sandblasted finishing.

SHEARBAR

- [HXE142409](#) (GRASS)
- [HXE142408](#) (CORN)
- [HXE169399](#) (DURALINE PLUS)

Sharp edge and high wear resistance for an exact and efficient cut.

SHARPENING STONE

- [AXE17437](#)
- Special composite material for the perfect edge and strong bond to the mounting plate

JD PREMIUM KERNEL PROCESSOR

KERNEL PROCESSOR ROLLS

- [AXE43163](#) (STANDARD, NON-COATED) (Z = 118)
- [AXE90181](#) (STANDARD, COATED) (Z = 118)
- [AXE43496](#) - (TRIANGULAR, NON-COATED) (Z = 238)
- [AXE84272](#) (XCUT, FRONT) (Z = 105)
- [AXE84275](#) (XCUT, REAR) (Z = 135)
- [AXE66440](#) (DURA LINE™, NON-COATED, FRONT) (Z = 178)
- [AXE66442](#) (DURA LINE™, NON-COATED, REAR) (Z = 178)

Strong shafts and exactly hardened teeth.

KERNEL PROCESSOR BEARING AND SEAL KIT

- [AXE59430](#) (SPHERICAL ROLLER BEARING)
- [AXE59608](#) (SEAL KIT, RH)
- [AXE59607](#) (SEAL KIT, LH)

KERNEL PROCESSOR DRIVE BELT AND IDLER

- [HXE176989](#) (32 AND 40% SPEED DIFFERENCE, 7 GROOVE)
- [AXE81568](#) (40% SPEED DIFFERENCE, 7 GROOVE)
- [AXE70751](#) (40% SPEED DIFFERENCE, 7 GROOVE)
- [AXE17553](#) (IDLER)

Strong belt and idler for constant processing
Drives the Kernel Processor Rolls.



REPLACEMENT PARTS GUIDE

9600 Self-Propelled Forage Harvester (S.N.620000 - 620999)

JD XSTREAM KERNEL PROCESSOR

KERNEL PROCESSOR ROLLS

[AXE89225](#) (STRAIGHT CUT) (Z = 110)

[AXE89227](#) (TWIN CUT) (Z = 110)

[AXE89226](#) (STRAIGHT CUT) (Z = 145)

[AXE89228](#) (TWIN CUT) (Z = 145)

[AXE89229](#) (TWIN CUT) (Z = 165)

[AXE89230](#) (STRAIGHT CUT) (Z = 165)

Strong shafts and exactly hardened teeth.



KERNEL PROCESSOR BEARING AND SEAL

[AXE131371](#) (BEARING)



[AXE131372](#) (SEAL)

BLOWER PADDLES

BLADE

[HXE29814](#)

Long lifetime and a efficient crop acceleration with a perfect throw distance.

