

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES


## 5M Series Tractors Tier 3 (5065M, 5075M, 5085M, 5095M, 5095MH, 5105M, 5105ML)

### CAB

**FRESH AIR FILTER – [RE198488](#)**  
(5065M, 5075M, 5085M, 5095M, 5095MH, 5105M)

Clean every 600 hours or annually,  
and as required per conditions.

Quantity 2




### CAB

**RECIRCULATION AIR FILTER – [RE195491](#)**  
(5065M, 5075M, 5085M, 5095M, 5095MH, 5105M)

Clean every 600 hours or annually,  
and as required per conditions.

Quantity 2




### HYDRAULIC

**OIL FILTER – [SJ11784](#)**

Replace every 600 hours.

(Click here for [capacity](#))



### ENGINE

**FUEL FILTER – [RE533026](#)** (5065M, 5075M)

**PRIMARY FUEL FILTER – [RE541922](#)** (5085M, 5095M, 5095MH, 5105M, 5105ML)

**FINAL FUEL FILTER – [RE526557](#)** (5085M, 5095M, 5095MH, 5105M, 5105ML)

Replace every 500 hours.




### ENGINE

**OIL FILTER – [RE519626](#)** (5065M, 5075M)

Replace every 300 hours.

If using Plus-50™ II 15-40,  
replace every 500 hours.

(Click here for [capacity](#))



### ENGINE

**PRIMARY AIR FILTER – [RE253518](#)**  
(5065M, 5075M)

Service every 600 hours or annually  
as required per conditions.

**PRIMARY AIR FILTER – [AL172780](#)**  
(5085M, 5095M, 5095MH, 5105M, 5105ML)

Service every 1200 hours or annually  
as required per conditions.

**SECONDARY AIR FILTER – [RE253519](#)**  
(5065M, 5075M)

**SECONDARY AIR FILTER – [AL150288](#)**  
(5085M, 5095M, 5095MH, 5105M, 5105ML)



### ENGINE

**OIL FILTER – [RE504836](#)** (5085M, 5095M, 5095MH, 5105M, 5105ML)

Initial replacement after 100 hours and then replace every 300 hours.

If using Plus-50™ II 15-40, replace every 500 hours.

(Click here for [capacity](#))



**JOHN DEERE**

Genuine Parts and Service

# CAPACITIES

## 5M Series Tractors Tier 3 (5065M, 5075M, 5085M, 5095M, 5095MH, 5105M, 5105ML)

### CAPACITIES (Approximate):

#### Fuel Tank:

5065M-5075M (Open Operator Station).....	84 L (22.3 gal)
5065M-5075M (Cab) .....	117 L (31 gal)
5085M-5095M-5095MH 5105M-5105ML (Open Operator Station).....	115 L (30.3 gal)
5085M-5095M-5095MH-5105M (Cab) .....	154 L (40.7 gal)

#### Cooling System:

##### Cool-Gard™ II

5065M-5075M (with Cab add 2 L).....	13 L (3.4 gal)
5085M-5095M-5095MH 5105M-5105ML (with Cab add 2 L) .....	13.5 L (3.6 gal)

#### Crankcase with Filter:

##### Plus-50™ II

5065M-5075M .....	10 L (2.6 gal)
5085M-5095M-5095MH-5105M-5105ML .....	13 L (3.4 gal)

#### Transmission and Hydraulic System:

##### Hy-Gard™

SyncShuttle™ Plus Transmission.....	53 L (14 gal)
Power Reverser™ or SyncReverser™ Transmission .....	53 L (14 gal)
Power Reverser™ Plus Transmission.....	53 L (14 gal)

#### Mechanical Front Wheel Drive (MFWD) Axle:

##### Hy-Gard™

Differential Housing .....	5 L (1.32 gal)
Wheel Hub (Each) .....	0.8 L (0.21 gal)

[Return to Filter Overview](#)

