

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

9000 Walker Series Combines

ENGINE

PRIMARY AIR FILTER

(9400 MSN -655288, 9500 MSN -645200, 9600 MSN -645300) – [AR80652](#), [AR82915](#)


PRIMARY AIR FILTER

(9400 MSN 655289-, 9500 MSN 645201-665977, 9600 MSN 645301-666172) – [AR70106](#)

PRIMARY AIR FILTER

(9500 MSN 665978-, 9600 MSN 666173-) – [AR95758](#)

Change annually and clean or change as required.



ENGINE

SECONDARY AIR FILTER

(9400 MSN -655288, 9500 MSN -645200, 9600 MSN -645300) – [AR80653](#), [AR81313](#)

SECONDARY AIR FILTER

(9400 MSN 655289-, 9500 MSN 645201-665977, 9600 MSN 645301-666172) – [AR70107](#)

SECONDARY AIR FILTER

(9500 MSN 665978-, 9600 MSN 666173-) – [AR95759](#)


Change only with primary filter.

CAB

RECIRCULATION AIR FILTER

(9400 – 9600) – [AH115836](#)

Clean or replace every 200 hours and as required.




CAB

AIR FILTER, STANDARD

(9400 – 9600) – [AH115833](#)

AIR FILTER, FOR OPERATORS WITH ALLERGIES (9400 – 9600) – [AH168783](#)

Clean or replace after 50 hours and as required.



ENGINE

FUEL WATER SEPARATOR FILTER

(9400 – 9600) – [AT81478](#)

Replace every 500 hours and as required.




HYDRAULIC/HYDROSTATIC/ ENGINE GEARCASE

OIL FILTER (9400 – 9600) – [AH128449](#)

Replace every 400 hours or yearly.

Note: Replace all three filters at a time.



ENGINE

OIL FILTER (9500, 9600) – [RE57394](#)

OIL FILTER (9400) – [T19044](#)

For Engine 6359T Upto MSN (-640100)

OIL FILTER (9400) – [RE59754](#)


For Engine 6068HH050 From MSN (701246 -)

OIL FILTER (9400) – [AH128448](#)

For Upto MSN (-650370)

Replace every 250 hours or once a season, whichever occurs first.

Fill crankcase with seasonal viscosity grade oil or Torq-Gard Supreme™ (250 hours change interval). If using Plus-50™ oil and a John Deere filter, the service interval can be extended by 50 percent.



ENGINE

FUEL FILTER (9500,9600) – [AR86745](#)


FUEL FILTER (9400) – [AR86745](#)

For Engine 6359T Upto MSN (-640100)

FUEL FILTER (9400) – [RE62419](#)

For Engine 6068HH050 From MSN (701246 -)

Replace every 500 hours and as required.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

9000 Walker Series Combines

CAPACITIES (Approximate):

Fuel Tank:

..... 530 L (140 gal)

**Cooling System with Heater:
Cool-Gard™II**

..... 35.5 L (9.4 gal)

**Engine Crankcase with Filter:
Plus-50™II**

9400..... 19 L (5 gal)

9500, 9600..... 25 L (6.7 gal)

**Transmission:
GL-5**

..... 9.6 L (2.5 gal)

**Final Drives (Each):
GL-5**

Ring and Pinion 8.5 L (2.2 gal)

Planetary 6.2 L (1.6 gal)

Feeder House Reverser Gearcase..... 0.9 L (0.2 gal)

Countershaft Drive Gearcase 1.4 L (0.3 gal)

Straw Walker Drive Gearcase 0.7 L (0.2 gal)

Loading Auger Gearcase..... 4.7 L (1.2 gal)

Hydrostatic Drive System:

Torq-Gard™ 10W or Low Viscosity Hy-Gard™

Gearcase 1.9 L (0.5 gal)

Engine Gearcase..... 16 L (4.2 gal)

Hydraulic/Hydrostatic Reservoir 34 L (9 gal)

**Dual-Range Cylinder Drive Gearcase:
GL-5**

..... 1.9 L (0.5 gal)

[Return to Filter Overview](#)

