

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

## 9750 STS Series Canadian Combine

### ENGINE AIR FILTER

SECONDARY AIR FILTER – [AH174196](#)

Change secondary filter only with primary filter.

### ENGINE AIR FILTER

PRIMARY AIR FILTER – [AH170798](#)

Replace every 400 hours or  
Service filters only when engine air filter light stays ON or  
change as required.

Note: Replace secondary filter with primary filter.

### CAB AIR FILTER

RECIRCULATION AIR FILTER – [AH115836](#)

Clean or replace every 200 hours and as required.

### CAB AIR FILTER

AIR FILTER, HEAVY DUTY – [AH168783](#)

AIR FILTER, STANDARD – [AH115833](#)

Clean or replace every 50 hours  
and as required.

### HYDROSTATIC PUMP / ENGINE GEARCASE / HYDRAULIC FILTER

OIL FILTER – [AH128449](#)

Replace every 400 hours.

Note: Replace all three filters at a time.

### ENGINE OIL FILTER

OIL FILTER – [RE58935](#)

Replace every 200 hours.

Fill Crankcase with seasonal viscosity grade  
oil or Torq-Gard™ Supreme (250 hours  
change interval). Change oil every 500 hours  
when using John Deere Plus-50™ II engine  
oil and a John Deere filter.

Note : Change oil every 100 hours if fuel con-  
tains more than 0.5 % sulfur.

### ENGINE FUEL FILTER

FUEL FILTER – [RE507284](#)

Replace every 500 hours.



**JOHN DEERE**

Genuine Parts and Service

(Click here for [capacity](#))

# CAPACITIES

## 9750 STS Series Canadian Combine

### CAPACITIES (Approximate):

#### Fuel Tank:

..... 945 L (249.64 gal)

#### Cooling System with Heater:

##### Cool-Gard™

..... 55 L (14.52 gal)

#### Hydraulic / Hydrostatic Reservoir:

##### Low Viscosity Hy-Gard™

..... 34 L (8.98 gal)

#### Feeder House Reverser Gearcase:

##### GL-5

Standard ..... 0.9 L (0.23 gal)

High Capacity with Cooler ..... 3.5 L (0.92 gal)

#### Final Drives (Each):

##### GL-5

Single Reduction ..... 8.5 L (2.24 gal)

#### Countershaft Drive Gearcase:

##### GL-5

..... 1.2 L (0.31 gal)

#### Loading Auger Gearcase:

##### GL-5

..... 3.8 L (1 gal)

#### Engine Gearcase with Transfer:

##### Low Viscosity Hy-Gard™

..... 21.3 L (5.62 gal)

#### Engine Crankcase with Filter:

##### Torq-Gard Supreme™ or Plus-50™ II

..... 42 L (11.09 gal)

#### Transmission:

##### GL-5

..... 9.6 L (2.53 gal)

#### Two Speed Separator Drive Gearcase:

##### GL-5

..... 4.7 L (1.24 gal)

[Return to Filter Overview](#)

