

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

1E and 1R Series Compact Utility Tractors - 1023E(HJ100001 -), 1025R(HJ100001 -), 1026R(HJ200001 -)

FILTER PAK

(1023E(- JJ117913), 1026R(- JJ202258)) – [LVA21035](#)
M806418, LVA16054, M113621, MIU804763, AM116304

1025R(-JJ153036) – [LVA21036](#)

M806418, LVA16054, AM116304, M131802, MIU804763

(1023E (JJ117914 -), 1025R (JJ153037 -), 1026R (JJ202259 -)) - [TA15270](#)

M806418, LVA16054, AM116304, LVU34503, MIU804763

Each kit contains above filters and offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

ENGINE

INLINE FUEL FILTER - [AM116304](#)

Replace every 400 hours and annually.
(Click here for [capacity](#))

TRANSMISSION

HYDRAULIC FILTER - [LVA16054](#)

Replace after first 50 hours and every 200 hours.
(Click here for [capacity](#))

ENGINE

OIL FILTER - [M806418](#)

Replace every 200 hours and annually if less than 200 hours of operation.
(Click here for [capacity](#))

ENGINE

FUEL FILTER

[MIU804763](#)

Replace every 400 hours and annually.
(Click here for [capacity](#))

ENGINE

PRIMARY AIR FILTER

(1023E(- JJ117913), 1026R(- JJ202258)) – [M113621](#)
(1025R(- JJ153036)) – [M131802](#)
(1023E (JJ117914 -), 1025R (JJ153037 -), 1026R (202259-))
[LVU34503](#)

SECONDARY AIR FILTER

(1023E(- JJ117913), 1026R(- JJ202258)) – [M123378](#)
(1025R(-JJ153036)) – [M131803](#)
(1023E (JJ117914 -), 1025R (JJ153037 -), 1026R (JJ202259 -))
[LVU34504](#)

Replace every 400 hours and as required.
Check and service every 10 hours/daily, every 200 hours and annually. (Service 1025R, 1026R when restriction indicator is red).

(Click here for [capacity](#))



CAPACITIES

1E and 1R Series Compact Utility Tractors - 1023E(HJ100001 -), 1025R(HJ100001 -), 1026R(HJ200001 -)

CAPACITIES (Approximate):

Fuel Tank:

..... 21.2 L (5.6 gal)

Cooling System:

Cool-Gard™ II

..... 3.7 L (0.98 gal)

Crankcase with Filter:

Plus-50™

..... 2.7 L (0.71 gal)

Transmission and Hydraulic System:

Hy-Gard™

..... 12.3 L (3.3 gal)

Front Axle:

Hy-Gard™

..... 2.8 L (0.74 gal)

[Return to Filter Overview](#)

