

**AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS**

**E12 Flex Wing Rotary Cutter
Equipment for Base Machine**

<p>Pull Type 12 Ft. (3.7 m) Cutting Width 2 In. Brush Cutting Capacity Four Gear cases Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 75 HP (55.1 kW) Peak Horsepower Rating: Splitter 300 HP (224 kW) Wing : 100 HP (75 kW) 1-3/4 In. Gear case Input Shafts Xxx in Gear case output shaft Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Tubular Telescoping Driveshaft Members Easy Clean Dome Shaped Welded Wear skid shoes Frames: Deck Thickness: 0.12 in (3 mm) 11 gauge Body Depth 10 In. (276 mm) 1/4 In. (6 mm) Side Skirt Thickness (3 gauge) 3-Section Flexible</p>	<p>90 Degrees Up for transportation Working angles: 22 Degrees Down, 45 Degrees Up Pivot Pins with Single Bushings Grease-able Hinges Blade Tip Speed: 17,047 fpm, (86.6 m/s) Double Leveling Rods for tip adjustment Easy Adjust Wing Leveling Turnbuckles Standard Self Level Hitch Clevis 30 mm Front and Rear Safety Shields - Chains Safety Tow Chain Hitch Integrated Jack Stand Implement Jack SMV Emblem and Support Transport light kit - comply with regulations Fully Assembled Heavy Duty Rating Intermittent, 4-Bolt Wheel Hubs - Four Wheels</p>
--	--

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario

2290P		E12 Flex Wing Rotary Cutter <i>Serial Number 1Y80E12CZJT412000 and above.</i>	15,219.00
-------	--	--	-----------

DESTINATION

0202		United States	In Base Price
0184		Canada	No Added Cost

TIRES

Laminated Tires			
3010		4 Laminated Tires - (Single tires on center and wings) - Puncture proof	-310.00
Severe Duty Tires			
3020		4 Pneumatic Tires - (Single tires on center and wings) - Severe duty ag tires	In Base Price

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9013		French Operator's Manual and Decal Kit	No Added Cost
9037		Spanish Operator's Manual and Decal Kit	No Added Cost

AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS

E12 Flex Wing Rotary Cutter
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		OPERATOR'S MANUAL, DECALS, AND LANGUAGE	
		...Continued...	
9043		Text Free Operator's Manual and Decal Kit	No Added Cost
		BLADES	
9120		Blade Bolt and Bushing Kit <i>Includes 6 bolts, 6 bushings and 6 nuts.</i>	236.00
		INDEPENDENT CONTROL VALVE	
9130		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	909.00
		WING CYLINDER HOSE	
9150		Extra Wing Cylinder Hose	108.00
		Attachment Information is not available in MOCI for the base code 2290P	

**AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS**

**E15 Flex wing Rotary Cutter
Equipment for Base Machine**

Pull Type	90 Degrees Up for transportation
15 Ft. (4.6 m) Cutting Width	Working angles: 22 Degrees Down, 45 Degrees Up
2 In. Brush Cutting Capacity	Pivot Pins with Single Bushings
Four Gear cases	Grease-able Hinges
Continuous Horsepower Rating:	Blade Tip Speed: 17,281 fpm, (87.8 m/s)
Splitter 250 HP (186 kW)	Double Leveling Rods for tip adjustment
Wing 75 HP (55.1 kW)	Easy Adjust Wing Leveling Turnbuckles
Peak Horsepower Rating:	Standard Self Level Hitch Clevis 30 mm
Splitter 300 HP (224 kW)	Front and Rear Safety Shields - Chains
Wing : 100 HP (75 kW)	Safety Tow Chain
1-3/4 In. Gear case Input Shafts	Hitch Integrated Jack Stand
2 in Gear case output shaft	Implement Jack
Constant Velocity and Lock-Slide Collar	SMV Emblem and Support Transport light kit -
Tractor-to-Cutter Driveline	comply with regulations
Three Slip Clutches,	Fully Assembled Heavy Duty Rating Intermittent,
Tubular Telescoping Driveshaft Members	4-Bolt Wheel Hubs - Four Wheels
Easy Clean Dome Shaped	
Welded Wear skid shoes	
Frames:	
Deck Thickness: 0.12 in (3 mm) 11 gauge	
Body Depth 10 In. (276 mm)	
1/4 In. (6 mm) Side Skirt Thickness (3 gauge)	
3-Section Flexible	

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario

230AP	E15 Flex wing Rotary Cutter <i>Serial Number 1Y80E15CZJT414000 and above</i>	18,447.00
-------	---	-----------

DESTINATION

0202	United States	In Base Price
0184	Canada	No Added Cost

TIRES

Laminated Tires		
3010	4 Laminated Tires - (Single tires on center and wings) - Puncture proof	-310.00
3015	6 Laminated Tires - (Double center, single on wings) - Puncture proof <i>For E15, M15, M20, R15, R20 - 6 tires (Double center , single on wing)</i>	464.00
Severe Duty Tires		
3020	4 Pneumatic Tires - (Single tires on center and wings) - Severe duty ag tires	In Base Price
3025	6 Pneumatic Tires - (Double center, single on wings) - Severe duty ag tires <i>For E15, M15, M20, R15, R20 - 6 tires (Double center , single on wing)</i>	924.00

AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS

E15 Flex wing Rotary Cutter
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
OPERATOR'S MANUAL, DECALS, AND LANGUAGE			
9013		French Operator's Manual and Decal Kit	No Added Cost
9037		Spanish Operator's Manual and Decal Kit	No Added Cost
9043		Text Free Operator's Manual and Decal Kit	No Added Cost
BLADES			
9120		Blade Bolt and Bushing Kit <i>Includes 6 bolts, 6 bushings and 6 nuts.</i>	236.00
INDEPENDENT CONTROL VALVE			
9130		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	909.00
WING CYLINDER HOSE			
9150		Extra Wing Cylinder Hose	108.00
Attachment Information is not available in MOCI for the base code 230AP			

**AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS**

**M15 Flex Wing Rotary Cutter
Equipment for Base Machine**

Pull Type
 15 Ft. (4.6 m) Cutting Width
 3 In. Brush Cutting Capacity
 Four Gear cases
 Continuous Horsepower Rating:
 Splitter 250 HP (186 kW)
 Wing : 100 HP (75 kW)
 Peak Horsepower Rating:
 Splitter 300 HP (224 kW)
 Wing 210 HP (157 kW)
 1-3/4 In. Gear case Input Shafts
 2.35 in Gear case output shaft
 Constant Velocity and Lock-Slide Collar
 Tractor-to-Cutter Driveline
 Three Slip Clutches,
 Tubular Telescoping Driveshaft Members
 Easy Clean Dome Shaped
 Replaceable bolt on Wear skid shoes
 Frames:
 Deck Thickness: 0.14 in (3.5 mm) 10 gauge
 Body Depth 10 In. (276 mm)
 1/4 In. (6 mm) Side Skirt Thickness (3 gauge)
 3-Section Flexible
 90 Degrees Up for transportation

Working angles: 22 Degrees Down, 45 Degrees Up
 Pivot Pins with Single Bushings
 Grease-able Hinges
 Blade Tip Speed:
 540 rpm: 15,586 fpm, (79.2 m/s)
 1000 rpm: 15,837 fpm, (80.5 m/s)
 Double Leveling Rods for tip adjustment
 Easy Adjust Wing Leveling Turnbuckles
 Front and Rear Safety Shields single row chains
 Safety Tow Chain
 Hitch Integrated Jack Stand (on rigid casting hitch)
 Implement Jack
 SMV Emblem and Support Transport light kit - comply with regulations
 Fully Assembled Heavy Duty Rating Intermittent,
 4-Bolt Wheel Hubs - Six Wheels

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario

2310P	M15 Flex Wing Rotary Cutter <i>Serial Number 1Y80M15CZJE416000 and above.</i>	24,329.00
-------	--	-----------

DESTINATION

0202	United States	In Base Price
0184	Canada	No Added Cost

BLADE ROTATION

2540	Outward Rotation <i>This configuration will deliver an improvement on material dispersion along the width of the machine. Outward rotations is new for the E M and R specs.</i>	No Added Cost
2541	Inward Rotation <i>This configuration of inward rotation is what you had on the HX and CX models, you could expect the same cut quality and material distribution as previous models. Option only available for M15 and R15</i>	In Base Price

GEARBOX

3600	540 RPM -100 hp Gearbox	In Base Price
------	-------------------------	---------------

AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS

M15 Flex Wing Rotary Cutter
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GEARBOX ...Continued...			
3601		540 RPM - 100 hp Gearbox - Inward rotation	No Added Cost
3602		540 RPM - 125 hp Gearbox - Commercial duty	691.00
3603		540 RPM - 125 hp Gearbox - Commercial duty - Inward rotation	691.00
3639		1000 RPM - 100 hp Gearbox	No Added Cost
3640		1000 RPM - 100 hp Gearbox - Inward rotation	No Added Cost
3641		1000 RPM - 125 hp Gearbox - Commercial duty	691.00
3642		1000 rpm - 125 hp Gearbox - Commercial duty - Inward rotation	691.00
DRIVELINES			
3510		540 RPM Driveline	In Base Price
3511		540 RPM Driveline - Cat 6	No Added Cost
3539		1000 RPM Driveline - 1 3/8" coupler	No Added Cost
3541		1000 RPM Driveline - 1 3/8" coupler - Cat 6	No Added Cost
3543		1000 RPM Driveline - 1 3/4" coupler	50.00
3545		1000 RPM Driveline - 1 3/4" coupler - Cat 6	50.00
BLADE HOLDER			
2500		Blade Pan	In Base Price
2501		Blade Pan - 125 hp	No Added Cost
2502		Blade Bar - Double blade	719.00
SUSPENSION			
1200		Spring Suspension	In Base Price
1210		Torsional Suspension	906.00
TONGUE			
5280		Rigid Casting Tongue	In Base Price
5290		Suspended Tongue	718.00
HITCH			
5110		Clevis Hitch	In Base Price
5120		Ball Type Hitch	277.00
5140		Swivel Hitch	459.00
TIRES			

AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS

M15 Flex Wing Rotary Cutter
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
TIRES ...Continued...			
Laminated Tires			
3015		6 Laminated Tires - (Double center, single on wings) - Puncture proof <i>For E15, M15, M20, R15, R20 - 6 tires (Double center , single on wing)</i>	-460.00
3315		8 Laminated Tires - (Double tires on center and wings) - Puncture proof <i>For M15, M20, R15, R20 - 8 tires (Double tires on center and wings)</i>	313.00
Severe Duty Tires			
3025		6 Pneumatic Tires - (Double center, single on wings) - Severe duty ag tires <i>For E15, M15, M20, R15, R20 - 6 tires (Double center , single on wing)</i>	In Base Price
3325		8 Pneumatic Tires - (Double tires on center and wings) - Severe duty ag tires <i>For M15, M20, R15, R20 - 8 tires (Double tires on center and wings)</i>	923.00
Foam Filled Tires			
3035		6 Foam-Filled Tires - (Double center, single on wings) - Severe duty ag tires <i>For M15, M20, R15, R20 - 6 tires (Double center , single on wing)</i>	366.00
3335		8 Foam-Filled Tires - (Double tires on center and wings) - Severe duty ag tires <i>For M15, M20, R15, R20 - 8 tires (Double tires on center and wings)</i>	1,402.00
OPERATOR'S MANUAL, DECALS, AND LANGUAGE			
9013		French Operator's Manual and Decal Kit	No Added Cost
9037		Spanish Operator's Manual and Decal Kit	No Added Cost
9043		Text Free Operator's Manual and Decal Kit	No Added Cost
BLADES			
9120		Blade Bolt and Bushing Kit <i>Includes 6 bolts, 6 bushings and 6 nuts.</i>	236.00
WALKING TANDEM			
9300		Walking Tandem Kit <i>Kit just for center section. For full coverage, order 1 additional kit and 2 additional tires/dual tires on wings. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,047.00
INDEPENDENT CONTROL VALVE			
9130		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	909.00
WING CYLINDER HOSE			
9150		Extra Wing Cylinder Hose	108.00

AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS

M15 Flex Wing Rotary Cutter
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Attachment Information is not available in MOCI for the base code 2310P

**AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS**

**M20 Flex wing Rotary Cutter
Equipment for Base Machine**

<p>Pull Type 20 Ft. (6.1 m) Cutting Width 3 In. Brush Cutting Capacity Four Gear cases Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing : 100 HP (75 kW) Peak Horsepower Rating: Splitter 300 HP (224 kW) Wing 210 HP (157 kW) 1-3/4 In. Gear case Input Shafts 2.35 in Gear case output shaft Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Tubular Telescoping Driveshaft Members Easy Clean Dome Shaped Replaceable bolt on Wear skid shoes Frames: Deck Thickness: 0.14 in (3.5 mm) 10 gauge Body Depth 10 In. (276 mm) 1/4 In. (6 mm) Side Skirt Thickness (3 gauge) 3-Section Flexible 90 Degrees Up for transportation</p>	<p>Working angles: 22 Degrees Down, 45 Degrees Up Pivot Pins with Single Bushings Grease-able Hinges Blade Tip Speed: 540 rpm: 16,087 fpm, (81.7 m/s) 1000 rpm: 16,346 fpm, (83.5 m/s) Double Leveling Rods for tip adjustment Easy Adjust Wing Leveling Turnbuckles Front and Rear Safety Shields single row chains Safety Tow Chain Hitch Integrated Jack Stand (on rigid casting hitch) Implement Jack SMV Emblem and Support Transport light kit - comply with regulations Fully Assembled Heavy Duty Rating Intermittent, 4-Bolt Wheel Hubs - Six Wheels</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario

2320P	M20 Flex wing Rotary Cutter	Serial Number 1Y80M20FZJE418000 and above	31,339.00
-------	-----------------------------	---	-----------

DESTINATION

0202	United States		In Base Price
0184	Canada		No Added Cost

GEARBOX

3600	540 RPM -100 hp Gearbox		No Added Cost
3602	540 RPM - 125 hp Gearbox - Commercial duty		691.00
3639	1000 RPM - 100 hp Gearbox		In Base Price
3641	1000 RPM - 125 hp Gearbox - Commercial duty		691.00

DRIVELINES

3510	540 RPM Driveline		No Added Cost
3511	540 RPM Driveline - Cat 6		No Added Cost

AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS

M20 Flex wing Rotary Cutter
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DRIVELINES ...Continued...			
3539		1000 RPM Driveline - 1 3/8" coupler	In Base Price
3541		1000 RPM Driveline - 1 3/8" coupler - Cat 6	No Added Cost
3543		1000 RPM Driveline - 1 3/4" coupler	50.00
3545		1000 RPM Driveline - 1 3/4" coupler - Cat 6	50.00
BLADE HOLDER			
2500		Blade Pan	In Base Price
2501		Blade Pan - 125 hp	No Added Cost
2502		Blade Bar - Double blade	719.00
SUSPENSION			
1200		Spring Suspension	In Base Price
1210		Torsional Suspension	906.00
TONGUE			
5280		Rigid Casting Tongue	In Base Price
5290		Suspended Tongue	718.00
HITCH			
5110		Clevis Hitch	In Base Price
5120		Ball Type Hitch	277.00
TIRES			
Laminated Tires			
3015		6 Laminated Tires - (Double center, single on wings) - Puncture proof <i>For E15, M15, M20, R15, R20 - 6 tires (Double center, single on wing)</i>	-460.00
3315		8 Laminated Tires - (Double tires on center and wings) - Puncture proof <i>For M15, M20, R15, R20 - 8 tires (Double tires on center and wings)</i>	313.00
Severe Duty Tires			
3025		6 Pneumatic Tires - (Double center, single on wings) - Severe duty ag tires <i>For E15, M15, M20, R15, R20 - 6 tires (Double center, single on wing)</i>	In Base Price
3325		8 Pneumatic Tires - (Double tires on center and wings) - Severe duty ag tires <i>For M15, M20, R15, R20 - 8 tires (Double tires on center and wings)</i>	923.00
Foam Filled Tires			
3035		6 Foam-Filled Tires - (Double center, single on wings) - Severe duty ag tires <i>For M15, M20, R15, R20 - 6 tires (Double center, single on wing)</i>	366.00

AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS

M20 Flex wing Rotary Cutter
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
3335		TIRES ...Continued... 8 Foam-Filled Tires - (Double tires on center and wings) - Severe duty ag tires <i>For M15, M20, R15, R20 - 8 tires (Double tires on center and wings)</i>	1,402.00
<hr/>			
OPERATOR'S MANUAL, DECALS, AND LANGUAGE			
9013		French Operator's Manual and Decal Kit	No Added Cost
9037		Spanish Operator's Manual and Decal Kit	No Added Cost
9043		Text Free Operator's Manual and Decal Kit	No Added Cost
BLADES			
9120		Blade Bolt and Bushing Kit <i>Includes 6 bolts, 6 bushings and 6 nuts.</i>	236.00
SHREDDING KIT			
9200		Shredding Kit <i>It is a diamond base to attach on the blade bar and add 4 more blades to each blade bar configuration, resulting in 8 blades per spindle.</i>	1,749.00
WALKING TANDEM			
9300		Walking Tandem Kit <i>Kit just for center section. For full coverage, order 1 additional kit and 2 additional tires/dual tires on wings. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,047.00
INDEPENDENT CONTROL VALVE			
9130		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	909.00
WING CYLINDER HOSE			
9150		Extra Wing Cylinder Hose	108.00
 Attachment Information is not available in MOCI for the base code 2320P			

AGRICULTURAL PRODUCTS
FLEX-WING ROTARY CUTTERS

M20 Flex wing Rotary Cutter
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**MX5 Lift-Type Rotary Cutter - 540 RPM PTO
Equipment for Base Machine**

<p>Smooth, Easy Clean, Top Deck Deck Thickness: Upper Deck - 1/8 In. (3.0 mm) Lower Deck - 1/8 In. (3.0 mm) Total - 1/4" (6.0 mm) One Gearcase, Power Rating: 75 HP (56 kW) Continuous 90 HP (67 kW) Peak 2 In. Brush Cutting Capacity Slip Clutch Protection Unibody Frame: 8.5 In. (216 mm) Body Depth 1/4 In. (6.0 mm) Skirt Thickness Cutting Width: 60 In. (1.52 m) Transport Width: 65 In. (1.62 m) Cutting Height: 1 to 9.5 In. (25 - 241 mm) Blade Tip Speed: 14121 ft/min (71.7 m/s) Hitch: Integral Hitch (Category I, Convertible to II, 3-Point Hitch with or without Quick Coupler) Weld on Full Length Wear Shoes - Replaceable Driveline:</p>	<p>Standard Driveline (Category 3) - 540 RPM PTO Round Pan Bladeholder (Stump Jumper) Suction Blades (1/2 In. x 4 In.) One Wheel Support (Swiveling, Height Adjustable) One Puncture Proof Laminated Tire Front Safety Shield - Chain Rear Safety Shield - Chain Minimum Recommended Tractor PTO HP: 25 HP; 4300 or equivalent</p> <p>Note: Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.</p>
--	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario

2134P	<p>MX5 Lift-Type Rotary Cutter - 540 RPM PTO <i>Order Code 9020 for Quick Coupler Compatibility. Order Code 9030 for Conversion to Category II. If ordering for use with the iMatch Auto-Hitch, you will need to shorten the rotary cutter driveline according to the iMatch Auto-Hitch instructions. Serial Number P00MX5C016000 and above.</i></p>	3,087.00
-------	--	----------

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099	French Operator's Manual and Decal Kit	No Charge
9100	Spanish Operator's Manual and Decal Kit	No Charge

HITCH ADAPTERS

9020	iMatch / Quik-Coupler Bushing Kit	98.00
9030	Category II Conversion Kit	157.00

Attachment Information is not available in MOCI for the base code 2134P

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX5 Lift-Type Rotary Cutter - 540 RPM PTO
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

MX6 Lift-Type Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

<p>Deck Thickness: Upper Deck - 9/64 In. (3.5 mm) Lower Deck - 9/64 In. (3.5 mm) Total - 9/32 In. (7.0 mm) One Gearcase, Power Rating: 75 HP (56 kW) Continuous 90 HP (67 kW) Peak 2 In. Brush Cutting Capacity Slip Clutch Protection Unibody Frame: 8.5 In. (216 mm) Body Depth 1/4 In. (6.0 mm) Skirt Thickness Cutting Width: 72 In. (1.83 m) Transport Width: 75 In. (1.91 m) Cutting Height: 1 to 9.5 In. (25 - 241 mm) Blade Tip Speed: 17416 ft/min (88.5 m/s) Hitch: Integral Hitch (Category I Convertible to II, 3-Point Hitch with or without Quick Coupler) Weld on Full Length Wear Shoes - Replaceable Driveline:</p>	<p>Standard Driveline (Category 3) - 540 RPM PTO Round Pan Bladeholder (Stump Jumper) Suction Blades (1/2 In. x 4 In.) One Wheel Support (Swiveling, Height Adjustable) One Puncture Proof Laminated Tire Front Safety Shield - Chain Rear Safety Shield - Chain Minimum Recommended Tractor PTO HP: 30 HP; 4500 or equivalent</p> <p>Note: Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario

2144P		MX6 Lift-Type Rotary Cutter - 540 RPM PTO <i>Order Code 9020 for Quick Coupler Compatibility. Order Code 9030 for Conversion to Category II. If ordering for use with the iMatch Auto-Hitch, you will need to shorten the rotary cutter driveline according to the iMatch Auto-Hitch instructions. Serial Number P00MX6C034000 and above.</i>	3,584.00
-------	--	---	----------

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

HITCH ADAPTERS

9020		iMatch / Quik-Coupler Bushing Kit	98.00
9030		Category II Conversion Kit	157.00

Attachment Information is not available in MOCI for the base code 2144P

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX6 Lift-Type Rotary Cutter - 540 RPM PTO
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**MX7 Lift-Type Rotary Cutter - 540 RPM PTO
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck
Deck Thickness:
Upper Deck - 9/64 In. (3.5 mm)
Lower Deck - 9/64 In. (3.5 mm)
Total - 9/32 In. (7.0 mm)

One Gearcase, Power Rating:
75 HP (56 kW) Continuous
100 HP (74.5 kW) Peak
2 In. Brush Cutting Capacity
Slip Clutch Protection

Unibody Frame:
8.5 In. (216 mm) Body Depth
1/4 In. (6.0 mm) Skirt Thickness
Cutting Width: 84 In. (2.13 m)
Transport Width: 88 In. (2.24 m)
Cutting Height: 1 to 9.5 In. (25 - 241 mm)
Blade Tip Speed: 16182 ft/min (82.2 m/s)

Hitch:
Integral Hitch (Category II and IIIN 3-Point
Hitch with or without Quick Coupler)
Weld on Full Length Wear Shoes - Replaceable
Driveline:

Standard Driveline (Category 4)
- 540 RPM PTO
Round Pan Bladeholder (Stump Jumper)
Suction Blades (1/2 In. x 4 In.)
One Wheel Support (Swiveling,
Height Adjustable)
One Puncture Proof Laminated Tire
Front Safety Shield - Chain
Rear Safety Shield - Chain
Minimum Recommended Tractor PTO HP:
40 HP; 4 cylinder 5000 Series or equivalent

Note: Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario

2154P		MX7 Lift-Type Rotary Cutter - 540 RPM PTO <i>Order Code 9020 for Quick Coupler Compatibility. Serial Number P00MX7C017500 and above.</i>	4,731.00
-------	--	---	----------

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

DUAL TAIL WHEEL SUPPORT

9010		Dual Tailwheel Support, Hub and Wheel <i>Includes the following components: 1 AW30473 -dual tail wheel support and hub 1 AW30715 -4X8 Bolt Wheel Hub- Puncture Proof Laminated Tire.</i>	410.00
------	--	---	--------

HITCH ADAPTERS

9020		iMatch / Quik-Coupler Bushing Kit	98.00
------	--	-----------------------------------	-------

Attachment Information is not available in MOCI for the base code 2154P

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX7 Lift-Type Rotary Cutter - 540 RPM PTO
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX8 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

Smooth, Easy Clean, Top Deck
Deck Thickness:
Upper Deck - 1/8" (3.0 mm)
Lower Deck - 1/8" (3.0 mm)
Total - 1/4" (6.0 mm)
Three Gearcases, Power Ratings:
Center - 120 Continuous HP (88.2 kW);
Outer - 75 Continuous HP (55.1 kW);
2 In. Brush Cutting Capacity
Shock Absorbing Cross Shafts
Slip Clutch Protection
Unibody Frame:
8.5 In. (216 mm) Body Depth
3/16 In. (4.5 mm) Skirt Thickness
Cutting Width: 96 In. (2.44 m)
Transport Width: 102 In. (2.58 m)
Cutting Height: 1 to 12 In. (25 - 305 mm)
Blade Tip Speed: 15739 ft/min (80 m/s)
Weld on Full Length Wear Shoes
Minimum Recommended Tractor PTO HP: 40 HP
Standard Driveline with Lock Slide Collar
(Equal Angle, Cat.4) - 540 RPM PTO
Level Lift

Round Pan Bladeholder (Stump Jumper)
Suction Blades (1/2 In. x 4 In.)
Two Wheel Supports (Swiveling and Row Width Adjustable)
Two Puncture Proof Laminated Tires
Front Safety Shield - Chain
Rear Safety Shield - Chain
Safety Tow Chain
Jack with Mounting Brackets
Lift Cylinder and Hose
Lift Cylinder Depth Stops

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

216AP		MX8 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number P00MX8E018000 and above.</i>	9,422.00
-------	--	---	----------

TIRES

1210		Laminated Tires Two 533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Puncture Proof Laminated Tires	In Base Price
1230		Severe Duty Tires Two 304.8 mm (12 in.) wheels with 533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tires	151.00

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

THIRD OR FOURTH PULL-TYPE WHEEL

9010		MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	253.00
------	--	--	--------

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX8 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
THIRD OR FOURTH PULL-TYPE WHEEL ...Continued...			
TIRES			
		Laminated Tires	
9030		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	135.00
		Severe Duty Tires	
9045		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	218.00
LIGHTING			
9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	663.00
SMV EMBLEM AND SUPPORT			
9080		SMV Emblem and Support <i>Includes the following components:</i> <i>1 BW10809 - SMV Emblem</i> <i>1 BW14053 - Support Assembly</i>	63.00

Attachment Information is not available in MOCI for the base code 216AP

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

MX8 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

Smooth, Easy Clean, Top Deck
Deck Thickness:
Upper Deck - 1/8" (3.0 mm)
Lower Deck - 1/8" (3.0 mm)
Total - 1/4" (6.0 mm)
Three Gearcases, Power Ratings:
Center - 120 Continuous HP (88.2 kW);
Outer - 75 Continuous HP (55.1 kW);
2 In. Brush Cutting Capacity
Shock Absorbing Cross Shafts
Slip Clutch Protection
Unibody Frame:
8.5 In. (216 mm) Body Depth
3/16 In. (4.5 mm) Skirt Thickness
Cutting Width: 96 In. (2.44 m)
Transport Width: 102 In. (2.58 m)
Cutting Height: 1 to 12 In. (25 - 305 mm)
Blade Tip Speed: 15739 ft/min (80 m/s)
Weld on Full Length Wear Shoes
Minimum Recommended Tractor PTO HP:
4 cyl. 5000 Series or equivalent
Standard Driveline with Lock Slide Collar

(Cat. 4) - 540 RPM 1-3/8 PTO
Hitch (Cat. II, III and IIIN 3-Point Hitch with or without Quick Coupler)
Round Pan Bladeholder (Stump Jumper)
Suction Blades (1/2 In. x 4 In.)
Two Wheel Supports (Swiveling, Height Adjustable)
Two Puncture Proof Laminated Tires
Front Safety Shield - Chain
Rear Safety Shield - Chain

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

216BP	MX8 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number P00MX8C018000 and above.</i>	7,443.00
-------	---	----------

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099	French Operator's Manual and Decal Kit	No Charge
9100	Spanish Operator's Manual and Decal Kit	No Charge

LIGHTING

9060	Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	663.00
------	--	--------

SMV EMBLEM AND SUPPORT

9080	SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	63.00
------	---	-------

Attachment Information is not available in MOCI for the base code 216BP

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX8 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

MX8 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

Smooth, Easy Clean, Top Deck
Deck Thickness:
Upper Deck - 1/8" (3.0 mm)
Lower Deck - 1/8" (3.0 mm)
Total - 1/4" (6.0 mm)
Three Gearcases, Power Ratings:
Center - 120 Continuous HP (88.2 kW);
Outer - 75 Continuous HP (55.1 kW);
2 In. Brush Cutting Capacity
Shock Absorbing Cross Shafts
Slip Clutch Protection
Unibody Frame:
8.5 In. (216 mm) Body Depth
3/16 In. (4.5 mm) Skirt Thickness
Cutting Width: 96 In. (2.44 m)
Transport Width: 102 In. (2.58 m)
Cutting Height: 1 to 12 In. (25 - 305 mm)
Blade Tip Speed: 15739 ft/min (80 m/s)
Weld on Full Length Wear Shoes
Minimum Recommended Tractor PTO HP: 40 HP
Standard Driveline with Lock Slide Collar

(Cat. 4) - 540 RPM PTO
Round Pan Bladeholder (Stump Jumper)
Suction Blades (1/2 In. x 4 In.)
Two Wheel Supports (Swiveling and Row Width Adjustable)
Two Puncture Proof Laminated Tires
Front Safety Shield - Chain
Rear Safety Shield - Chain
Lift Cylinder and Hose
Lift Cylinder Depth Stops

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

216CP		MX8 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number P00MX8H018000 and above.</i>	7,585.00
-------	--	--	----------

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

LIGHTING

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	663.00
------	--	--	--------

SMV EMBLEM AND SUPPORT

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	63.00
------	--	---	-------

Attachment Information is not available in MOCI for the base code 216CP

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX8 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

MX8 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

Smooth, Easy Clean, Top Deck
Deck Thickness:
 Upper Deck - 1/8" (3.0 mm)
 Lower Deck - 1/8" (3.0 mm)
 Total - 1/4" (6.0mm)
Three Gearcases, Power Ratings:
 Center - 120 Continuous HP (88.2 kW);
 Outer - 75 Continuous HP (55.1 kW);
2 In. Brush Cutting Capacity
Shock Absorbing Cross Shafts
Slip Clutch Protection
Unibody Frame:
 8.5 In. (216mm) Body Depth
 3/16 In. (4.5mm) Skirt Thickness
Cutting Width: 96 In. (2.44 m)
Transport Width: 102 In. (2.58 m)
Cutting Height: 1 to 12 In. (25 - 305 mm)
Blade Tip Speed: 15739 ft/min (80 m/s)
Weld on Full Length Wear Shoes
Minimum Recommended Tractor PTO HP: 40 HP
Offset: 0-13" RIGHT or LEFT
Standard Driveline with Lock Slide Collar

(Cat. 4) - 540 RPM PTO
Round Pan Bladeholder (Stump Jumper)
Suction Blades (1/2 In. x 4 In.)
Two Wheel Supports (Swiveling and Row Width Adjustable)
Two Puncture Proof Laminated Tires
Front Safety Shield - Chain
Rear Safety Shield - Chain
Offset Cylinder and Hoses
Lift Cylinder and Hose
Lift Cylinder Depth Stops

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

216DP		MX8 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO <i>Serial Number P00MX8G018000 and above.</i>	8,812.00
-------	--	--	----------

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

LIGHTING

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	663.00
------	--	--	--------

SMV EMBLEM AND SUPPORT

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	63.00
------	--	---	-------

Attachment Information is not available in MOCI for the base code 216DP

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX8 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

MX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

Smooth, Easy Clean, Top Deck

Deck Thickness:

- Upper Deck - 1/8" (3.0 mm)
- Lower Deck - 1/8" (3.0 mm)
- Total - 1/4" (6.0 mm)

Three Gearcases, Power Ratings:

- Center - 120 Continuous HP (88.2 kW);
- Outer - 75 Continuous HP (55.1 kW);

2 In. Brush Cutting Capacity

Shock Absorbing Cross Shafts

Slip Clutch Protection

Unibody Frame:

- 8.5 In. (216 mm) Body Depth
- 3/16 In. (4.5 mm) Skirt Thickness

Cutting Width: 125.5 In. (3.19 m)

Transport Width: 129 In. (3.28 m)

Cutting Height: 1 to 12 In. (25 - 305 mm)

Blade Tip Speed: 16275 ft/min (82.7 m/s)

Weld on Full Length Wear Shoes

Minimum Recommended Tractor PTO HP: 40 HP

Standard Driveline with Lock Slide Collar

- (Equal Angle, Cat.4) - 540 RPM PTO

Level Lift

Round Pan Bladeholder (Stump Jumper)

Suction Blades (1/2 In. x 4 In.)

Two Wheel Supports (Swiveling and Row Width Adjustable)

Two Puncture Proof Laminated Tires

Front Safety Shield - Chain

Rear Safety Shield - Chain

Safety Tow Chain

Jack with Mounting Brackets

Lift Cylinder and Hose

Lift Cylinder Depth Stops

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

217AP		MX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number POMX10E0170000 and above.</i>	10,144.00
-------	--	---	-----------

TIRES

1210		Laminated Tires Two 533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Puncture Proof Laminated Tires	In Base Price
------	--	--	---------------

1230		Severe Duty Tires Two 304.8 mm (12 in.) wheels with 533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tires	151.00
------	--	---	--------

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

THIRD OR FOURTH PULL-TYPE WHEEL

9010		MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	253.00
------	--	--	--------

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
THIRD OR FOURTH PULL-TYPE WHEEL ...Continued...			
TIRES			
		Laminated Tires	
9030		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	135.00
		Severe Duty Tires	
9045		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	218.00
LIGHTING			
9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	663.00
SMV EMBLEM AND SUPPORT			
9080		SMV Emblem and Support <i>Includes the following components:</i> <i>1 BW10809 - SMV Emblem</i> <i>1 BW14053 - Support Assembly</i>	63.00

Attachment Information is not available in MOCI for the base code 217AP

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

MX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

Smooth, Easy Clean, Top Deck

Deck Thickness:

- Upper Deck - 1/8" (3.0 mm)
- Lower Deck - 1/8" (3.0 mm)
- Total - 1/4" (6.0 mm)

Three Gearcases, Power Ratings:

- Center - 120 Continuous HP (88.2 kW);
- Outer - 75 Continuous HP (55.1 kW);

2 In. Brush Cutting Capacity

Shock Absorbing Cross Shafts

Slip Clutch Protection

Unibody Frame:

- 8.5 In. (216 mm) Body Depth
- 3/16 In. (4.5 mm) Skirt Thickness

Cutting Width: 125.5 In. (3.19 m)

Transport Width: 129 In. (3.28 m)

Cutting Height: 1 to 12 In. (25 - 305 mm)

Blade Tip Speed: 16275 ft/min (82.7 m/s)

Weld on Full Length Wear Shoes

Minimum Recommended Tractor PTO HP:

- 6000 Series or equivalent

Standard Driveline with Lock Slide Collar (Cat. 4)
- 540 RPM 1-3/8 PTO

Hitch (Cat. II, III and IIIN 3-Point Hitch
with or without Quick Coupler)

Round Pan Bladeholder (Stump Jumper)

Suction Blades (1/2 In. x 4 In.)

Two Wheel Supports (Swiveling, Height Adjustable)

Two Puncture Proof Laminated Tires

Front Safety Shield - Chain

Rear Safety Shield - Chain

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

217BP		MX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number POMX10C017000 and above.</i>	8,716.00
-------	--	--	----------

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

LIGHTING

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	663.00
------	--	--	--------

SMV EMBLEM AND SUPPORT

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	63.00
------	--	---	-------

Attachment Information is not available in MOCI for the base code 217BP

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX10 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

Smooth, Easy Clean, Top Deck
Deck Thickness:
Upper Deck - 1/8" (3.0 mm)
Lower Deck - 1/8" (3.0 mm)
Total - 1/4" (6.0mm)
Three Gearcases, Power Ratings:
Center - 120 Continuous HP (88.2 kW);
Outer - 75 Continuous HP (55.1 kW);
2 In. Brush Cutting Capacity
Shock Absorbing Cross Shafts
Slip Clutch Protection
Unibody Frame:
8.5 In. (216 mm) Body Depth
3/16 In. (4.5 mm) Skirt Thickness
Cutting Width: 125.5 In. (3.19 m)
Transport Width: 129 In. (3.28 m)
Cutting Height: 1 to 12 In. (25 - 305 mm)
Blade Tip Speed: 16275 ft/min (82.7 m/s)
Weld on Full Length Wear Shoes
Minimum Recommended Tractor PTO HP: 40 HP
Standard 217CP with Lock Slide Collar (Cat. 4) -

540 RPM PTO
Round Pan Bladeholder (Stump Jumper)
Suction Blades (1/2 In. x 4 In.)
Two Wheel Supports (Swiveling and Row Width Adjustable)
Two Puncture Proof Laminated Tires
Front Safety Shield - Chain
Rear Safety Shield - Chain
Lift Cylinder and Hose
Lift Cylinder Depth Stops

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

217CP		MX10 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number P00MX10H017000 and above.</i>	8,701.00
-------	--	--	----------

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

LIGHTING

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	663.00
------	--	--	--------

SMV EMBLEM AND SUPPORT

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	63.00
------	--	---	-------

HOMOLOGATION KITS

9070		Semi-mount extension brackets <i>Order when attaching a semi-mount machine to a tractor with a three-point hitch only</i>	127.00
------	--	--	--------

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX10 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Attachment Information is not available in MOCI for the base code 217CP

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

MX10 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

Smooth, Easy Clean, Top Deck

Deck Thickness:

- Upper Deck - 1/8" (3.0 mm)
- Lower Deck - 1/8" (3.0 mm)
- Total - 1/4" (6.0 mm)

Three Gearcases, Power Ratings:

- Center - 120 Continuous HP (88.2 kW);
- Outer - 75 Continuous HP (55.1 kW);

2 In. Brush Cutting Capacity

Shock Absorbing Cross Shafts

Slip Clutch Protection

Unibody Frame:

- 8.5 In. (216 mm) Body Depth
- 3/16 In. (4.5 mm) Skirt Thickness

Cutting Width: 125.5 In. (3.19 m)

Transport Width: 129 In. (3.28 m)

Cutting Height: 1 to 12 In. (25 - 305 mm)

Blade Tip Speed: 16275 ft/min (82.7 m/s)

Weld on Full Length Wear Shoes

Minimum Recommended Tractor PTO HP: 40 HP

Offset: 0-13" RIGHT or LEFT

Standard Driveline with Lock Slide Collar (Cat. 4)

- 540 RPM PTO

Round Pan Bladeholder (Stump Jumper)

Suction Blades (1/2 In. x 4 In.)

Two Wheel Supports (Swiveling and Row Width Adjustable)

Two Puncture Proof Laminated Tires

Front Safety Shield - Chain

Rear Safety Shield - Chain

Offset Cylinder and Hoses

Lift Cylinder and Hose

Lift Cylinder Depth Stops

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

217DP		MX10 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO <i>Serial Number POMX10G017000 and above.</i>	10,122.00
-------	--	---	-----------

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

LIGHTING

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	663.00
------	--	--	--------

SMV EMBLEM AND SUPPORT

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	63.00
------	--	---	-------

Attachment Information is not available in MOCI for the base code 217DP

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

MX10 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

HX6 Lift-Type Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

1.83-m (72-in.) cutting width
10.16-cm (4-in.) brush cutting capacity
Heavy-duty construction
Smooth, easy clean, top deck
Deck thickness: Upper deck - 3.0-mm (0.118-in.),
lower deck - 3.5-mm (0.138-in.), total - 6.5-mm
(0.256-in.)
One gear case, power rating: 112-kW (150-hp)
continuous, 153-kW (205-hp) peak
Category 2 or 3N
Slip clutch protection
Shielded driveline with lock slide collar - 540
revolutions per minute (RPM)

Suction blades 1.27-cm x 10.16-cm (0.5-in. x 4-in.)
One wheel support (swiveling, height adjustable)
One puncture proof laminated tire
Safety shields - front and rear chain
Less safety chain
Round pan blade holder (stump jumper)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

219HP		HX6 Lift-Type Rotary Cutter - 540 RPM PTO <i>(with Stump Jumper and Single Suction Blades)</i>	6,490.00
-------	--	---	----------

DESTINATION

0202		North America United States of America	In Base Price
0184		Canada	No Added Cost

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
------	--	--	-----------

Attachment Information is not available in MOCI for the base code 219HP

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

HX6 Lift-Type Rotary Cutter - 540 RPM PTO
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

HX7 Lift-Type Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

2.130-m (84-in.) cutting width
10.16-cm (4-in.) brush cutting capacity
Heavy-duty construction
Smooth, easy clean, top deck
Deck thickness: Upper deck - 3.0-mm (0.118-in.),
lower deck - 3.5-mm (0.138-in.), total - 6.5-mm
(0.256-in.)
One gear case, power rating: 112-kW (150-hp)
continuous, 153-kW (205-hp) peak
Category 2 or 3N
Slip clutch protection
Shielded driveline with lock slide collar - 540
revolutions per minute (RPM)

Suction blades 1.27-cm x 10.16-cm (0.5-in. x 4-in.)
One wheel support (swiveling, height adjustable)
One puncture proof laminated tire
Safety shields - front and rear chain
Less safety chain
Round pan blade holder (stump jumper)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

220HP		HX7 Lift-Type Rotary Cutter - 540 RPM PTO <i>(with Stump Jumper and Single Suction Blades)</i>	8,316.00
-------	--	---	----------

DESTINATION

0202		North America United States of America	In Base Price
0184		Canada	No Added Cost

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

Attachment Information is not available in MOCI for the base code 220HP

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

HX7 Lift-Type Rotary Cutter - 540 RPM PTO
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

HX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

Smooth, Easy Clean, Top Deck
Deck Thickness:
Upper Deck - 3.5 mm (0.138 in.)
Lower Deck - 3.5 mm (0.138 in.)
Total - 7.0 mm (0.28 in.)
Three Gearcases, Power Ratings:
Center - 150 Continuous hp (112 kW);
Outer - 100 Continuous hp (73.5 kW);
Round Pan Bladeholder (Stump Jumper)
Shock Absorbing Cross Shafts
Slip Clutch Protection
Unibody Frame:
267 mm (10.5 in.) Body Depth
6 mm (.25 in.) Skirt Thickness
Cutting Width: 3.20 m (126 in.)
Transport Width: 3.35 m (132 in.)
Cutting Height: 25 - 305 mm (1 to 12 in.)
Blade Tip Speed: 85.8 m/s (16889 fpm)
Replaceable Full Length Wear Shoes
Minimum Recommended Tractor Power Take-Off (PTO)
hp:
6000 Series or Equivalent
Standard Driveline with

Lock-Slide Collar (Category 4) - 540 rpm 1.38 PTO
Integral Hitch (Category 2, 3 and
3N 3-Point Hitch with or without Quick Coupler)
Suction Blades 12.7 mm by 101.6 mm (.5 in. by 4
in.)
Two Wheel Supports (Swiveling, Height and Row Width
Adjustable)
Two Puncture Proof Laminated Tires
Front Safety Shield - Chain
Rear Safety Shield - Chain
Rear safety shield - Chain

Front and rear safety shields reduce the risk of
thrown objects which could be hazardous. The base
rotary cutter complies with the industrial mower
safety standard Society of Automotive Engineers
(SAE) J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

221AP		HX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number POHX10C010000 and above.</i>	11,473.00
-------	--	--	-----------

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

LIGHTING

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	663.00
------	--	--	--------

SMV EMBLEM AND SUPPORT

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	63.00
------	--	---	-------

Attachment Information is not available in MOCI for the base code 221AP

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

HX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

HX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO
Equipment for Base Machine

Smooth, Easy Clean, Top Deck
Deck Thickness:
 Upper Deck - 3.5 mm (0.138 in.)
 Lower Deck - 3.5 mm. (0.138 in.)
 Total - 7.0 mm (0.28 in.)
Three Gearcases, Power Ratings:
 Center - 150 Continuous hp (112 kW);
 Outer - 100 Continuous hp (73.5 kW);
44.45 mm (1.75 in.) Gearcase Input Shafts
76.2 mm (3 in.) Brush Cutting Capacity
Round Pan Bladeholder (Stump Jumper)
Shock Absorbing Cross Shafts
Slip Clutch Protection
Unibody Frame:
 267 mm (10.5 in.) Body Depth
 6 mm (.25 in.) Skirt Thickness
Cutting Width: 3.20 m (126 in.)
Transport Width: 3.35 m (132 in.)
Cutting Height: 1 to 12 in. (25 - 305 mm)
Blade Tip Speed: 16889 fpm (85.8 m/s)
Replaceable Full Length Wear Shoes
Minimum Recommended Tractor PTO hp: 50 hp
Constant Velocity Driveline with
 Lock-Slide Collar - 540 rpm (Category 4) - 1.38 PTO

Level Lift
Suction Blades 12.7 mm by 101.6 mm (.5 in. by 4 in.)
Two Wheel Supports (Swiveling, Height and Row Width Adjustable)
Two Puncture Proof Laminated Tires
Front Safety Shield - Chain
Rear Safety Shield - Chain
Safety Tow Chain
Jack with Mounting Brackets
Lift Cylinder and Hoses
Lift Cylinder and Depth Stops

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the industrial mower safety standard Society of Automotive Engineers (SAE) J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

221BP		HX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number POHX10C010000 and above.</i>	12,222.00
-------	--	--	-----------

TIRES

	Laminated Tires	Two 533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Puncture Proof Laminated Tires	In Base Price
1230	Severe Duty Tires	Two 304.8 mm (12 in.) wheels with 533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tires	151.00

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

THIRD OR FOURTH PULL-TYPE WHEEL

9010		MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub	253.00
------	--	---	--------

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

HX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		THIRD OR FOURTH PULL-TYPE WHEEL ...Continued... <i>Additional wheel support and hub. Requires wheel and tire.</i>	
		TIRES	
		Laminated Tires	
9030		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	135.00
		Severe Duty Tires	
9045		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	218.00
		LIGHTING	
9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	663.00
		SMV EMBLEM AND SUPPORT	
9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	63.00

Attachment Information is not available in MOCI for the base code 221BP

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**HX14 Lift-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder
Equipment for Base Machine**

Three Gearcases, Power Ratings:
 Center - 119.311 Continuous kW (160 hp);
 Outer - 74.569 Continuous kW (100 hp);
 50.8 mm (2 in.) Brush Cutting Capacity
 Shock Absorbing Cross Shafts
 Slip Clutch Protection
 Unibody Frame:
 266.7 mm (10.5 in.) Body Depth
 6.35 mm (0.25 in.) Skirt Thickness
 Cutting Width: 4.191 m (165 in.)
 Transport Width: 4.3434 m (171 in.)
 Cutting Height: 25.4 mm to 304.8 mm (1 in. to 12 in.)
 Blade Tip Speed: 14896 fpm (75.7 m/s)
 Replaceable Full Length Wear Shoes
 Transport Warning Lights
 Minimum Recommended Tractor Power Take-Off (PTO) hp: 7610 or equivalent
 Standard Driveline with Lock-Slide Collar (Category 5) - 1000 rpm 1.375 PTO
 Lock-Slide Collar (Cat. 5) -1000 rpm 1.375 Power Take-Off (PTO)

Integral Hitch (Category 2, 3 and 3N 3-Point Hitch with or without Quik-Coupler)
 Bar Type Bladeholder and Dual Suction Blades
 Two Wheel Supports (Swiveling, Height and Row Width Adjustable)
 Two Puncture Proof Laminated Tires
 Front Safety Shield - Chain
 Rear Safety Shield - Solid

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter is designed for agricultural applications only. This machine shall not be used in areas where bystanders may be present and could be injured or where property could be damaged by thrown objects.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

2228P		HX14 Lift-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder <i>Serial Number P0HX14D008500 and above.</i>	13,935.00
-------	--	--	-----------

DRIVELINES

1060		Standard Driveline with Lock-Slide Collar - 1000 rpm 1-3/8 Power Take-Off (PTO)	In Base Price
1070		Standard Driveline with Lock-Slide Collar - 1000 rpm 1-3/4 Power Take-Off (PTO)	50.00

TIRES

Laminated Tires			
1210		Two 533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Puncture Proof Laminated Tires	In Base Price
Severe Duty Tires			
1230		Two 304.8 mm (12 in.) Wheels with 533.4 mm by 177.8 mm by 304.8 mm (21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tires	151.00

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

HX14 Lift-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		OPERATOR'S MANUAL, DECALS, AND LANGUAGE ...Continued...	
		TIRES	
		Laminated Tires	
9030		533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	135.00
		Severe Duty Tires	
9060		533.4 mm by 177.8 mm by 304.8 mm (21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	218.00
		THIRD OR FOURTH PULL-TYPE WHEEL	
9020		Third or Fourth Lift-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	475.00
		SMV EMBLEM AND SUPPORT	
9080		Slow Moving Vehicle (SMV) Emblem and Support <i>Includes the following components: One BW10809 - SMV Emblem. One BW14053 - Support Assembly.</i>	63.00

Attachment Information is not available in MOCI for the base code 2228P

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**HX14 Pull-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck
Deck Thickness:
Upper Deck - 3.5052 mm (0.138 in.)
Lower deck - 3.5052 mm (0.138 in.)
Total - 7.112 mm (0.28 in.)
Three Gearcases, Power Ratings:
Center - 119.311 Continuous kW (160 hp);
Outer - 74.569 Continuous kW (100 hp);
44.45 mm (1.75 in.) Gearcase Input Shafts
50.8 mm (2 in.) Brush Cutting Capacity
Shock Absorbing Cross Shafts
Slip Clutch Protection
Unibody Frame:
266.7 mm (10.5 in.) Body Depth
6.35 mm (0.25 in.) Skirt Thickness
Cutting Width: 4.191 m (165 in.)
Transport Width: 4.3434 m (171 in.)
Cutting Height: 25.4 mm to 304.8 mm (1 in. to 12 in.)
Blade Tip Speed: 14896 fpm (75.7 m/s)
Replaceable Full Length Wear Shoes
Transport Warning Lights
Minimum Recommended Tractor Power Take-Off
(PTO) hp: 44.741 kW (60 hp)
Constant Velocity Driveline with
Lock-Slide Collar - 1000 rpm (Category 4) 1.375

PTO
Level Lift
Bar Type Bladeholder
Dual Suction Blades
Two Wheel Supports (Row Width Adjustable)
Two Puncture Proof Laminated Tires
Front Safety Shield - Chain
Rear Safety Shield - Solid
Safety Tow Chain
Jack with Mounting Brackets
Lift Cylinder and Hose(s)
Lift Cylinder Depth Stops

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter is designed for agricultural applications only. This machine shall not be used in areas where bystanders may be present and could be injured or where property could be damaged by thrown objects.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

2229P		HX14 Pull-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder <i>Serial Number POHX14F008500 and above.</i>	13,868.00
-------	--	--	-----------

DRIVELINES

1030		Constant Velocity Driveline with Lock-Slide Collar - 1000 rpm 1-3/8 Power Take-Off (PTO)	In Base Price
1040		Constant Velocity Driveline with Lock-Slide Collar - 1000 rpm 1-3/4 Power Take-Off (PTO)	50.00

TIRES

1210		Laminated Tires Two 533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Puncture Proof Laminated Tires	In Base Price
1230		Severe Duty Tires Two 304.8 mm (12 in.) Wheels with 533.4 mm by 177.8 mm by 304.8 mm(21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tires	151.00

OPERATOR'S MANUAL, DECALS, AND LANGUAGE

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

HX14 Pull-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
OPERATOR'S MANUAL, DECALS, AND LANGUAGE			
...Continued...			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
TIRES			
Laminated Tires			
9030		533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	135.00
Severe Duty Tires			
9060		533.4 mm by 177.8 mm by 304.8 mm (21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	218.00
THIRD OR FOURTH PULL-TYPE WHEEL			
9010		MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	253.00
SMV EMBLEM AND SUPPORT			
9080		Slow Moving Vehicle (SMV) Emblem and Support <i>Includes the following components: One BW10809 - SMV Emblem. One BW14053 - Support Assembly.</i>	63.00

Attachment Information is not available in MOCI for the base code 2229P

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**HX14 Lift-Type Rotary Cutter - 1000 RPM Round Pan Blade Holder - Stump Jumper
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck
Deck Thickness:
Upper Deck - 3.5052 mm (0.138 in.)
Lower Deck - 3.5052 mm (0.138 in.)
Total - 7.112 mm (0.28 in.)
Three Gearcases, Power Ratings:
Center - 119.311 Continuous kW (160 hp);
Outer - 74.569 Continuous kW (100 hp);
44.45 mm (1.75 in.) Gearcase Input Shafts
50.8 mm (2 in.) Brush Cutting Capacity
Shock Absorbing Cross Shafts
Slip Clutch Protection
Unibody Frame:
266.7 mm (10.5 in.) Body Depth
6.35 mm (0.25 in.) Skirt Thickness
Cutting Width: 4.191 m (165 in.)
Transport Width: 4.3434 m (171 in.)
Cutting Height: 25.4 mm to 304.8 mm (1 in. to 12 in.)
Blade Tip Speed: 14896 fpm (75.7 m/s)
Replaceable Full Length Wear Shoes
Transport Warning Lights
Minimum Recommended Tractor Power Take-Off
(PTO) hp: 7610 or equivalent
Standard Driveline with

Lock-Slide Collar (Category 5) - 1000 rpm 1,375 PTO
Integral Hitch (Category 2, 3 and 3N 3-Point Hitch with or without Quik-Coupler
Round Pan Blade Holder (Stump Jumper) and Single Suction Blades
Two Wheel Supports (Swiveling, Height and Row Width Adjustable)
Two Puncture Proof Laminated Tires
Front Safety Shield - Chain
Rear Safety Shield - Solid

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter is designed for agricultural applications only. This machine shall not be used in areas where bystanders may be present and could be injured or where property could be damaged by thrown objects.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.

222AP	HX14 Lift-Type Rotary Cutter - 1000 RPM Round Pan Blade Holder - Stump Jumper <i>Serial Number POHX14D008500 and above.</i>	13,532.00
-------	--	-----------

DRIVELINES

1060	Standard Driveline with Lock-Slide Collar - 1000 rpm 1-3/8 Power Take-Off (PTO)	In Base Price
1070	Standard Driveline with Lock-Slide Collar - 1000 rpm 1-3/4 Power Take-Off (PTO)	50.00

TIRES

Laminated Tires		
1210	Two 533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Puncture Proof Laminated Tires	In Base Price
Severe Duty Tires		
1230	Two 304.8 mm (12 in.) Wheels with 533.4 mm by 177.8 mm by 304.8 mm (21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tires	151.00

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

HX14 Lift-Type Rotary Cutter - 1000 RPM Round Pan Blade Holder - Stump Jumper
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
OPERATOR'S MANUAL, DECALS, AND LANGUAGE			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
TIRES			
Laminated Tires			
9030		533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	135.00
Severe Duty Tires			
9060		533.4 mm by 177.8 mm by 304.8 mm (21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	218.00
THIRD OR FOURTH PULL-TYPE WHEEL			
9020		Third or Fourth Lift-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	475.00
SMV EMBLEM AND SUPPORT			
9080		Slow Moving Vehicle (SMV) Emblem and Support <i>Includes the following components: One BW10809 - SMV Emblem. One BW14053 - Support Assembly.</i>	63.00
Attachment Information is not available in MOCI for the base code 222AP			

AGRICULTURAL PRODUCTS
JOHN DEERE FLAIL MOWERS

25A Flail Mower with Heavy Duty Roller and 9 In. Offset
Equipment for Base Machine

Cutting Height 1/2 to 5 Inch
Cutting Width 78 Inches
Three Bank Rotor 17-1/4 Inch Diameter
36 Heat Treated Knives
Built-In Tractor Hookup
PTO Shields
PTO-540 RPM
65 Continuous, 90 Intermittent
HP Rated Gearbox
Heavy Duty Gauge Roller with Anti-Friction

Self-Aligning Bearings
For Tractors Equipped with Category 1 3-Point Hitch

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas or Moline, Illinois

0488P		25A Flail Mower with Heavy Duty Roller and 9 In. Offset	5,765.00
-------	--	---	----------

OPERATOR'S MANUAL AND DECALS

Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.

9020		French Operator's Manuals and Labels	No Added Cost
------	--	--------------------------------------	---------------

RUBBER DEFLECTORS

Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.

9010		Rubber Deflector Shield for Rear Mounting	216.00
------	--	---	--------

HITCH ADAPTERS

9002		Hitch adapter for category 2 hitches	73.00
------	--	--------------------------------------	-------

Attachment Information is not available in MOCI for the base code 0488P

AGRICULTURAL PRODUCTS
JOHN DEERE FLAIL MOWERS

25A Flail Mower with Heavy Duty Roller and 9 In. Offset
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE FLAIL MOWERS**

**360 Heavy Duty Flail Mower
Equipment for Base Machine**

Cutting Height: 1/2 to 5 In.
 Cutting Width: 58.5 In.
 Heat Treated Side-Slicer Knives: 54
 Built-In Tractor Hook-Up: Cat. I/II
 PTO Shields
 PTO - 540 RPM
 Rotor Bearings 1-3/8 In. in Cast Mountings
 Skid Shoes
 Replaceable Skid Plates
 3-Bank Rotor 17 1/4 In. Diameter at
 Knife Tips
 Bearing Shield Rings Inside
 Anti-Wrap System

65 Continuous, 90 Intermittent HP
 Rated Gearbox
 Bearing Protection Guards Outside

For Tractors Equipped with Cat. I/II Hitch and 540
 RPM PTO.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas or Moline, Illinois

0484P		360 Heavy Duty Flail Mower	5,875.00
-------	--	----------------------------	----------

KNIVES CONFIGURATION

1000		Heat Treated Side-Slicer Knives	In Base Price
1010		Smooth-Cut Knives	-147.00

OPERATOR'S MANUAL AND DECALS

Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.

9020		French Operator's Manuals and Labels	No Added Cost
------	--	--------------------------------------	---------------

RUBBER DEFLECTORS

Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.

9010		Rubber Deflector Shield for Rear Mounting	129.00
------	--	---	--------

Attachment Information is not available in MOCI for the base code 0484P

AGRICULTURAL PRODUCTS
JOHN DEERE FLAIL MOWERS

360 Heavy Duty Flail Mower
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE FLAIL MOWERS**

**370 Heavy Duty Flail Mower
Equipment for Base Machine**

Cutting Height: 1/2 to 5 In.
Cutting Width: 71.5 In.
Heat Treated Side-Slicer Knives: 66
Built-In Tractor Hook-Up: Cat. I/II
PTO Shields
PTO - 540 RPM
Rotor Bearings 1-3/8 In. in Cast Mountings
Skid Shoes
Replaceable Skid Plates
3-Bank Rotor 17 1/4 In. Diameter at
Knife Tips
Bearing Shield Rings Inside
Anti-Wrap System

65 Continuous, 90 Intermittent HP
Rated Gearbox
Bearing Protection Guards Outside

For Tractors Equipped with Cat. I/II Hitch and 540 RPM PTO.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas or Moline, Illinois

0485P		370 Heavy Duty Flail Mower	6,450.00
-------	--	----------------------------	----------

DESTINATION

0202		United States	In Base Price
0184		Canada	No Added Cost

KNIVES CONFIGURATION

1000		Heat Treated Side-Slicer Knives	In Base Price
1010		Smooth-Cut Knives	-184.00

OPERATOR'S MANUAL AND DECALS

Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.

9020		French Operator's Manuals and Labels	No Added Cost
------	--	--------------------------------------	---------------

RUBBER DEFLECTORS

Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.

9010		Rubber Deflector Shield for Rear Mounting	142.00
------	--	---	--------

Attachment Information is not available in MOCI for the base code 0485P

AGRICULTURAL PRODUCTS
JOHN DEERE FLAIL MOWERS

370 Heavy Duty Flail Mower
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

AGRICULTURAL PRODUCTS
JOHN DEERE FLAIL MOWERS

390 Heavy Duty Flail Mower - 12 In. Offset
Equipment for Base Machine

Cutting Height: 1/2 to 5 In.
Cutting Width: 90.5 In.
Heat Treated Side-Slicer Knives: 84
Built-In Tractor Hook-Up: Cat. I/II
PTO Shields
PTO - 540 RPM
Rotor Bearings 1-3/8 In. in Cast Mountings
Skid Shoes
Replaceable Skid Plates
3-Bank Rotor 17 1/4 In. Diameter at
Knife Tips
Bearing Shield Rings Inside
Anti-Wrap System

65 Continuous, 90 Intermittent HP
Rated Gearbox
Bearing Protection Guards Outside

For Tractors Equipped with Cat. I/II Hitch and 540 RPM PTO.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas or Moline, Illinois

0487P		390 Heavy Duty Flail Mower - 12 In. Offset	7,288.00
-------	--	--	----------

KNIVES CONFIGURATION

1000		Heat Treated Side-Slicer Knives	In Base Price
1010		Smooth-Cut Knives	-239.00

OPERATOR'S MANUAL AND DECALS

Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.

9020		French Operator's Manuals and Labels	No Added Cost
------	--	--------------------------------------	---------------

RUBBER DEFLECTORS

Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.

9010		Rubber Deflector Shield for Rear Mounting	162.00
------	--	---	--------

Attachment Information is not available in MOCI for the base code 0487P

AGRICULTURAL PRODUCTS
JOHN DEERE FLAIL MOWERS

390 Heavy Duty Flail Mower - 12 In. Offset
Continued

THIS PAGE INTENTIONALLY LEFT BLANK
