6120M Cab Tractor

Equipment for Base Machine

```
Rear Hitch Category (check code selection)
Draft Links Type (check code selection)
ENGINE
John Deere PowerTechTM PSS
Stage IV Compliant EGR, DEF and SCR Afertreatment
                                                                Top Link Category (check code selection)
                                                                Top Link Type (check code selection)
                                                               External Hitch Remote control: RH & LH for Region 4
4 cylinders
Rated Power 97/68EC w/o IPM: 89 kW (120 hp)
Max Power 97/68EC w/o IPM: 93 kW (126 hp)
Engine Displacement: 4.5 L (275 cu in.)
Engine Rated Speed: 2100 r.p.m.
                                                                External Hitch Remote control
                                                                Transport lock for rear hitch
                                                               Wagon Hitch Type (check code selection)
Drawbar Category (check code selection)
High Pressure Common Rail
                                                               PTO
4 Valves per cylinder
                                                               Rear PTO Speeds (check code selection)
                                                               Rear PTO Connection: Electrical Shifting
PSS Turbo
Cooling system: Distributed cooling system with
                                                               Rear PTO Diameter: 35 mm (1.38 in.)
                                                               Rear PTO Reversible (check code selection)
temperature controlled viscous fan driver and
charge air cooler
Corner Post Exhaust
                                                               Rear PTO Remote Control (check code selection)
Rear PTO Brake: Hydraulically Controlled
Fuel Tank Capacity: 195 L (51.5 gal)
Diesel Exhaust Fluid Tank Capacity: 13 L (3.4 gal)
                                                               HYDRAULICS
                                                               Hydraulic System (check code selection)
Hydraulic Flow Capacity (check code selection)
TRANSMISSION
Transmission (check code selection)
Max Speed (check code selection)
                                                                Hydraulic Take Out capacity (check code selection)
                                                                SCV 1 Rear (check code selection)
Multiple-wet-disc
                                                               SCV 2 Rear (check code selection)
SCV 3 Rear (check code selection)
Park Lock
DIFFERENTIALS & AXLES
Front Axle Type (check code selection)
Front Axle Differential Limited Slip
                                                               SCV 4 Rear (check code selection)
                                                               OPERATOR STATION
Front Axle Max Permissible Weight (check code
                                                               Operator Station Type: Cab
Tilt able cab, 330° all-around visibility
selection)
Rear Axle Type (check code selection)
Rear Axle Differential Blockage: Hydraulic
                                                                Transmission operating: Right Hand Console
                                                               Hand throttle & Foot throttle
                                                               Roof description (check code selection)
Air Conditioning/ Heater (check code selection)
Rear Wheel Bolt Circle Diameter: 203 mm (8 in.)
STEERING & BRAKES
                                                                Radio Installation (check code selection)
Steering system: Hydrostatic
                                                                Speakers and antenna (check code selection)
Front Axle Steering Angle: 52 Degrees
Front Axle Pivoting Angle: 11 Degrees
                                                                Beacon Lights (check code selection)
                                                                Windshield (check code selection)
                                                                Rear Wiper and Washer (check code selection)
Front Axle Caster Angle: 12 Degrees
Front Axle Brakes (check code selection)
                                                                Steering Column: Telescoping and tilting
Rear Axle Brakes: Hydraulic Actuated
                                                               Driver s Seat (check code selection)
Hydraulic Trailer Brake (check code selection)
                                                               Passenger s Seat (check code selection)
                                                               Outside Mirrors (check code selection)
Pneumatic Trailer Brake Type (check code selection)
                                                                Inside Mirror (check code selection)
Rear Tires size (check code selection)
                                                                Storage compartment: Roof mounted
Rear & Front Tires brand (check code selection)
                                                               Additional Storage compartment (check code
Rear Fenders Type (check code selection)
                                                               selection)
Front Tires size (check code selection)
                                                               AG MANAGEMENT SOLUTIONS
Front Fenders Type (check code selection)
                                                                Isobus Connection (check code selection)
BALLASTING
Front weights support (check code selection)
                                                               MISCELLANEOUS
Quick Tach weights (check code selection)
                                                                Country code (check code selection)
Rear wheels weights (check code selection)
                                                                Operator's Manual
ELECTRICS & LIGHTS
Alternator capacity: 14 V / 120 A
Battery capacity: 12 V /154 AH
External Electric socket connection (check code
selection)
Lightning description (check code selection)
HITCHES & DRAWBAR
```

ATTACHMENT
CODE IDENTIFIER DESCRIPTION

SUGGESTED LIST PRICE USD (\$)

Select One Code From Each Required Category

BASE MACHINE

Ex-works Port of Entry

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|-------|--------------------------|---|-------------------------------------|
| 4295L | | BASE MACHINEContinued 6120M Cab Tractor | 102,537.00 |
| +230L | | | 102,307.00 |
| 0404 | | DESTINATION | Como Drico |
| 0184 | | Canada | Same Price |
| 0202 | | United States | In Base Price |
| | | OPERATOR'S MANUAL | |
| 0409 | | English | In Base Price |
| 0413 | | French | Same Price |
| 0437 | | Spanish | Same Price |
| | | SHIPPING PREPARATION | |
| 7702 | | Shipment Preparation - by Ship Overseas includes various step as: 1) Tractor is equipped with operator manual etc. 2) All loose parts are removed or tied up (e.g. bolts, upper link, etc.) inluding beacon light only in R1, R2 & R3 | In Base Price |
| 7706 | | Shipment Preparation - by Ship Overseas, with Conservation Code 7702 plus certain parts of the tractor are coated with a protective film | 55.00 |
| | | TRANSMISSION | |
| 1436 | | PowrQuad Plus - 24/24, 40 km/h Includes electrical lefthand reverser. Transmission with Left Hand Power Reverser (25 mph) Requires Code 6045(MFWD) Includes Transmission De-Clutch Function. | In Base Price |
| 1437 | | PowrQuad Plus - 16/16, 30 km/h Includes electrical lefthand reverser. Transmission with Left Hand Power Reverser (19 mph) Includes Transmission De-Clutch Function. | -1,877.00 |
| 1440 | | PowrQuad Plus - 24/24, 40 km/h, with creeper Includes electrical lefthand reverser. Transmission with Left Hand Power Reverser (25 mph) with Creeper Requires Code 6045 (MFWD) Includes Transmission De-Clutch Function. | 2,601.00 |
| 1441 | | PowrQuad Plus - 16/16, 30 km/h, with creeper Includes electrical lefthand reverser. Transmission with Left Hand Power Reverser (19 mph) with Creeper Includes Transmission De-Clutch Function. | 1,148.00 |
| 1454 | | AutoQuad Plus - 24/24, 40 km/h Includes electrical lefthand reverser. Transmission with Left Hand Power Reverser (25 mph) Requires Code 6045 (MFWD) Includes Transmission De-Clutch Function. | 2,859.00 |
| 1458 | | AutoQuad Plus - 24/24, 40 km/h, with creeper Includes electrical lefthand reverser. Transmission with Left Hand Power Reverser (25 mph) with Creeper Requires Code 6045 (MFWD) | 3,665.00 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| | | TRANSMISSIONContinued Includes Transmission De-Clutch Function. | |
| 1500 | | CommandQuad Plus - 24/24, 40 km/h Includes electrical lefthand reverser. SOP June 16. | 7,428.00 |
| | | OPERATOR'S STATION | |
| 2071 | | Basic Cab Right-hand Steps Front Windshield Wiper and Washer Tilt/Telescopic Steering Column Right Hand Operational Controls Floor Mat Hand and Foot Throttle Control Overhead Reading Light 7-pin Signal Interface Socket (Code 8224) Inner Rear View Mirror (Code 8230) Power Outlet Socket (Code 8240) LH Remote Hitch Controls (Code 8446) Air conditioning (Code 8206) No Handbrake (Code 8762) Swinging Drawbar with hammerstrap (Code 8434) 154ah battery (Code 8746) Requires Code Mechanical Suspension Seat (Code 2109) and Mirrors Standard-Left-hand and Right-hand (Code 2510) and Panorama windshield with RH door (Code 2631) | In Base Price |
| 2072 | | Economy Cab Includes in addition to Base Cab: Economy Seat (Code 2127), Mirrors Manually Adjustable and Telescopic- LH & RH (Code 2511), Front & Rear Windshield Wiper & Washer, Cup Holder, and Sun Visor (Code 8278). | 1,954.00 |
| 2073 | | Standard Cab Includes in addition to Economy Cab Front & Rear Roller Blind (Code 8276) Instructor Seat (Code 8254) Additional Storage Compartment (Code 8266) Bottle Holder (878R) iTec Basic (Code 8217) | 2,640.00 |
| 2074 | | Low Clearance Standard Cab Only for USA (Code 0202), Canada (Code 0184), Australia and New Zealand (Codes 0202, 0184, 0230, 0237) Requires 30 k transmission (Codes 1424, 1437) Air conditioning Front Windshield Wiper and Washer Not with Right-hand footstep Not with Right-hand door Not with Rear hitch remote control (8446), LH remote in base Tilt/Telescopic Steering Column Right Hand Operational Controls Floor Mat Hand and Foot Throttle Control Overhead Reading Light 7-pin Signal Interface Socket (Code 8224) Inner Rear View Mirror (Code 8230) Power Outlet Socket (Code 8762) Swinging Drawbar with hammerstrap (Code 8434) 154AH battery (Code 8746) Horizontal exhaust (Code 8330) Includes Air Suspension Seat (Code 2127) No Mirrors (Code 2500 | 13,070.00 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | | OPERATOR'S STATIONContinued | |
| | | SEAT | |
| 2109 | | Basic Seat With mechanical suspension, Grammer Seat MSG85-731. Comes with operator presence switch if CommandQuad Plus transmission (Code 1500, 1501, 1502, 1503, 1504, or 1505) is chosen. Operator presence switch is included. | In Base Price |
| 2127 | | Economy Seat With air suspension, Grammer Seat MSG 95GL-731. Comes with operator presence switch if CommandQuad Plus transmission (Code 1500, 1501, 1502, 1503, 1504, or 1505) is chosen. Operator presence switch is included. | In Configuration |
| | | MIRRORS | |
| 2500 | | Without Mirrors for Low Clearance Cab | In Configuration |
| 2510 | | Mirrors - Left-hand and Right-hand Standard Have fixed length arms with manually adjustable mirror positions. | In Base Price |
| 2511 | | Mirrors - Left-hand and Right-hand Manual Telescopic | In Configuration |
| | | WINDSHIELD | |
| 2631 | | Panorama Front Windshield | In Base Price |
| | | RADIO | |
| 2650 | | Radio Preparation Includes pre-radio wiring, antenna installation and speaker package. | In Base Price |
| 2651 | | Without Radio Preparation No pre-radio wirering, antenna installation and speaker package. | -868.00 |
| 2663 | | Radio (Business Radio Package) only for North America & Japan Includes: AM/FM Stereo, Weatherband, Remote Mounted Auxiliary Input Jack, Two Speakers and External Antenna. | 327.00 |
| | | REAR AXLE | |
| 5010 | | Flange-Type Rear Axle | In Base Price |
| 5040 | | R&P Rear Axle - 79 mm Shaft 100.6 Inch lengths (2.556 mm). Rack and Pinion Axle 3.1 In. (79.45 mm) Diameter by 100.6 In. Length | 2,434.00 |
| 5042 | | R&P rear axle - 79 mm shaft - short version 90 Inch length (2.286 mm) | 2,128.00 |
| | | FRONT AXLE | |
| 6022 | | 2WD Front Axle | -8,566.00 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| 6045 | | FRONT AXLEContinued 4WD Front Axle - Unsuspended Limited slip differential. | In Base Price |
| | | WHEELS AND HUBS | |
| 5093 | | 2-Position Steel Wheels Front and rear wheels. | -1,156.00 |
| 5090 | | Adjustable Steel Wheels (Steel Disk) Front and rear wheels. Adjustable steel wheels allow a finer setting of treads, possible positions may vary between 8 or 16 allowable sets, please refer to Operators Manual for more precise information. Adjustable Steel wheel with flange axle Steel wheel with cast hub on R&P axle (2 position or adjustable) When ordered with 2WD (6022) the front wheel will be a 2-position. | In Base Price |
| 5091 | | Adjustable Cast Wheels (Cast Disk) Front adjustable steel wheels. Only available with Rack & Pinion. Front wheels are adjustable steel when ordered with MFWD If ordered with Rack and Pinion axle code 5040 only available with the following tire sizes: 5202, 5204, 5208, 5212, 5214, 5221, 5222, 5223, 5234, 5237. When ordered with 2WD (6022) the front wheel will be a 2-position | 174.00 |
| | | TIRE BRAND PREFERENCE | |
| 5904 | | Rear and Front Tire Brand - Mitas | 200.00 |
| 5901 | | Rear and Front Tire Brand - Firestone | 200.00 |
| 5903 | | Rear and Front Tire Brand - Michelin | 400.00 |
| 5915 | | Rear and Front Tire Brand - Nokian Special profile - Tight block pattern tread - ideal for grass and communal applications. | 200.00 |
| 5999 | | Rear and Front Tire Brand - No preference Order results in either Mitas or Firestone tires. | In Base Price |
| | | REAR WHEELS AND TIRES | |
| 5150 | | Rear Wheels Size 21.5L-16.1 21.5L-16.1 In. 6PR R3 Bias Use of these tires reduces ground clearance to less than eight inches. For 2WD: Requires 27/9.5-15 In. 6PR I1 Bias Front wheel (Code 6141) Not compatible with 25 mph (40kmh) transmissions. Available in Firestone Turf and Field only. | -1,842.00 |
| 5161 | | Rear Wheels Size 420/85R24/16.9-24 R3 profile (All weather), 2WD and MFWD. Available in Firestone. 2WD requires Front wheels size 11L-15 (Code 6100) or Front wheels size 27/9.5-15 (Code 6141), MFWD requires Front wheels size 10.5/80-18 (Code 6110). | -616.00 |
| 5180 | | Rear Wheels Size 420/85R30 Available in Mitas, Firestone, Michelin or Trelleborg. 16.9R30 In. 137A8 R1W Radial (420/85R30 140A8 R1W Radial) For 2WD: Requires Code 6100. For MFWD: Requires Code 6200. | -92.00 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| | | REAR WHEELS AND TIRESContinued Available in Firestone Performer 85, Michelin Agribib, and Mitas AC85. | |
| 5190 | | Rear Wheels Size 460/85R30 Available in Mitas, Firestone, Michelin or Trelleborg. 18.4R30 In. 142A8 RIW (460/85R30 In. 145A8 RIW) For 2WD: Requires Code 6100 or 6151. For MFWD: Requires Code 6210 or 6200. Available in Firestone Performer 85, Michelin Agribib, and Continental/Mitas AC85. | -6.00 |
| 5202 | | Rear Wheels Size 420/85R34 Available in Mitas, Michelin, Firestone. 16.9R34 In. 139A8 RIW (420/85R34 In. 139A8 RIW) For 2WD: Requires Code 6100 or 6151. For MFWD: Requires Code 6210. Available in Firestone Performer 85, Michelin Agribib, and Continental/Mitas AC85 | -344.00 |
| 5208 | | Rear Wheels Size 480/70R34 Available in Mitas, Firestone, Michelin. 480/70R34 In. 143A8 RIW For MFWD: Requires Code 6211. Available in Firestone Performer 70, Michelin Omnibib, and Mitas HC70. | 354.00 |
| 5212 | | Rear Wheels Size 460/85R34 Available in Mitas, Firestone, Michelin. 18.4R34 In. 144A8 RIW (460/85R34 In. 147A8 RIW) For 2WD: Requires Code 6151. For MFWD: Requires Code 6220 or 6210. Available in Firestone Performer 85, Michelin Agribib, and Mitas AC85. | In Base Price |
| 5215 | | Rear Wheels Size 520/70R34 Available in Mitas, Firestone, Michelin. 520/70R34 In. 148A8 R1W For MFWD: Requires Code 6221 Available in Firestone Performer 70, Michelin Omnibib, and Continental/Mitas AC70 | 602.00 |
| 5220 | | Rear Wheels Size 320/90R42 Available in Firestone. 320/90R42 In. 139A8 R1W For MFWD: Requires Code 6215. Requires Code 5040(Rack & Pinion Steel). Available in Firestone R9000. | -2.00 |
| 5221 | | Rear wheels size 420/85R38 Available in Mitas, Firestone, Michelin. 16.9R38 In. 141A8 RIW (420/85R38 In. 144A8 RIW) For 2WD: Requires Code 6151. For MFWD: Requires Code 6230, 6215, or 6220. Available in Firestone Performer 85, Michelin Agribib, and Mitas AC85. | 160.00 |
| 5222 | | Rear Wheels Size 480/70R38 Available in Mitas, Firestone, Michelin. 480/70R38 In. 145A8 R1W For MFWD: Requires Code 6221. Available in Firestone Performer 70, Michelin Omnibib, and Continental/Mitas AC70T & Trelleborg | 1,316.00 |
| 5234 | | Rear Wheels Size 460/85R38 Available in Mitas, Firestone. 460/85R38 In. 145A8 RIW For MFWD: Requires Code 6221. Available in Firestone Performer 70, Michelin Omnibib, and Continental/Mitas AC70T and Trelleborg. | 1,782.00 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| 5232 | | REAR WHEELS AND TIRESContinued Rear Wheels Size 520/70R38 Available in Mitas, Firestone, Michelin. 520/70R38 In. 150A8 RIW For MFWD: Requires Code 6240 or 6221. Available in Firestone Performer 70, Michelin Omnibib, and Mitas HC70. | 2,088.00 |
| 5245 | | Rear Wheels Size 13.6-46 Available in Firestone R2 CSG only. 13.6-46 In. 6PR R2 Bias For MFWD: Requires Code 6280. Only compatible with 30K Transmissions. Available in Firestone R2 CSG only. | -34.00 |
| 5252 | | Rear Wheels Size 380/90R46 Available in Mitas. | 346.00 |
| 5214 | | Rear Wheels Size 480/80R34 - Special Profile Available in Nokian only. Tight block pattern tread - ideal for grass and communal applications. 480/80R34 In. 159D R4 Radial For MFWD: Requires Code 6225. Available in Nokain TRI2 only. | 1,290.00 |
| 5237 | | Rear Wheels Size 480/80R38 - Special Profile Available in Nokian only. Tight block pattern tread - ideal for grass and communal applications. 480/80R38 In. 161D R4 Radial For MFWD: Requires Code 6225 or 6237. Available in Nokain TRI2 only. Not compatible with No Rear Tire Preference (Code 5999) | 3,340.00 |
| | | FRONT WHEELS AND TIRES | |
| 6100 | | For 2WD Front Axle / Transmission Front Wheels Size 11L-15 Available in Firestone. 11L-15 In. 8PR F3 Bias Available in Firestone F3 Industrial Special. Standard Load Capacity 4708 Lbs. | -2,618.00 |
| 6110 | | Front Wheels Size 10.5/80-18 Available in Firestone. 10.5/80-18 In. 10PR 13 Bias Available in Firestone ATU. Not with front fenders (Code 8011 or 8012). Available for 2WD and MFWD (Code 6022 or 6045). | -2,034.00 |
| 6123 | | Front Wheels Size 11.00-16 Available in Firestone. 11.00-16 In. 12PR F2 Bias Available in Firestone. | -2,064.00 |
| 6141 | | Front Wheels Size 27/9.5-15 Available in Firestone. Only with 2WD axle. Not compatible with no rear tire preference (code 5999). 27/9.5-15 In. 6PR II Bias Available in Firestone only. | -2,814.00 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| 6151 | | FRONT WHEELS AND TIRESContinued Front Wheels Size 10.00-16 Available in Firestone. 10.00-16 In. 10PR F2 Bias | -2,240.00 |
| 6180 | | For MFWD Front Axle / Transmission Front Wheels Size 280/85R24 Available in Firestone, Michelin. 11.2R24 In. 114A8 RIW Available in Michelin Agribib. 280/85R24 115A8 RIW Available in Firestone Performer 85 | -1,162.00 |
| 6200 | | Front Wheels Size 320/85R24 Available in Mitas, Firestone, Michelin or Trelleborg. 320/85R24 In. 122A8 R1W Available in Firestone Performer 85, Michelin Agribib, and Mitas AC85. | -754.00 |
| 6210 | | Front Wheels Size 340/85R24 Available in Mitas, Firestone, Michelin. 13.6R24 In. 121A8 R1W Available in Michelin Agribib, 340/85R24 125A8 R1W Available in Firestone Performer 85, Mitas AC85.and Trelleborg | -148.00 |
| 6211 | | Front Wheels Size 380/70R24 Available in Mitas, Firestone, Michelin. 380/70R24 In. 125A8 R1W Available in Firestone Performer 70, Michelin Omnibib, and Mitas HC70. | -534.00 |
| 6215 | | Front Wheels Size 320/85R28 Available in Mitas, Firestone, Michelin. 12.4R28 In. 121A8 RIW Available in Michelin Agribib 320/85R28 124 A8 RIW Available in Firestone Performer 85, and Mitas AC85. | -314.00 |
| 6220 | | Front Wheels Size 380/85R24 Available in Mitas, Firestone, Michelin. 380/85R24 In. 131A8 R1W Available in Firestone Performer 85 and Mitas AC85. 14.9R24 In. 126A8 R1W Available in Michelin Agribib, Not with Turnable Front Fenders for MFWD (Code 8012). | In Base Price |
| 6221 | | Front Wheels Size 420/70R24 Available in Mitas, Firestone, Michelin. 420/70R24 In. 130A8 RIW Radial Available in Firestone Performer 70, Michelin Omnibib, Mitas AC70T and Trelleborg. | -248.00 |
| 6230 | | Front Wheels Size 340/85R28 Available in Mitas, Firestone, Michelin. 13.6R28 In. 123A8 R1W Available in ,Michelin Agribib 340/85R28 127A8 R1W Available in Firestone Performer 85, Mitas AC85, and Trelleborg. | -12.00 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | T DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| 6232 | | FRONT WHEELS AND TIRESContinued Front Wheels Size 420/85R24 Available in Mitas, Firestone. 16.9R24 In. 134A8 RIW Radial Available in Michelin Agribib (420/85R24 137A8 RIW Radial) Available in Firestone Performer 85, Mitas AC85, and Trelleborg. | 354.00 |
| 6236 | | Front Wheels Size 380/85R28 Available in Mitas, Firestone, Michelin. 380/85R28 In. 133A8 R1W Radial Available in Firestone Performer 85, Michelin Agribib, Mitas AC85, and Trelleborg. | 236.00 |
| 6240 | | Front Wheels Size 420/70R28 Available in Mitas, Firestone, Michelin. 420/70R28 133A8 RIW Radial Available in Firestone Performer 70, Michelin Omnibib, Mitas HC70, and Trelleborg. | 654.00 |
| 6258 | | Front Wheels Size 380/85R30 Available in Firestone, Mitas. Available in Michelin. 380/85R30 In. 135A8 R1W Radial Available in Firestone Performer 85, Mitas, and Michelin Agribib and Trelleborg. | 1,192.00 |
| 6275 | | Front Wheels Size 340/85R38 Available in Mitas. 340/85R38 133A8 RIW Radial Available in Mitas. | 1,690.00 |
| 6280 | | Front Wheels Size 13.6-38 - R2 Available in Firestone R2 CSG only. 13.6-38 In. 6PR R2 Bias Available in Firestone CSG only. | -90.00 |
| 6237 | | Front Wheels Size 440/80R24 - Special Profile Available in Nokian only. Tight block pattern tread - ideal for grass and communal applications. 440/80R24 149D R4 Radial Available in Nokian TRI2 only. Requires Code 5237 (Rear). | 1,486.00 |
| 6225 | | Front Wheels Size 400/80R24 - Special Profile Available in Nokian only. Tight block pattern tread - ideal for grass and communal applications. 400/80R24 144D R4 Radial Available in Nokian TRI2 only. Requires Code 5214 (Rear). | 884.00 |
| | | CENTER LINK | |
| 4200 | | No Center Link | -885.00 |
| 4210 | | Center Link with Ball End - Category 2 Comes with category 2 ball. | In Base Price |
| 4213 | | Center Link with Ball End - Category 3 Comes with category 3 ball. | In Base Price |
| | | DRAFT LINK | |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| 4100 | | DRAFT LINKContinued No Draft Links/No Rockshaft | -2,773.00 |
| 4120 | | Draft Links with Telescopic Ball End - Category 2 | In Base Price |
| 4121 | | Draft Links with Telescopic Ball End - Category 3N / Category 3 Category 3N. | In Base Price |
| | | STABILIZER | |
| 4400 | | No Sway Control Blocks and No Stabilizer Bar | -459.00 |
| 4410 | | Sway Control Blocks Stop-bar at PTO housing to prevent horizontal drawbar movement. | In Base Price |
| 4421 | | Stabilizer Bars - Adjustable Both Sides Left-hand and right-hand. | 594.00 |
| | | REAR POWER TAKE-OFF (PTO) | |
| 3810 | | Rear Independent 540 rpm PTO Rear Independent 540 RPM PTO Not compatible with Power Beyond (Code 832J) or 3 SCVs (Codes 3335 or 3338) | -778.00 |
| 3820 | | Rear Independent 540/1000rpm PTO | In Base Price |
| | | HYDRAULIC PUMP | |
| 3232 | | Hydraulic Pump - 80 l/min PC system, 35 ccm pump. In base. Load Sensing Constant Flow Hydraulic System: 21.1 GPM (80 L/min), 35cc | In Base Price |
| 3223 | | Hydraulic Pump - 114 l/min PFC system, 45 ccm pump. Required if Cold Start package II (Code 8301) is chosen. | 1,697.00 |
| | | SELECTIVE CONTROL VALVES (SCVS) | _ |
| 3319 | | 2 Mechanical SCVs (2 SCV 200 Series) Standard couplers. 2 Detent-200 Series with Standard Couplers with Plug Type Covers. | In Base Price |
| 3320 | | 2 Mechanical SCVs (2 SCV 450 Series) Standard couplers. 3 Detents - 450 Series with Standard Couplers with Dust Cover. Required with Hydraulic Motors. | 113.00 |
| 3338 | | 3 Mechanical SCVs (3 SCV 450 Series) Standard couplers. 3 Detents - 450 Series with Standard Couplers with Dust Cover. Not possible if tractor equipped with Load Sensing Constant Flow Hydraulic (3232), loader ready/preparation and with Power Beyond (832J). | 980.00 |
| | | GREENSTAR AND AUTOTRAC | |
| 1834 | | Less Greenstar Ready | In Base Price |

6120M Cab Tractor

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| | | GREENSTAR AND AUTOTRACContinued | |
| 1830 | | ISObus Ready / GreenStar Ready Option Power harness Connector at the A-post StarFire Receiver roof harness and bracket ISOBUS Class 2 gateway controller and In-cab ISOBUS connector 60A socket. | 814.00 |
| | | RECEIVER | |
| 1835 | | Less StarFire Receiver | In Base Price |
| 1840 | | StarFire 6000 Receiver - SF1 Ready Provides access to the no-charge SF1 differential correction signal. SF1 provides +/- 15 cm (+/- 6 in) horizontal pass-to-pass accuracy. An SF3 Ready Activation and License is required to use SF3 differential corrections. License sold separately via AMS PricePage. Use of this service, and all rights and obligations of John Deere and the Customer (as identified in the applicable agreement), are governed by the terms and conditions outlined in the applicable Services and Software agreements available at www.JohnDeere.com/Agreements. If these terms and conditions are not agreeable do not proceed and do not use the service. | 3,895.00 |
| 1841 | | StarFire 6000 Receiver - SF3 Ready Includes StarFire 6000 SF3 with Ready Activation. SF3 provides +/- 3 cm (1.2 in) horizontal pass-to-pass accuracy with in-season repeatability (where applicable). An SF3 Subscription is required to use SF3 differential corrections. Subscription sold separately via AMS PricePage. See Ag Sales Manual for additional information. Use of this service, and all rights and obligations of John Deere and the Customer (as identified in the applicable agreement), are governed by the terms and conditions outlined in the applicable Services and Software agreements available at www.JohnDeere.com/Agreements. If these terms and conditions are not agreeable do not proceed and do not use the service. | 7,895.00 |
| 1842 | | StarFire 6000 Receiver - SF3 Ready and 1 Year SF3 License Includes StarFire 6000 with SF3 Ready Activation and 1 Year SF3 license. SF3 provides +/- 3 cm (1.2 in) horizontal pass-to-pass accuracy with in-season repeatability (where applicable). See Ag Sales Manual for additional information. Additional locking bracket available to secure the StarFire 6000 Receiver via JDPoint. StarFire 6000 Receiver shipped inside the cab. Use of this service, and all rights and obligations of John Deere and the Customer (as identified in the applicable agreement), are governed by the terms and conditions outlined in the applicable Services and Software agreements available at www.JohnDeere.com/Agreements. If these terms and conditions are not agreeable do not proceed and do not use the service. | 8,945.00 |
| 1843 | | StarFire 6000 Position Receiver - SF3 Ready and RTK Ready Includes StarFire 6000 with SF3 Ready Activation and StarFire 6000 RTK Ready Activation. RTK provides +/- 2.5 cm (1 in) horizontal pass-to-pass accuracy with long-term repeatability. RTK functionality requires access to differential corrections from an RTK base station and additional hardware or subscriptions may be required. Use of this service, and all rights and obligations of John Deere and the Customer (as identified in the applicable agreement), are governed by the terms and conditions outlined in the applicable Services and Software agreements available at www.JohnDeere.com/Agreements. If these terms and conditions are not agreeable do not proceed and do not use the service. | 11,395.00 |
| | | ENGINE | |

06 June 2017 US & Canada 2-TRACTOR- 11

141.00

Fuel Heater System

8304

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | ENGINEContinued | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| 8300 | | COLD START PACKAGES Cold Start Package I This package includes an engine block heater and electrical cable for 230V/110V socket. Not compatible with Code 8301 (Cold Start Package II) | 321.00 |
| 8301 | | Cold Start Package II This package includes a set of heaters (engine block heater, transmission oil pump heater & charge pump heater) and an electrical cable for 230V/110V socket. Not compatible with Code 8300 (Cold Start Package I) | 457.00 |
| 8307 | | FUEL TANK Fuel Tank Bottom Guard Metal shield protecting the bottom of the fuel tank. | 418.00 |
| 8330 | | EXHAUST Horizontal Exhaust Not with RH footstep | No Charge |
| | | Not with RH door Not with RH outer mirror Only for Canada and USA (Codes 0184, 0202) Not with mechanical cab suspension (8261) Not with ISOBUS Ready / AutoTrac Ready option or StarFire receiver (Codes 1830, 1832, 1840, 1841, 1842, 1843) Not with trailer brake system (Codes 8750, 8751, 8756) Not with additional oil reservoir (Code 832D) Not with Economy front hitch & front PTO (Codes 8410, 8381) Not with TLS front axle (Codes 6065, 6070) Not with footstep lights (Code 8728) Not with floormat (Code 8284) Not with Tier 2 engine (Code 8343) Not with mid stack SCVs (Codes 891H, 891G, 891D, 891C, 8923, 8922) | |
| 8261 | | CAB EQUIPMENT Mechanical Cab Suspension | 1,553.00 |
| 8237 | | Cigarette Lighter and Ashtray Mounted at right-hand console. | 21.00 |
| 8782 | | Backup Alarm Safety alarm for reverse. | 477.00 |
| 878J | | Vandal Protection Package Includes lock for hood, latch for transmission oil filler neck and lockable fuel cap. | 345.00 |
| 878M | | Condenser Screen If the tractor is equipped with air conditioning, the optional super fine screen in front of the air conditioning perfects the protection of the Dual Temperature Cooling System. for Cooling Package | 21.00 |
| 070T | | ROOF SELECTION | 040.00 |
| 878T | | Roof Hatch with Glass | 610.00 |

6120M Cab Tractor

| CODE | ATTACHMENT | T DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|------------|---|-------------------------------------|
| | | ROOF SELECTIONContinued Openable hatch for ventilation, opens to rear. | |
| 8607 | | FRONT AXLE AutoDifflock Steering angle dependent engagement and disengagement. Provides 100 % rear axle Difflock, front axle remains limited slip | 274.00 |
| | | STEERING AND BRAKES No handbrake in base for R4 | |
| 8763 | | Heavy Duty Rear Wheel Brakes Increased disc brake thickness (+20%) to ensure higher braking capacity (designed for transport with non-braked trailers). | 128.00 |
| 8765 | | Powerfill Brake The hydraulic system supports the operator to reduce braking pedal force. | 501.00 |
| | | FRONT FENDERS | |
| 8011 | | Front Fenders 4WD - Rigid | 566.00 |
| 8012 | | Front Fenders 4WD - Turnable | 850.00 |
| 8020 | | REAR FENDERS Rear Fender Extensions - Adjusted to Tire Size 110 x 15 for tires up to 478 mm width (overall coverage 2200 mm), 200 x 20 for tires above 478 mm width (overall coverage 2380 mm). | 646.00 |
| | | EDONT WEIGHTO | |
| 8950 | | FRONT WEIGHTS Front Base Weight - 60 kg Allows installation of quik-tatch weights. Front Weight Support- 132 lbs Holds up to 14 quick-tatch Front Weights. | 282.00 |
| 8951 | | Front Base Weight - 110 kg Allows installation of quik-tatch weights. Front Weight Support- 242 lbs Holds up to 18 quick-tatch Front Weights. | 377.00 |
| 8973 | | REAR WHEEL WEIGHTS Rear Wheel Weights - 110 kg (242 lbs) 2 x 55 kg, 110 kg total weight split on both sides, cast iron. 2 x 55 kg, 110 kg (242 lbs) total weight, split on both sides. Requires Code 5010 (Flange Axle) and 34"-38" wheelsize. | 311.00 |

6120M Cab Tractor

| | | OSHAHAGA | |
|------|--------------------------|--|-------------------------------------|
| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
| 8974 | | REAR WHEEL WEIGHTSContinued Rear Wheel Weights - 220 kg (485 lbs) 4 x 55 kg, 220 kg total weight, split on both sides, codes. 4 x 55 kg, 220 kg (485 lbs) total weight, split on both sides. Requires Code 5010 (Flange Axle) and 34"-38" wheelsize. | 311.00 |
| 8747 | | BATTERY Battery 12V/174AH Located on right-hand floor. | 119.00 |
| | | ALTERNATOR | |
| 8742 | | Alternator 14V/200A | 264.00 |
| 878B | | ELECTRICAL EQUIPMENT Battery Circuit Breaker Can be ordered with any battery, integrated in ignition key. Located at top of left hand steps. | 148.00 |
| 878H | | Multi Power Outlet Strip Six additional outlets for powering monitors or other electrical equipment. Located at right-hand door behind right-hand console. | 86.00 |
| | | LIGHTING PACKAGES Base lighting - Cab: Hood High-beam light (HB3) (2) Hood Low-beam light (HB3) (1) Turn lights rear fender (17) Tail lights rear fender (18) Brake-lights fender (18) Work lights roof front outer left-hand and right-hand (H3) (8) Work light roof rear inner right-hand (H3) (14) Base lighting - Cab: Hood High-beam light (HB3) (2) Hood Low-beam light (HB3) (1) Four roof mounted fixed amber position lights Turn lights rear fender (17) Tail lights rear fender (18) Brake-lights fender (18) Work light roof front outer left-hand and right-hand (H3) (8) Work light roof frar inner right-hand (H3) (14) Region 4 Base Lighting - Cab Four Front Grille Headlights Two Front Outer Roof Worklights One Rear Right Roof Worklights Two Rear Fender Tail Lights with Brake Lights | |
| 873D | | Light Package - Economy Base lighting plus. Two hood corner lights (H3) (3). One work light left-hand on the rear roof (H3) (14). | 189.00 |
| 873U | | Light Package - Standard Base lighting plus. Two hood corner lights (H3) (3). | 429.00 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| | | LIGHTING PACKAGESContinued One work light left-hand on the rear roof (H3) (14). Two front inner work lights (H3). | |
| | | LIGHTING | |
| 873O | | 2 Beltline Road Lights - H4 If a frontloader or front hitch is installed road lights might be covered during road drive by frontloader boom or implement. For safety the lights delivered with this code replace the front grill road light function. two beltline mounted adjustable road lights (H4) (6) Not with Code 2074 (Low Clearance Cab). | 472.00 |
| 8725 | | Beacon Light Front cab roof mounted. Not with Code 2074 (Low Clearance Cab). | 208.00 |
| | | HITCH | |
| 8424 | | Draft Control Electronic Lower Link Sensing. Requires draft links (Codes 4110, 4112, 4113, 4120,4121). Electronic Lower Link Sensing. Requires Draft Links (Code 4110 or 4421). | 615.00 |
| | | DRAWBAR | |
| 8435 | | Drawbar - High Clearance Includes chainholder. Not compatible with Code 3810 (540 PTO) or 8434 (Swinging Drawbar with Hammerstrap). High Clearance with Sway Chains and Hammerstrap | 254.00 |
| | | REAR HITCH | |
| 8446 | | Rear Hitch Remote Control Left-hand and right-hand. | In Base Price |
| 8457 | | Higher Hitch Lift Capacity Capacity increase is achieved by bigger lift cylinders. 6110M and 6120M: 7,431 lbs (3,371 kg) | 376.00 |
| | | REAR POWER TAKE-OFF (PTO) | |
| 8385 | | Heavy-Duty Rear PTO Heavy-duty PTO option (for 540/1000 rpm PTO) includes ductile iron inner bearing support design for those heavy-duty PTO applications. | 301.00 |
| 8386 | | PTO Remote Control Left-hand and right-hand, mounted on rear fenders. Rear Remote PTO Control- LH Included with Standard Cab (Code 2073) | 62.00 |
| | | FRONT POWER TAKE-OFF (PTO) | |
| 8380 | | Preparation for Front Auxiliary Drive | 602.00 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | | FRONT POWER TAKE-OFF (PTO)Continued Includes torsion-damper and belt-pulley. Crankshaft Pulley without Drive Shaft | |
| 832J | | SELECTIVE CONTROL VALVES Power Beyond - Rear Allows the supply of hydraulic oil to implements with own control valves or hydraulic motors. It is a dedicated plate located on the RH side of the rockshaft providing four ports: pressure, load sensing, tank and drain. Allows Hydraulic Pump to power implements that have Independent Control Valves | 603.00 |
| | | (Electro-hydraulic stack valves on forage harvesters) or Orbital Motors (vacuum pump on planters). Provides a dedicated plate located on the RH side of the rockshaft providing four ports: pressure, load sensing, tank, and load drain. Includes pressure free return. Not available if tractor is equipped with 4 SCVs. | |
| | | FRONT LOADER PREPARATION | |
| 8924 | | Loader Preparation - Mechanical Midstack SCV - 3 Functions Includes 3 mechanical midstack SCVs: 3 function mechanical independent control valve, mechanical joystick: handle connected to the valve with cables, buttons on the joystick: front loader suspension, one rocker switch for the 3rd function plus wiring harnesses. Loader mounting frames, hood guard to be ordered separately, hydraulic connections from the valve up to front loader coupling point must to be ordered separately. Gear shifting buttons (Code 8214) included, without function on OOS tractors | 3,238.00 |
| 8925 | | Loader Preparation - Mechanical Midstack SCV - 2 Functions Includes 2 mechanical midstack SCVs: 2 function mechanical independent control valve, mechanical joystick: handle connected to the valve with cables, buttons on the joystick: front loader suspension, one rocker switch for the 3rd function (rocker switch not connected, plus wiring harnesses. Loader mounting frames, hood guard to be ordered separately, hydraulic connections from the valve up to front loader coupling point must to be ordered separately. Gear shifting buttons (Code 8214) included, without function on OOS tractors Includes: 2-function mid-mounted control valve with mechanical joystick control. | 2,687.00 |
| | | FRONT LOADER PACKAGES | |
| 891E | | Loader Ready Package - Mechanical SCV, 2 Functions Includes mechanical midstack SCV's: 2 function mechanical independent control valve, mechanical joystick: handle connected to the valve with cables, buttons on the joystick: front loader suspension plus wiring harness. Loader mounting frames, hood guard, hydraulic connections from the valve up to front loader coupling point, tractor half multicoupler. Gear shifting buttons (Code 8214) included, without function on OOS tractors For R-Series Front Loaders. Includes: 2-function mechanical joystick and inactive rocker switch, activated gear shifting buttons, 4-hydraulic hoses from mid-mount tractor valve to loader mounting frame, attached single point half coupler, loader mounting frame, and hood guard. | 4,687.00 |
| | | Note: Loader component of single point is ordered with loader. Front weight support is recommended. Compatible with 2-function R Series loaders. | |
| 891F | | Loader Ready Package - Mechanical SCV, 3 Functions Includes mechanical midstack SCV's: 3 function mechanical independent control valve, mechanical joystick: handle connected to the valve with cables, buttons on the joystick: front loader suspension, rocker switch for 3rd function plus wiring harnesses. Loader mounting frames, hood guard, hydraulic connections from the valve up to front loader coupling point, tractor half multicoupler. Gear shifting buttons (Code 8214) included, without function on OOS tractors For R-Series Front Loaders. | 5,503.00 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | | FRONT LOADER PACKAGESContinued Includes: 3-function mechanical joystick and activated rocker switch, activated gear shifting buttons, 6-hydraulic hoses from mid-mount tractor valve to loader mounting frame, attached single point half coupler, loader mounting frame, and hood guard. | |
| | | Note: Loader component of single point is ordered with loader. Front weight support is recommended. Compatible with 3-function R Series loaders. | |
| 0000 | | MISCELLANEOUS | 20.00 |
| 8002 | | Toolbox Left-hand side installed, on OOS behind driver's seat | 80.00 |
| 8781 | | License Plate Bracket - Rear Fender mounted. Not with Code 2074 (Low Clearance Cab). | 36.00 |
| | | SPECIAL PAINTING | |
| 8030 | | Special Painting - Industrial Yellow No RAL definition. John Deere owned colour. | 1,510.00 |
| 8031 | | Special Painting - Municipality Orange RAL2011 'Community Orange' Paint Finish | 1,510.00 |
| | | ATTACHMENTS FOR FIELD CONVERSION | |
| | BL15680 | Brakes Hydraulic Trailer Brake Kit PFC System, Basic, No Front Axle Brake | 761.20 |
| | BL15790 | Hydraulic Trailer Brake Kit PC System, without SFA, No Front Axle Brake | 599.50 |
| | BL15659 | Electrical Battery Cut-Off Switch Also Order Software AL216894. | 557.70 |
| | BL15726 | Radar, Dual Beam Attaching Kit See installation instructions for also order parts. Requires software AL220212. | 118.80 |
| | BL15427 | Engine Cold Weather Starting Package, 110 V, 4 cyl. Only compatible with AutoQuad and PowrQuad Transmissions. Includes engine block heater, charge pump preheater and all required hardware. | 852.50 |
| | BL15749 | Cold Weather Starting Package, 110 V, 4 cyl. Only compatible with AutoQuad and PowrQuad Transmissions. Includes engine block heater, charge pump preheater and all required hardware. | 559.90 |
| | BL15538 | DEF Tank Filler Neck Heater | 110.00 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| | BL15431 | ATTACHMENTS FOR FIELD CONVERSIONContinued Engine Block Heater, 4 cyl. Only compatible with 6R and 6M tractors. | 421.30 |
| | BL15206 | Front Auxiliary Drive | 1,230.90 |
| | BL15539 | Fuel Pre-Heater | 183.70 |
| | BL15384 | Stainless Steel Exhaust | 926.20 |
| | AL208651 | Fenders Fender Mud Guard | 58.30 |
| | BL15292 | Fender Side Extension Refer to installation instructions for additional hardware needed to complete installation on certain models. 110X15 for North America only. | 213.40 |
| | BL15293 | Fender Side Extension Refer to installation instructions for additional hardware needed to complete installation on certain models.200X20 for North America only. | 213.40 |
| | BL15650 | MFWD Front Fender, Turnable, 14.5 in. (370mm) Wide See Ag Sales Manual for compatible tire combinations. Not recommended for Loader Usage, Fender/Loader interference may occur. Also order BL15647 MFWD Front Fender, Turnable, Base Support Kit. | 874.50 |
| | BL15652 | MFWD Front Fender, Turnable, 16.5 in. (420mm) Wide See Ag Sales Manual for compatible tire combinations. Not recommended for Loader Usage, Fender/Loader interference may occur. Also order BL15647 MFWD Front Fender, Turnable, Base Support Kit. | 903.10 |
| | BL15654 | MFWD Front Fender, Turnable, 18.9 in. (480mm) Wide See Ag Sales Manual for compatible tire combinations. Not recommended for Loader Usage, Fender/Loader interference may occur. Also order BL15647 MFWD Front Fender, Turnable, Base Support Kit. | 917.40 |
| | BL15655 | MFWD Front Fender, Turnable, 21.3 in. (540mm) Wide See Ag Sales Manual for compatible tire combinations. Not recommended for Loader Usage, Fender/Loader interference may occur. Also order BL15059 MFWD Front Fender, Turnable, Base Support Kit. | 931.70 |
| | BL15656 | MFWD Front Fender, Turnable, 21.3 in. (540mm) Wide - Long See Ag Sales Manual for compatible tire combinations. Not recommended for Loader Usage, Fender/Loader interference may occur. Also order BL15059 MFWD Front Fender, Turnable, Base Support Kit. | 931.70 |
| | BL15646 | MFWD Front Fender, Turnable, 24.4 in. (620mm) Long See Ag Sales Manual for compatible tire combinations. Not recommended for Loader Usage, Fender/Loader interference may occur. Also order BL15059 MFWD Front Fender, Turnable, Base Support Kit. | 944.90 |
| | BL15658 | MFWD Front Fender, Turnable, 24.4 in. (620mm) Wide See Ag Sales Manual for compatible tire combinations. Not recommended for Loader Usage, Fender/Loader interference may occur. Also order BL15059 MFWD Front Fender, Turnable, Base Support Kit. | 944.90 |
| | AL180215 | MFWD Front Fenders, Fixed, 10.2 ln. (260 mm) Wide See Ag Sales Manual for compatible tire combinations. | 711.70 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| | BL15649 | ATTACHMENTS FOR FIELD CONVERSIONContinued MFWD Front Fenders, Fixed, 14.5 ln. (370 mm) Wide See Ag Sales Manual for compatible tire combinations. | 633.60 |
| | BL15651 | MFWD Front Fenders, Fixed, 16.5 In. (420 mm) Wide See Ag Sales Manual for compatible tire combinations. | 649.00 |
| | BL15653 | MFWD Front Fenders, Fixed, 18.9 In. (480 mm) Wide See Ag Sales Manual for compatible tire combinations. | 655.60 |
| | BL15648 | MFWD Front Fenders, Fixed, Base Support Kit Also order MFWD front fender kit in corresponding width and size. | 181.50 |
| | BL15771 | Stop Panel Kit for Turnable Front Fenders | 18.70 |
| | BL15550 | Guards Fuel Tank Bottom Guard 58 US Gal. (220L) | 249.70 |
| | BL15134 | Hitch and Drawbar Center Link, Hook Assembly Category 2 Hook Type | 1,071.40 |
| | AL81724 | Drawbar Drop-Down Kit Lowers the height of Drawbar by approximately 3 Inches. | 474.10 |
| | AL179161 | Guide Ball Holder, Category 2 | 111.10 |
| | AL180047 | Guide Ball Holder, Category 3 | 97.90 |
| | AL180493 | Hitch Raise/Lower Switch Requires Diagnostic Software Kit AL180889 ordered through Parts. Refer to installation instructions MHM1170. | 103.40 |
| | AL81619 | Holder for Hitch Cable | 66.00 |
| | BL15610 | Lift Cylinder for Increased Lift Capacity (75mm) | 889.90 |
| | BL15216 | Hydraulics Additional Oil Reservoir Increases the existing oil capacity to 3.7 gallons (14 liters). Pressure and Flow Compensated. | 552.20 |
| | BL15288 | Control Lever (Joystick) upgrade Converts PowerQuad Plus into AutoQuad Plus control. Requires software AL214131, see installation instructions. | 594.00 |
| | BL15710 | ICV Oil Line Kit Used only in Power Reverser applications. | 181.50 |
| | BL15711 | ICV Oil Line Kit Used only in PowerQuad Plus and 2WD applications. | 92.40 |
| | BL15712 | ICV Oil Line Kit Used only in PowerQuad Plus 4 range/PowerQuad and 4WD applications. | 92.40 |
| | BL15684 | ICV Oil Lines, PC Hyd System PB in Position #3 Independent Control Valve. Also order AL206034 power beyond and 3 studs L173495. | 345.40 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| | BL15685 | ATTACHMENTS FOR FIELD CONVERSIONContinued ICV Oil Lines, PC Hyd System PB in Position #4 Independent Control Valve. See installation instructons for also order parts. | 345.40 |
| | BL15635 | Lever M-ICV, 2-Function Mechanical Independent Control Valve.NOTE: A field kit for single-lever actuator and a field kit for oil lines must always be ordered in conjunction with a field kit for valve block. These field kits must be appropriate to the tractor and its equipment, and must be ordered through normal parts channels. | 1,949.20 |
| | BL15251 | M-ICV 2-Function to 3-Function Upgrade Mechanical Independent Control Valve. To convert from 2-Function to 3-Function. | 567.60 |
| | BL15634 | M-ICV, 2-Function Mechanical Independent Control Valve.NOTE: A field kit for single-lever actuator and a field kit for oil lines must always be ordered in conjunction with a field kit for valve block. These field kits must be appropriate to the tractor and its equipment, and must be ordered through normal parts channels. | 1,265.00 |
| | BL15682 | M-SCV, 200 Series And 450 Series Position 3 Mechanical Selective Control Valve. Kit contains deluxe quick coupler and leak-off oil parts for dust protector housing. | 437.80 |
| | BL15683 | M-SCV, 200 Series And 450 Series Position 4 Mechanical Selective Control Valve. Kit contains deluxe quick coupler and leak-off oil parts for dust protector housing. | 437.80 |
| | BL15812 | Power Beyond Coupler Impliment side flat face coupler. Size 20, ISO 16028. | 215.60 |
| | BL15813 | Power Beyond Coupler Impliment side flat face coupler case drain. Size 10, ISO 16028. | 47.30 |
| | AL176808 | Power Beyond Coupler, 1/2-Inch (12.5 mm) Coupler for Implement Kit contains three male Hose Tips and Dust Shields on Attachment Side for Connection of pressure, return and load sense. Kit does not contain Hydraulic Hoses. Requires Power Beyond Couplers (AL176299) 1/2-In. (12.5 mm) for Tractor End. | 280.50 |
| | BL15735 | Power Beyond Pressure Coupler, 1/2-Inch (12.5 mm) Also requires Power Beyond Return Coupler, BL15438. Additional also order parts are required. See installation instructions. | 279.40 |
| | BL15438 | Power Beyond Return Coupler 1/2-Inch (12.5 mm) Also requires Power Beyond Pressure Coupler, BL15435. Additional also order parts are required. See installation instructions. | 276.10 |
| | BL15737 | Power Beyond Return Coupler 3/4-Inch (20 mm) Also requires Power Beyond Pressure Coupler, BL15434. Additional also order parts are required. See installation instructions. | 297.00 |
| | BL15671 | Power Beyond Return Coupler, 3/4-Inch (19 mm), Flat Face Also requires Power Beyond Pressure Coupler, BL15432. Additional also order parts are required. See installation instructions. | 403.70 |
| | BL15739 | Power Beyond With External Pressure Free Return Includes complete Power Beyond supply and pressure free return coupler kits. Four connectors (Pressure, Return, Load Sense and Case Drain). | 279.40 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| | BL15740 | ATTACHMENTS FOR FIELD CONVERSIONContinued Power Beyond With External Pressure Free Return Includes only the Power Beyond pressure free return coupler kit. Two connectors (Return, Case Drain). | 72.60 |
| | BL15674 | Power Beyond Without External Pressure Free Return Includes complete Power Beyond supply and pressure free return coupler kits. Four connectors (Pressure, Return, Load Sense and Case Drain). | 165.00 |
| | BL15686 | V Oil Lines, PFC Hydraulic System | 345.40 |
| | AL205916 | Lighting (1) H3 Work Light Installed on beacon light support. | 152.90 |
| | BL15170 | (2) H3 Flood Lamps, Rear Cab Roof Mounted Additional also order parts and software required. See installation instructions. | 210.10 |
| | BL15169 | (2) H3 Work Lights, Front Cab Roof Mounted, LH and RH Additional also order parts and software required. See installation instructions. | 210.10 |
| | AL179972 | (2) H3 Work Lights, Rear Fender Mounted, LH and RH Also requires software, AL217733. Additional also order parts are required. See installation instructions. | 233.20 |
| | BL15174 | (2) HB3 Work Lights, Beltline Upright Mounted Also order software AL217716. | 295.90 |
| | AL111705 | Beacon Light, LH Requires Switch (AL181123). | 259.60 |
| | BL15716 | Beacon Light, RH | 256.30 |
| | BL15670 | Bracket, Headlights and Worklights | 23.10 |
| | AL201586 | Extremity Lights Preparation Kit See Parts Catalog and MHM 873 Installation Instructions for additional components. | 1,092.30 |
| | AL205881 | Head Lights H4 on Beltline, RH Additional also order parts required. Also requires software AL217713. See installation instructions. | 309.10 |
| | BL15257 | Hood Corner Work Lights | 480.70 |
| | AL206240 | Miscellaneous 2WD Front Axle (Tobacco Axle) | 1,536.70 |
| | BL15181 | Accumulator, Suspended Front Axle Adds 1 liter accumulator for suspended front axle in areas where cold climate or extreme cold temperatures are common. Compatible with pipe fitting using female thread M22 x 1.5. | 663.30 |
| | BL15202 | Accumulator, Suspended Front Axle Adds 1 liter accumulator for suspended front axle in areas where cold climate or extreme cold temperatures are common. Compatible with pipe fitting using male thread M27 x 2. | 663.30 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | BL15201 | ATTACHMENTS FOR FIELD CONVERSIONContinued Accumulator, Suspended Front Axle Adds 1.4 liter accumulator for suspended front axle in areas where cold climate or extreme cold temperatures are common. Compatible with pipe fitting using male thread M27 x 2. | 663.30 |
| | BRE10015 | Cell phone mount kit | 61.60 |
| | BRE10151 | Front Utility Box Must also order Front Utility Box Bracket (BRE10153). Utility Box is intended for front tractor mounting only. | 349.80 |
| | BRE10153 | Front Utility Box Bracket Compatible only with front suitcase weight R127764. You must have a minimum of 4 suitcase weights and a maximum of 22 suitcase weights. | 121.00 |
| | BL15006 | Screen, Condenser Compatible on tractors without air conditioning. | 85.80 |
| | AL204829 | Tool Box | 283.80 |
| | BL15295 | Window decal, rear John Deere logo. | 22.00 |
| | AL203919 | Operator Environment 3-Terminal Socket | 85.80 |
| | AL204297 | Backrest Extension, Telescopic | 159.50 |
| | BL15522 | Bottle Holder, Floormat | 47.30 |
| | BL15387 | Deluxe Radio Also order software varies by model, see installation instructions for complete list. | 385.00 |
| | | Also order (1) Radio Button - BL15585. Reference installation instructions for more information. | |
| | BL15385 | Deluxe Radio with CD Also order software AL216783. Only for North America (region 4). | 429.00 |
| | BL15158 | Display Bracket For mounting display and implement controls. | 167.20 |
| | AL178985 | Field Office without Beverage Holder Compatible with Instructional Seat. | 257.40 |
| | AL173569 | Instructional Seat, Unsuspended Includes seatbelt. | 652.30 |
| | AL151224 | Mirror, Inside Rear | 172.70 |
| | AL80126 | Mirror, Telescopic, LH, Manually Adjustable | 177.10 |
| | AL80127 | Mirror, Telescopic, RH, Manually Adjustable | 177.10 |
| | AL174215 | Power Strip with Six Outlets | 82.50 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| | BL15082 | ATTACHMENTS FOR FIELD CONVERSIONContinued Presence Switch, Operator Seat For air suspended seat. See installation instructions for additional parts and/or software required. | 187.00 |
| | AL180494 | Remote Switch, PTO Also requires software, AL210796. Also order AL174668. See installation instructions. | 102.30 |
| | BL15037 | Seat, Operator Air suspended (value spec.). Includes seatbelt. See installation instructions for additional parts and/or software required. | 1,501.50 |
| | BL15038 | Seat, Operator Air suspended (mid spec.). Includes seatbelt. See installation instructions for additional parts and/or software required. | 2,004.20 |
| | BL15278 | Seat, Operator - Mechanical Suspension See installation instructions for additional parts and/or software required. Includes foldable armrests, seatbelt, and salt and pepper colored fabric. | 919.60 |
| | AL117734 | Seatbelt for Instructional Seat | 68.20 |
| | AL157620 | Sun Visor Flip down style. | 105.60 |
| | BL15198 | Sunshade Compatible in front, side, and rear. Pull to unroll style. | 192.50 |
| | AL173570 | Suspension for Instructional Seat | 267.30 |
| | BRE10255 | Tablet Mount Kit Compatible with all accessory mounting brackets (RE343680, RE162262, RE245374, RE317435, BRE10141). With 1.5 inch toughball mount for increased tablet stability over original BRE10034. | 85.80 |
| | AL208658 | Wiper/Washer, Rear | 254.10 |
| | BL15629 | Wiper/Washer, Rear | 254.10 |
| | BL15231 | iTEC Headland Management System Reference Installation Instructions. Also order software AL213360. | 30.80 |
| | AL158728 | Transmission Back-up Alarm | 595.10 |
| | BL15622 | Creeper Field Kit for PowrQuad Transmissions Reference Installation Instructions. | 1,521.30 |
| | BL15623 | Creeper Kit for AutoQuad and PowrQuad PLUS Transmissions, 6-Range Reference Installation Instructions for also ordering parts and software. 40k Speed Radius Index 750, 775 50k Speed Radius Index 700, 725, 800, 825, 875 | 1,521.30 |
| | BL15624 | Creeper Kit for AutoQuad and PowrQuad PLUS Transmissions, 6-Range Reference Installation Instructions for also ordering parts and software. 40k Speed Radius Index 700, 725, 800, 825, 875 50k Speed Radius Index 750, 775 | 1,521.30 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| | BL15625 | ATTACHMENTS FOR FIELD CONVERSIONContinued Creeper Kit for PowrQuad PLUS Transmissions, 4-Range Reference Installation Instructions. | 1,521.30 |
| | BL15709 | Creeper Module Required for Power Reverser, PowerQuad, PowerQuad Plus, or with 40k Speed Radius Index 700,725,800,825,875; and 50k Speed Radius Index 750,775. | 477.40 |
| | BL15708 | Creeper Module Required for Power Reverser, PowerQuad, PowerQuad Plus, or with 40k Speed Radius Index 750,775; and 50k Speed Radius Index 700,725,800,825,875. | 870.10 |
| | AL213767 | Creeper Shift Components Required for creeper retrofit. | 151.80 |
| | BL15714 | Creeper Shift Components Required for Power Reverser, PowerQuad Plus 4 range/PowerQuad 4 range. | 151.80 |
| | BL15715 | Creeper Shift Components Required for PowerQuad Plus 6 range/PowerQuad 6 range. | 151.80 |
| | BL15702 | Creeper, Assembly Parts Required for electronic PowerQuad Plus 6 range. | 101.20 |
| | BL15706 | Creeper, Countershaft Required for Power Reverser, PowerQuad Plus 4 range/PowerQuad 4 range. | 387.20 |
| | BL15707 | Creeper, Countershaft Required for PowerQuad Plus 6 range/PowerQuad 6 range. | 387.20 |
| | AL71345 | Vandal Protection Vandal Protection, Door Locks - Custom Key Includes Lockable Door Handles (2). Key is different than that used to start Tractor. | 192.50 |
| | BL15086 | Vandal Protection, Hood | 146.30 |
| | AL211572 | Vandal Protection, Lockable DEF Cap | 44.77 |
| | AL113087 | Vandal Protection, Lockable Fuel Tank Cap | 36.73 |
| | AL213203 | Vandal Protection, Lockable Fuel Tank Cap | 32.76 |
| | BL15362 | Vandal Protection, Lockable Transmission Oil Filler Cap | 156.20 |
| | BL15869 | Vandal Protection, Lockable Transmission Oil Filler Cap | 156.20 |
| | AL157299 | Weights Front Shield Protecting the frame end. | 52.80 |
| | R127764 | Front Weight For front mount balasting. 43.1 kg (95 lbs) each. High gloss green paint. North American applications. | 134.20 |
| | AL176565 | Front Weight Carrier, 243 Lb. (110 Kg) | 402.67 |

6120M Cab Tractor

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | R167153 | ATTACHMENTS FOR FIELD CONVERSIONContinued Starter Weight, Wheel, 159 Lb. (72 Kg) | 246.40 |
| | T21689 | Weight, Rear Wheel, 107 Lb. (49Kg) Please verify compatibility with the wheel weight matrix before ordering any weights. | 166.10 |
| | R56920 | Weight, Rear Wheel, 110 Lb. (50Kg) Please verify compatibility with the wheel weight matrix before ordering any weights. | 142.26 |
| | R61524 | Weight, Rear Wheel, 135 Lb. (61Kg) Please verify compatibility with the wheel weight matrix before ordering any weights. | 358.60 |
| | AR112536 | Weight, Rear Wheel, 440 Lb. (200Kg) (4-R56920) Requires Steel Wheels. Not compatible with Rack and Pinion Axle. Please verify compatibility with the wheel weight matrix before ordering any weights. | 1,518.00 |
| | APY10029 | Weight, Rear Wheel, 480 Lb. (218Kg) (4-L28228) Please verify compatibility with the wheel weight matrix before ordering any weights. | 746.90 |
| | R207782 | Weight, Wheel, 452 Lb. (205 kg) Please verify compatibility with the wheel weight matrix before ordering any weights. | 701.80 |
| | L28228 | Weight, Wheel, 120 Lb. (54Kg) Please verify compatibility with the wheel weight matrix before ordering any weights. | 299.02 |
| | BL15934 | Wheel Equipment Wheel Reinforcements, Rear For models with 8in. (203mm) bolt circle diameter. | 1,666.50 |
| | AL156776 | Wheel Spacer Rear, 1.2in. (30mm) each side, for BCD=203mm | 680.90 |
| | AL156778 | Wheel Spacers, MFWD, 2.36 In. (60 mm) with Hardware (Qty 2) Increased Tread Setting from 2016 mm to 2134 mm. 8 Bolt Patterns (275 mm diameter). | 680.90 |
| | AL156779 | Wheel Spacers, Rear, 1.73 In. (44 mm) with Hardware (Qty 2) | 556.60 |
| | AL156777 | Wheel Spacers, Rear, 4.37 In. (111 mm) with Hardware (Qty 2) | 713.90 |

G120M Cab Tractor Continued THIS PAGE IS INTENTIONALLY LEFT BLANK

6135E Cab Tractor (114 PTO hp)

Equipment for Base Machine

ENGINE: John Deere PowerTech PWS Diesel Engine In-line 4-Cylinder Wet-Sleeve with High Pressure Common Rail (HPCR) Fuel System and 16 Valve Head 4.5 L (276 Cu. In.) Displacement 135 Engine Horsepower [97/68/EC] @ Rated Speed 114 SAE PTO Horsepower @ Rated Speed High Pressure Common Rail Wastegate Turbocharger and Exhaust Gas Recirculation Closed Cooling System PowerCore Air Filtration System with Permanent Pre-Cleaning and Safety Element Underhood AfterTreatment System with Deluxe Cornerpost Exhaust 41.7 Gal (158 L) Fuel
Tank Capacity TRANSMISSION: 12 Forward / 12
PowrReverser Transmission (19 mph (30km/h) LH Power
Reverser Wet Multi-Disk Clutch Mechanically Actuated Park Brake Neutral Safety Start System STEERING, BRAKES, DIFFERENTIAL: Hydrostatic Steering Sealed Wet Disk Rear Axle Differential Lock HYDRAULICS: Open Center 20.0 GPM (75.7 L/min) Flow @ Rated Speed (2200) 2 SCV's; Mechanical; ISO Breakaway Couplers REAR PTO: 540/1000 PTO Speeds, 1-3/8 In. Independent Rear PTO, Reversible Shaft and PTO Master Shield Electrohydraulic PTO Activation Wet Clutch Neutral Start Safety System Seat Activated PTO Warning ROCKSHAFT, HITCH AND DRAWBAR: Mechanical Hitch Category 2, 3-Point Hitch Mechanical Hitch Control 5500 Lb. (2500 kg) Lift 3-Point Hitch Capacity Telescopic Draft Links Sway Chain Retainers Category 2 Drawbar; Swinging Safety Chain Holder INSTRUMENTATION: Tachometer Speedometer Hour Meter Fuel Gauge Engine Oil Pressure Coolant

Temperature PTO Engagement Engine Air Filter Alternator Directional Indicators Hazard Switch Park Brake Indicator MFWD Indicator CAB OPERATOR STATION: Air Conditioning and Heater 2 Doors Front Fixed Windshield Wiper and Washer Mechanical Seat with Seat Belt Tilt / Telescopic Steering Column Right Hand and Left Hand Foot Steps Operational Controls, RH Console Floor Mat Foot Throttle Control Power Outlet Pre-Radio Wiring and Speaker Package Overhead Courtesy Light Two Cup Holders RH & LH Fixed External Mirrors ELECTRICAL: Key Shutoff 12-Volt Electrical System 12-Volt Battery, 925 Cold Cranking Amps 90 Amp Alternator 7 Terminal ASAE Outlet Socket LIGHTS: Two Front Grille Headlights Two Front Roof Lights Two Rear Roof Lights Flashing Hazard Lights Two Rear Fender Tail Lights with Brake Lights FRONT AXLE WHEELS AND TIRES: MFWD Steel Wheels Electrohydraulic MFWD Engagement, Right-hand Console 13.6-24 In. 8PR R1 Bias Tires REAR AXLE WHEELS AND TIRES: Flange Axle 8 Position Steel Wheels 18.4-34 In. 8PR Rl Bias MISCELLANEOUS: Operator's Manual (English) and Holder SMV Emblem Horn Fuel Tank Guard

| | | | SUGGESTED |
|------|------------|-------------|------------|
| | ATTACHMENT | | LIST PRICE |
| CODE | IDENTIFIER | DESCRIPTION | USD (\$) |

Select One Code From Each Required Category

BASE MACHINE

| 334RP | 6135E Cab Tractor (114 PTO hp) | 86,803.00 |
|-------|---|---------------|
| | | |
| | DESTINATION | |
| 0202 | United States | In Base Price |
| 0184 | Canada | Same Price |
| 0203 | Puerto Rico | Same Price |
| | OPERATOR'S MANUAL | |
| 0409 | English Operator's Manual North America | In Base Price |
| 0437 | Spanish Operator's Manual North America Includes Warning Labels in Spanish. | Same Price |
| 0413 | French Operator's Manual North America Includes Warning Labels in Spanish. | Same Price |
| | PACKAGE CONFIGURATIONS | |
| 0500 | No Package | In Base Price |

6135E Cab Tractor (114 PTO hp) Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| 0521 | | PACKAGE CONFIGURATIONSContinued Cab MFWD 2-SCV 12F/12R PowrReverser Air Seat Value Package Cab Tractor with MFWD, 12F/12R PowrReverser Transmission, Air Seat, Two Telescopic Draft Links and Two Selective Control Valves. | In Configuration |
| | | Package contains Codes: 2050,1383,2130, 4120, and 3320. | |
| 0526 | | Priority Replenishment Unit Cab Tractor with MFWD, 24F/12R PowrReverser Transmission, Air Seat, Two Telescopic Draft Links, Two Selective Control Valves, 18.4-38 In. R1 Rear Tires, 14.9-24 In. R1 Front Tires, and 2 function Loader Ready Package. | In Configuration |
| | | Package contains Codes: 2050, 1386, 2130, 4120, 3320, 5234, 6220 and 8910. | |
| | | OPERATOR'S STATION | |
| 2050 | | Standard Cab | In Base Price |
| 2000 | | Cianadra Gab | III Base I nice |
| | | SEAT | |
| 2100 | | Mechanical Suspension Seat (MSG85) Scissor-type suspension; Operator presence switch; Seat belt with retractor; Operator's Manual holder on seat; Flip up armrest; Adjustable armrest height and backrest angle; Lumbar adjustment; No swivel. | In Base Price |
| 2130 | | Air Suspension Seat with Swivel (MSG 95) Scissor-type suspension; Operator presence switch; Seat belt with retractor; Operator's Manual holder on seat; Flip up armrest; Adjustable armrest height, backrest angle, and lower seat cushion; Fore-aft attenuator; Lumbar adjustment; 15 degree Seat swivel | 860.00 |
| | | TRANSMISSION | |
| 1383 | | 12F/12R PowrReverser Transmission (19mph/30kmh) - MFWD Axle MFWD Axle. 540/1000 rpm PTO. Requires code 6120 or 6220. | In Base Price |
| 1386 | | 24F/12R PowrReverser Transmission (25mph/40kmh) - MFWD Axle MFWD Axle.540/1000rpm PTO. Includes: Electrohydraulic high/low button. Requires code 6210 or 6220. | 1,211.00 |
| | | SELECTIVE CONTROL VALVES | |
| 3320 | | Dual Standard SCV with ISO Breakaway Couplers Four Positions in each spool: Raise, Off/Neutral, Lower, and Float. Provides detent in Float position. See Ag Sales Manual for details. | In Base Price |
| 3340 | | Triple Deluxe SCV with ISO Breakaway Couplers Spools 1, 2, and 3 have three detent choices: - Pressure Limit Kick-out (cylinder use)- Spring Center (front loader use)- Continuous Detent (hydraulic motor use) Spool #1 has Pressure-Compensated Flow Control and priority over Spools 2 & 3. See Ag Sales Manual for details. | 372.00 |
| | | DRAFT LINK | |
| 4120 | | Two Telescopic Draft Links | In Base Price |
| | | STABILIZER | |

6135E Cab Tractor (114 PTO hp) Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|--|-------------------------------------|
| 4420 | | STABILIZERContinued Sway Chain with Retainers | In Base Price |
| 4421 | | Sway Bars | Same Price |
| | | HITCH TYPE | |
| 4015 | | Standard Hitch Hitch lift capacity 5500lb (2500kg) | In Base Price |
| 4020 | | Heavy Duty Hitch Hitch lift capacity 7300lb (3318kg) | 372.00 |
| | | DRAWBAR | |
| 4315 | | Standard Drawbar | In Base Price |
| 4320 | | Heavy Duty Drawbar | 239.00 |
| | | FRONT WHEELS AND TIRES | |
| 6210 | | 340/85R24 In. 8PR R1 Radial Available in Continental/Mitas. Only available with Code 5212. Requires 12F/12R PowrReverser Transmission (19 mph/30 kmh) - MFWD Axle (Code 1383) or 24F/12R PowrReverser Transmission (25 mph/40kmh) - MFWD Axle (Code 1386). | In Base Price |
| 6220 | | 380/85R24 In. 8PR R1 Radial Available in Continental/Mitas. Only available with Code 5234 or 5221. Requires 12F/12R PowrReverser Transmission (19 mph/30 kmh) - MFWD Axle (Code 1383) or 24F/12R PowrReverser Transmission (25 mph/40kmh) - MFWD Axle (Code 1386). | 148.00 |
| 6200 | | 320/85R24 In. 8PR R1 Radial <i>Available in Mitas</i> . | 322.00 |
| | | REAR WHEELS AND TIRES | |
| 5234 | | 460/85R38 In. 8PR R1 Radial Available in Continental/Mitas. | 726.00 |
| 5212 | | 460/85R34 In. 8PR R1 Radial Available in Continental/Mitas. | In Base Price |
| 5221 | | 420/85/R38 In. 8PR R1 Radial Available in Continental/Mitas. | 420.00 |
| 5460 | | 300/95R42 R1 Radial Available in MITAS | -85.00 |
| | | CAB EQUIPMENT | |
| 8261 | | Cab with Loader View Roof includes sun visor | 561.00 |
| 8254 | | Instructional Seat | 546.00 |

6135E Cab Tractor (114 PTO hp) Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | | LIGHTING | |
| 8726 | | Rotating Warning Light (Beacon Light) | 219.00 |
| | | FRONT LOADER PACKAGES | |
| 8910 | | 2-Function Mechanical Independent Control Valve Loader Ready Includes: 2-Function Mechanical Joystick, 4-hydraulic hoses from mid-mount tractor valve to loader mounting frame, individual quick couplers, H-series loader mounting frames, hood guard, and toolbox. Note: This package includes both the tractor and loader halves of the quick coupler connection. | 3,273.00 |
| 8911 | | 3-Function Mechanical Independent Control Valve Loader Ready Includes: 3-Function Mechanical Joystick, 6-hydraulic hoses from mid-mount tractor valve to loader mounting frame, individual quick couplers, H-series loader mounting frames, hood guard, and toolbox. Note: This package includes both the tractor and loader halves of the quick coupler connection. | 4,016.00 |
| | | MISCELLANEOUS | |
| 8461 | | Draft Control | 590.00 |
| 8002 | | Tool Box | 49.00 |
| | | SPECIAL PAINTING | |
| 8030 | | John Deere Industrial Yellow Paint Finish | 1,472.00 |
| | | FRONT FENDERS | |
| 8010 | | Fixed Front Fenders (MFWD Front Axle only) Not compatible with Front Loader Ready Packages (Code 8910 or 8911). | 573.00 |
| | | FRONT WEIGHTS | |
| 8995 | | Front Weight Support Bracket Holds up to eighteen 100-Lbs suitcase weights. | 268.00 |
| | | REAR WHEEL WEIGHTS | |
| 8970 | | Two Rear Wheel Weights Two - 120 Lb (54 kg) weights. | 309.00 |
| 8971 | | Four Rear Wheel Weights Four - 120 Lb (54 kg) weights. | 617.00 |
| 8972 | | Six Rear Wheel Weights Six - 120 Lb (54 kg) weights. | 926.00 |
| 8973 | | Eight Rear Wheel Weights Eight - 120 Lb (54 kg) weights. | 1,235.00 |

ATTACHMENTS FOR FIELD CONVERSION

6135E Cab Tractor (114 PTO hp) Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | | ATTACHMENTS FOR FIELD CONVERSIONContinued | |
| | RE227949 | Engine Engine Block Heater (110V) | 108.37 |
| | BSJ10210 | Radiator Screen kit field Removable screen helps maintain good radiator air flow. | 35.20 |
| | BSJ10216 | Fenders Fixed Front Fenders (MFWD only) | 625.90 |
| | LVB25714 | Rear Fender Extension Kit | 213.40 |
| | BSJ10042 | Hitch and Drawbar Hammerstrap | 191.40 |
| | BSJ10046 | Heavy Duty Drawbar | 366.30 |
| | BSJ10045 | Heavy Duty Hitch: Hitch Lift Capacity: 7300 lb (3318 kg) | 531.30 |
| | BSJ10047 | Mechanical Draft Sensing | 702.90 |
| | TY16042 | Quik-Coupler, Economy, Category 2 | 580.37 |
| | BSJ10218 | Hydraulics Dual Function Mid SCV to Triple Function Mid SCV Conversion Includes valve, with switch and harness for third function. (Does not include loader mounting frames). | 1,784.20 |
| | BSJ10219 | Dual Function Mid SCV with Joystick Control Kit Does not include loader mounting frames or quick connect hose couplers. | 1,433.30 |
| | BSJ10212 | Rear SCV Oil Collection Kit Environmental system for collecting small drips of hydraulic oil during implement connection and removal process at the SCV. | 66.00 |
| | BSJ10221 | Triple Function Mid SCV Kit Does not include loader mounting frames or quick connect hose couplers. | 2,129.60 |
| | LVB25720 | Lighting Auxiliary Work Light Kit (2 Lights) For Cab Tractors Only. | 151.80 |
| | BLV10120 | Beacon Light Kit | 237.60 |
| | BSJ10026 | Miscellaneous Backup Alarm Kit Compatible with PowrReverser transmission only. | 78.10 |
| | LVB25727 | PowrReverser Modulation Control Kit | 150.70 |

6135E Cab Tractor (114 PTO hp) Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | SU34006 | ATTACHMENTS FOR FIELD CONVERSIONContinued Tool Box Also order bracket SU25610, and hardware 19M8184(2), 14M7166(4), and 19M7866(4). | 52.93 |
| | SJ10170 | Operator Environment Antenna | 29.96 |
| | RE321102 | Radio, Deere/Delco AM/FM Stereo with Clock, Front Audio Input Jack for MP3 Players, and Weatherband Requires Standard Cab Antenna Kit (L113922) ordered separately through Parts. | 477.40 |
| | RE321109 | Radio, Deere/Delco AM/FM Stereo with Single Compact Disc Player, Clock, Front Audio Input Jack for MP3 Players, and Weatherband Requires Standard Cab Antenna Kit (L113922) Ordered Separately through Parts. | 933.90 |
| | BLV10173 | Wiper/Washer, Rear | 345.40 |
| | BSJ10215 | Vandal Protection Vandal Protection Package (Includes Lockable Transmission Oil Fill, Lockable Hood, Lockable Oil Fill Cap and lockable DEF cap.) | 143.00 |
| | AL71345 | Vandal Protection, Door Locks - Custom Key Includes Lockable Door Handles (2). Key is different than that used to start Tractor. | 192.50 |
| | AL113087 | Vandal Protection, Lockable Fuel Tank Cap | 36.73 |
| | R127764 | Weights Front Weight | 134.20 |
| | BSJ10217 | Front Weight Support Bracket | 345.40 |
| | APY10029 | Weight, Rear Wheel, 480 Lb. (218Kg) (4-L28228) | 746.90 |