5055E Utility Tractor (41-45 PTO hp) Equipment for Base Machine

ENGINE: 57 (42.0 kW) 97/68/EC Engine Horsepower @ 2100* RPM 45 (33.1 kW) PTO Horsepower @ 2100 ERPM (Open Station) 41 (30.1 kW) PTO Horsepower @ 2100 ERPM (Cab) 3 Cylinder Turbocharged John Deere PowerTech Diesel Engine 179 C.I.D. (2.9L) EPA Final Tier 4 Compliant Dry Type Air Cleaner with Safety Element Underhood Muffler with Vertical Exhaust Stack Anti-Freeze Hand and Foot Throttles Key Engine Shutoff Fan Finger Guard Heavy Duty Air Intake Pre-Heater Fuel Cooler TRANSMISSION: 9F/3R TSS 9F/3R SyncShuttle Synchronized Speed Shifts, Integrated Park Position Right Hand Shifted Speeds Left Hand Shifted Ranges Differential Lock Neutral Start Safety Switch REAR AXLE: Flanged Rear Axle Planetary Final Drives

STEERING AND BRAKES: Hydrostatic Power Steering Hydraulically Actuated Wet Disk Brakes Self-Equalizing and Self-Adjusting

HYDRAULICS: Open Center Hydraulic System Tandem Gear Pump 18.2 GPM (68.9 LPM) Maximum Total Flow Steering Pump 6.8 GPM (25.7 LPM) Implement Pump 11.4 GPM (43.1 LPM) 2 One Rear Selective Control Valve

POWER TAKE-OFF SHAFT: 9x3 TSSTransmission Independent "Live" 540 RPM Rear PTO Shaft Operator Presence Safety Warning - PTO Flip Up PTO Shield Safety Start Switch ROCKSHAFT, HITCH AND DRAWBAR: Rear Rockshaft with Position Control, Draft Control, and Adjustable Rate of Drop 3-Point (Category II) Hitch

with Sway Chains -Convertible to Category I Adjustable Drawbar INSTRUMENTATION: Electric Fuel Gauge Tachometer/Hour Meter Oil Pressure Indicator Light Coolant Temperature Gauge Alternator Indicator Light Air Restriction Indicator Light Turn Signal Indicator Light High Beam Light PTO Engagement Light Digital Display - Hour Meter ELECTRICAL: Open Station 12-Volt Electrical System One Battery - 623 CCA** with 145 Minute Reserve Capacity 40 Amp Alternator LIGHTS: Two Front Halogen Headlights Two Turn/Flashing Warning Lights Two Tail Lights One Rear Work Light (Open Station) MISCELLANEOUS: SMV Emblem Tilt-Up Hood Toolbox BASE MACHINE: Open Station 2-Post Foldable Roll-Over Protective Structure (ROPS) Deluxe Adjustable Vinyl Seat with Retractable Seat Belt 18 U.S. Gallon (68 L) Fuel Tank Capacity Adjustable Front Axle (56-80 In.) 8-Position Steel Rear Wheels with

Two Rear Tires 14.9-28 6PR (R1) 2-Position Steel Front Wheels with Two Front Tires 7.50-16 6PR (F2)

* Manufacturer's Rating ** Cold Cranking Amps

ATTACHMENT CODE IDENTIFIER DESCRIPTION

Select One Code From Each Required Category

	BASE MACHINE	
1734LV	5055E Utility Tractor (41-45 PTO hp)	22,097.00
	OPERATORS MANUAL	
0409	English Operators Manual and Decal Kit	In Base Price

0413

French Operators Manual and Decal Kit

11 May 2015 US & Canada 2-TRACTOR- 1

SUGGESTED LIST PRICE USD (\$)

Same Price

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
		OPERATORS MANUALContinued	
0437		Spanish Operators Manual and Decal Kit	Same Price
		TRANSMISSION	
1363		9F/3R SyncShuttle Transmission (TSS) 9F/3R Full Top Shaft Synchronized [TSS] Synchronized Speed Shifts Integrated Park Position Code 1363 with Code 2050 - Standard Cab is available only on 5055E (Base Code 1734LV)	In Base Price
1381		12F/12R PowrReverser Transmission - 540/540E (PR) Electrohydraulic (EH) Directional Reverser Wet Traction Clutch Wet PTO Clutch Neutral Start Safety Switch Electrohydraulic (EH) PTO engagement Economy-PTO/Standard PTO MFWD indicator light Digital hour meter indicator Digital ground speed indicator Digital PTO speed indicator Requires Code 6040 - MFWD.	2,160.00
		OPERATOR STATION	
2000		Open Operator Station Fixed Open Operator Station 2 Post Foldable Roll-Over Protection Structure (ROPS) Beverage Holder Single Rear Work Light 18 Gallon Fuel Tank	In Base Price
2050		Cab Left Side Door Air Conditioning Cup Holders Radio/CD Ready (Antenna Cable,Two Speakers, and Wiring Harness) Front Windshield Wiper Mechanical Suspension Seat 21.6 Gallon Fuel Tank Requires Code 6040 MFWD. Requires Code 4120 Telescopic Draft Link.	7,488.00
		MID SELECTIVE CONTROL VALVES	
3400		Less Mid Valves Recommended for applications WITHOUT front loaders. Can later be upgraded for front loader and/or other hydraulic applications using field-installed attachments. Requires Code 6020 - 2WD. In order to install dual mid valves in the field, order kit BSJ10083.	In Base Price
3420		Dual Mid Valves with Joystick Control Recommended for applications WITH front loaders. Requires Code 6040 - MFWD.	1,162.00
		DRAFT LINKS	

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
4115		DRAFT LINKSContinued Fixed Draft Links	In Base Price
4120		Telescopic Draft Links	518.00
		REAR WHEELS WITH TIRES (TWO)	
5101		14.9-28 ln. 6PR R1 Bias Code 6020 requires Code 6102. Code 6040 requires Code 6101.	In Base Price
5103		22.5LL-16.1 In. 6PR R3 (Turf Special) Bias <i>Requires Code 6103</i> .	1,033.00
5113		21.5L-16.1 In. 6PR R3 Bias Code 6020 requires Code 6103. Code 6040 requires Code 6171.	-365.00
5184		16.9-24 In. 6PR R4 Bias Code 6020 requires Code 6113. Code 6040 requires Code 6133.	-106.00
5185		16.9-28 In. 6PR R1 Bias Code 6020 requires Code 6102. Code 6040 requires Code 6101.	256.00
		FRONT AXLE	
6020		2 Wheel Drive Requires Code 1363.	In Base Price
6040		MFWD (4 Wheel Drive) Mechanical Engagement. Engagement Indicator Light on PowrReverser Transmission. Requires Code 3420.	5,296.00
		FRONT WHEELS WITH TIRES (TWO)	
6102		FOR OPTION CODE 6020 (2WD): 7.50-16 In. 6PR F2 Bias Requires Code 2000 - Open Operator Station.	In Base Price
6103		27/12LL-15 In. 6PR Turf Special Bias Requires Code 2000 - Open Operator Station.	486.00
6113		11L-15 In. 8PR F3 (Truck Type) Bias Requires Code 2000 - Open Operator Station.	114.00
6101		FOR OPTION CODE 6040 (MFWD): 9.5-24 In. 6PR R1 Bias	1,052.00
6133		12.5/80-18 In. 6PR I3(R4 Type) Bias	728.00
6171		9.5-16 In. 6PR R3 Bias	396.00

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION	
	L154683	Axle - Rear: Rear Axle 1.2 In. Extension (30 mm) <i>Two required.</i> <i>Requires (16) 19M9364 Cap Screws (8 per Extension), ordered separately.</i>	168.82
	L154682	Rear Axle 1.6 In. Extension (40 mm) Two required. Requires (16) 19M8979 Cap Screws (8 per Extension), ordered separately.	197.95
	L154684	Rear Axle 4.4 In. Extension (111 mm) <i>Two required.</i> <i>Requires (16) 19M9365 Cap Screws (8 per Extension), ordered separately.</i>	279.43
	LV150155	Engine: Engine Coolant Heater Kit (3 Cyl.)	96.80
	LVB25714	Fenders: Rear Fender Extension Kit Cab Tractors only.	209.00
	BSJ10044	Rear Fender Extension Kit without Work Lights Open Station Tractors only.	335.50
	T12553	Hitch and Drawbar: Center Link Conversion Bushing, Cat. II to Cat. I <i>One required.</i>	13.45
	R66432	Draft Link Conversion Bushing, Cat. II to Cat. I Two required.	16.04
	R133359	Drawbar - Offset	310.00
	RE39830	Drawbar Clevis Kit (Hammer Strap) - Offset Drawbar	246.55
	RE39829	Drawbar Clevis Kit (Hammer Strap) - Straight Drawbar	282.28
	TY16042	Quik-Coupler, Economy, Category 2	580.37
	SJ11072	Hitch: Left Hand Telescopic Draft Link	367.78
	SJ11073	Right Hand Telescopic Draft Link	367.78
	LVB25976	iMatch Quick Hitch Category 1 with adjustable top hook Includes one set of Bushings(LVU15507). Not compatible on a 5115M.	357.50
	BSJ10083	Hydraulic Controls: Mid-Mount Dual SCV with Joystick Control Compatible with Open Station 2WD Tractors.	1,411.30

CODE	ATTACHMENT	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
		ATTACHMENTS FOR FIELD CONVERSIONContinued	
	BLV10347	Hydraulics: Mid-Mount Dual SCV with Joystick Control <i>Compatible with 5E Cab Tractors</i> .	1,411.30
	LVB25771	Second Rear SCV with Detented Float and Lever Control <i>For 9x3 TSS Open Station Tractors.</i>	805.20
	BLV10348	Second Rear SCV with Detented Float and Lever Control <i>Compatible with 5E Cab Tractors</i> .	805.20
	BLV10431	Second Rear SCV with Detented Float and Lever Control For 12x12 PR Open Station Tractors.	805.20
	LVB25547	Lighting: Auxiliary Rear Work Light Kit (1 Light) Open Station Only.	63.80
	BLV10120	Beacon Light Kit	236.50
	LVB25728	Miscellaneous: Backup Alarm Kit Compatible with 5E 3-Cyl Cab tractors and PR Open Station Tractors.	161.70
	LVB25817	Backup Alarm Kit NOT compatible with 2WD front axle and 5D Series Tractors. Compatible with 5E 3-Cyl TSS open station tractors only.	161.70
	BSJ10063	Creeper Gear Kit For 9F/3R TSS transmission only.	855.80
	BLV10407	Operator's Manual and Decal Kit - French	0.00
	BLV10406	Operator's Manual and Decal Kit - Spanish	0.00
	LVB25727	PowrReverser Modulation Control Kit For 12x12 PR Tractors Only.	147.40
	LVB25926	Single Horn Kit OOS tractors only	51.70
	LVB26096	Single Horn Kit CAB tractors only.	51.70
	SJ10170	Operator Environment: Antenna <i>Cab only</i>	28.49
	AH104259	Ash Tray Cab only.	50.62
	BLV10419	Cab Instructional Seat For Cab Tractors only. Requires SJ20970 to be Ordered Separately.	611.60

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
	LVB25785	ATTACHMENTS FOR FIELD CONVERSIONContinued Canopy - Deluxe Requires LVB25332 Canopy Mounting Bracket and Hardware Kit ordered separately.Open Station Tractors Only.	961.40
	LVB25334	Canopy - Standard Requires LVB25332 Canopy Mounting Bracket and Hardware Kit ordered separately.	583.00
	LVB25332	Canopy Mounting Bracket and Hardware Kit Requires LVB25334 or LVB25785 Canopy Kit ordered separately.	105.60
	AR60937	Cigarette Lighter Cab only.	13.16
	RE334177	John Deere/Delco AM/FM Weatherband Radio Cab Only. Requires Standard Cab Antenna Kit (SJ10170), ordered separately. MY2011 and newer Tractors also require the following: AT209965 Ground Strap, 37M7090 Self-tapping screw M6 X 1 X 16 to attach Ground Strap to roof metal structure, 14M7450 Flange nut M5 x 0.8 to attach ground strap to radio.	412.64
	RE244177	Kit, Rear View Mirror Mounting Kit Requires AL80127 and/or AL80126. Cab Only. Kit contains support plates and hardware for one rear view mirror.	33.07
	AL80126	Mirror, Telescopic, LH, Manually Adjustable Cab Compatible Only.	171.60
	AL80127	Mirror, Telescopic, RH, Manually Adjustable Cab Compatible Only.	171.60
	BLV10350	Right Hand Door Cab Only	291.50
	BLV10173	Wiper/Washer, Rear Cab only.	343.20
	AL113087	Vandal Protection: Vandal Protection, Lockable Fuel Tank Cap	36.75
	R262449	Weights: Front Weight Support, 187 Lbs Requires (4) 19M8100 Cap Screws and (4) 24M7242 Washers, ordered separately.	400.58
	R127764	Weight, Front Suitcase 95 Lb. (43 kg) Quantity of One	134.20
	R213907	Weight, Rear Wheel - 95 Lb. Not compatible on wheels sized 24" or smaller. Maximum of 2 per wheel.	147.40

5065E Utility Tractor (49-53 PTO hp) Equipment for Base Machine

ENGINE:

65 (48 kW) 97/68/EC Engine Horsepower @ 2100 RPM* 53 (39.0 kW) PTO Horsepower @ 2100 RPM* (Open Station) 49 (36.0 kW) PTO Horsepower @ 2100 RPM* (Cab) 3 Cylinder Turbocharged John Deere PowerTech Diesel Engine 179 C.I.D. (2.9L) EPA Final Tier 4 Compliant Dry Type Air Cleaner with Safety Element Underhood Muffler with Vertical Exhaust Stack Anti-Freeze Hand and Foot Throttles Key Engine Shutoff Fan Finger Guard Heavy Duty Air Intake Pre-Heater Fuel Cooler TRANSMISSION: 9F/3R TSS 9F/3R SyncShuttle Synchronized Speed Shifts, Integrated Park Position Right Hand Shifted Speeds Left Hand Shifted Ranges Differential Lock Neutral Start Safety Switch REAR AXLE:

Flanged Rear Axle Planetary Final Drives

STEERING AND BRAKES: Hydrostatic Power Steering Hydraulically Actuated Wet Disk Brakes Self-Equalizing and Self-Adjusting

HYDRAULICS: Open Center Hydraulic System Tandem Gear Pump 18.2 GPM (68.8 LPM) Maximum Total Flow Steering Pump 6.8 GPM (25.7 LPM) Implement Pump 11.4 GPM (43.1 LPM) One Rear Selective Control Valve

POWER TAKE-OFF SHAFT: 9x3 TSS Transmission Independent "Live" 540 RPM Rear PTO Shaft Operator Presence Safety Warning - PTO Safety Start Switch Flip Up PTO Shield

ROCKSHAFT, HITCH AND DRAWBAR: Rear Rockshaft with Position Control, Draft Control, and Adjustable Rate of Drop 3-Point (Category II) Hitch

INSTRUMENTATION: Electric Fuel Gauge Tachometer/Hour Meter Oil Pressure Indicator Light Coolant Temperature Gauge Alternator Indicator Light Air Restriction Indicator Light Turn Signal Indicator Light High Beam Light PTO Engagement Light Digital Display - Hour Meter ELECTRICAL: Open Station 12-Volt Electrical System One Battery - 623 CCA** with 145 Minute Reserve Capacity 40 Amp Alternator LIGHTS: Two Front Halogen Headlights Two Turn/Flashing Warning Lights Two Tail Lights One Rear Work Light (Open Station) MISCELLANEOUS: SMV Emblem Tilt-Up Hood Fender Mounted Toolbox BASE MACHINE: Open Station 2-Post Foldable Roll-Over Protective Structure (ROPS) Deluxe Adjustable Vinyl Seat with Retractable Seat Belt 18 U.S. Gallon (68 L) Fuel Tank Capacity Adjustable Front Axle (56-80 In.) 8-Position Steel Rear Wheels with Two Rear Tires 16.9-28 6PR (R1) 2-Position Steel Front Wheels with Two Front Tires 7.50-16 6PR (F2) * Manufacturer's Rating

with Sway Chains -Convertible to Category I

Adjustable Drawbar

Interchangeable Hitch Balls

** Cold Cranking Amps

ATTACHMENT

IDENTIFIER

SUGGESTED LIST PRICE USD (\$)

Select One Code From Each Required Category

BASE MACHINE

DESCRIPTION

1744LV 5065E

5065E Utility Tractor (49-53 PTO hp)

24,708.00

OPERATORS MANUAL

0409

CODE

English Operators Manual and Decal Kit

In Base Price

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
0413		OPERATORS MANUALContinued French Operators Manual and Decal Kit	Same Price
0437		Spanish Operators Manual and Decal Kit	Same Price
		TRANSMISSION	
1363		9F/3R SyncShuttle Transmission (TSS) 9F/3R Full Top Shaft Synchronized [TSS] Synchronized Speed Shifts Integrated Park Position Code 1363 with Code 2050 - Standard Cab is NOT available on 5065E (Base Code 1744LV) and 5075E (Base Code 1754LV)	In Base Price
1381		12F/12R PowrReverser Transmission - 540/540E (PR) Electrohydraulic (EH) Directional Reverser Wet Traction Clutch Wet PTO Clutch Neutral Start Safety Switch Electrohydraulic (EH) PTO engagement Economy-PTO/Standard PTO MFWD indicator light	2,160.00
		Digital hour meter indicator Digital ground speed indicator Digital PTO speed indicator Requires Code 6040 - MFWD.	
		OPERATOR STATION	
2000		Open Operator Station Fixed Open Operator Station 2 Post Foldable Roll-Over Protection Structure (ROPS) Beverage Holder Single Rear Work Light 18 Gallon Fuel Tank	In Base Price
2050		Cab Left Side Door Air Conditioning Cup Holders	7,488.00
		Radio/CD Ready (Antenna Cable,Two Speakers, and Wiring Harness) Front Windshield Wiper Mechanical Suspension Seat 21.6 Gallon Fuel Tank Requires Code 6040 MFWD. Requires Code 4120 Telescopic Draft Link.	
		MID SELECTIVE CONTROL VALVES	
3400		Less Mid Valves Recommended for applications WITHOUT front loaders. Can later be upgraded for front loader and/or other hydraulic applications using field-installed attachments. Requires Code 6020 - 2WD. In order to install dual mid valves in the field, order kit BSJ10083.	In Base Price
3420		Dual Mid Valves with Joystick Control Recommended for applications WITH front loaders. Requires Code 6040 - MFWD.	1,162.00

5065E Utility Tractor (49-53 PTO hp) Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
		DRAFT LINKS	
4115		Fixed Draft Links	In Base Price
4120		Telescopic Draft Links	518.00
		REAR WHEELS WITH TIRES (TWO)	
5103		22.5LL-16.1 In. 6PR R3 (Turf Special) Bias Requires Code 6103.	777.00
5113		21.5L-16.1 ln. 6PR R3 Bias Code 6020 requires Code 6103. Code 6040 requires Code 6171.	-621.00
5184		16.9-24 In. 6PR R4 Bias Code 6040 requires Code 6133.	-362.00
5185		16.9-28 In. 6PR R1 Bias Code 6020 requires Code 6102. Code 6040 requires Code 6101.	In Base Price
		FRONT AXLE	
6020		2 Wheel Drive Requires Code 1363.	In Base Price
6040		MFWD (4 Wheel Drive) Mechanical Engagement. Engagement Indicator Light on PowrReverser Transmission. Requires Code 3420.	5,296.00
		FRONT WHEELS WITH TIRES (TWO)	
6102		FOR OPTION CODE 6020 (2WD): 7.50-16 In. 6PR F2 Bias Requires Code 2000 - Open Operator Station.	In Base Price
6103		27/12LL-15 In. 6PR Turf Special Bias Requires Code 2000 - Open Operator Station.	486.00
6101		FOR OPTION CODE 6040 (MFWD): 9.5-24 In. 6PR R1 Bias	1,052.00
6133		12.5/80-18 In. 6PR I3(R4 Type) Bias	728.00
6171		9.5-16 In. 6PR R3 Bias	396.00

ATTACHMENTS FOR FIELD CONVERSION

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
		ATTACHMENTS FOR FIELD CONVERSIONContinued	
	L154683	Axle - Rear: Rear Axle 1.2 In. Extension (30 mm) <i>Two required.</i> <i>Requires (16) 19M9364 Cap Screws (8 per Extension), ordered separately.</i>	168.82
	L154682	Rear Axle 1.6 In. Extension (40 mm) Two required. Requires (16) 19M8979 Cap Screws (8 per Extension), ordered separately.	197.95
	L154684	Rear Axle 4.4 In. Extension (111 mm) Two required. Requires (16) 19M9365 Cap Screws (8 per Extension), ordered separately.	279.43
	LV150155	Engine: Engine Coolant Heater Kit (3 Cyl.)	96.80
	LVB25714	Fenders: Rear Fender Extension Kit Cab Tractors only.	209.00
	BSJ10044	Rear Fender Extension Kit without Work Lights Open Station Tractors only.	335.50
	T12553	Hitch and Drawbar: Center Link Conversion Bushing, Cat. II to Cat. I One required.	13.45
	R66432	Draft Link Conversion Bushing, Cat. II to Cat. I <i>Two required</i> .	16.04
	R133359	Drawbar - Offset	310.00
	RE39830	Drawbar Clevis Kit (Hammer Strap) - Offset Drawbar	246.55
	RE39829	Drawbar Clevis Kit (Hammer Strap) - Straight Drawbar	282.28
	TY16042	Quik-Coupler, Economy, Category 2	580.37
	SJ11072	Hitch: Left Hand Telescopic Draft Link	367.78
	SJ11073	Right Hand Telescopic Draft Link	367.78
	LVB25976	iMatch Quick Hitch Category 1 with adjustable top hook Includes one set of Bushings(LVU15507). Not compatible on a 5115M.	357.50
	BSJ10083	Hydraulic Controls: Mid-Mount Dual SCV with Joystick Control Compatible with Open Station 2WD Tractors.	1,411.30

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
		ATTACHMENTS FOR FIELD CONVERSIONContinued	
	BLV10347	Hydraulics: Mid-Mount Dual SCV with Joystick Control <i>Compatible with 5E Cab Tractors.</i>	1,411.30
	LVB25771	Second Rear SCV with Detented Float and Lever Control <i>For 9x3 TSS Open Station Tractors.</i>	805.20
	BLV10348	Second Rear SCV with Detented Float and Lever Control Compatible with 5E Cab Tractors.	805.20
	BLV10431	Second Rear SCV with Detented Float and Lever Control For 12x12 PR Open Station Tractors.	805.20
	LVB25547	Lighting: Auxiliary Rear Work Light Kit (1 Light) Open Station Only.	63.80
	BLV10120	Beacon Light Kit	236.50
	LVB25728	Miscellaneous: Backup Alarm Kit Compatible with 5E 3-Cyl Cab tractors and PR Open Station Tractors.	161.70
	LVB25817	Backup Alarm Kit NOT compatible with 2WD front axle and 5D Series Tractors. Compatible with 5E 3-Cyl TSS open station tractors only.	161.70
	BSJ10063	Creeper Gear Kit For 9F/3R TSS transmission only.	855.80
	BLV10407	Operator's Manual and Decal Kit - French	0.00
	BLV10406	Operator's Manual and Decal Kit - Spanish	0.00
	LVB25727	PowrReverser Modulation Control Kit For 12x12 PR Tractors Only.	147.40
	LVB25926	Single Horn Kit OOS tractors only	51.70
	LVB26096	Single Horn Kit CAB tractors only.	51.70
	SJ10170	Operator Environment: Antenna <i>Cab only</i>	28.49
	AH104259	Ash Tray Cab only.	50.62
	BLV10419	Cab Instructional Seat For Cab Tractors only. Requires SJ20970 to be Ordered Separately.	611.60

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
	LVB25785	ATTACHMENTS FOR FIELD CONVERSIONContinued Canopy - Deluxe Requires LVB25332 Canopy Mounting Bracket and Hardware Kit ordered separately.Open Station Tractors Only.	961.40
	LVB25334	Canopy - Standard Requires LVB25332 Canopy Mounting Bracket and Hardware Kit ordered separately.	583.00
	LVB25332	Canopy Mounting Bracket and Hardware Kit Requires LVB25334 or LVB25785 Canopy Kit ordered separately.	105.60
	AR60937	Cigarette Lighter Cab only.	13.16
	RE334177	John Deere/Delco AM/FM Weatherband Radio Cab Only. Requires Standard Cab Antenna Kit (SJ10170), ordered separately. MY2011 and newer Tractors also require the following: AT209965 Ground Strap, 37M7090 Self-tapping screw M6 X 1 X 16 to attach Ground Strap to roof metal structure, 14M7450 Flange nut M5 x 0.8 to attach ground strap to radio.	412.64
	RE244177	Kit, Rear View Mirror Mounting Kit Requires AL80127 and/or AL80126. Cab Only. Kit contains support plates and hardware for one rear view mirror.	33.07
	AL80126	Mirror, Telescopic, LH, Manually Adjustable Cab Compatible Only.	171.60
	AL80127	Mirror, Telescopic, RH, Manually Adjustable Cab Compatible Only.	171.60
	BLV10350	Right Hand Door Cab Only	291.50
	BLV10173	Wiper/Washer, Rear Cab only.	343.20
	AL113087	Vandal Protection: Vandal Protection, Lockable Fuel Tank Cap	36.75
	R262449	Weights: Front Weight Support, 187 Lbs Requires (4) 19M8100 Cap Screws and (4) 24M7242 Washers, ordered separately.	400.58
	R127764	Weight, Front Suitcase 95 Lb. (43 kg) Quantity of One	134.20
	R213907	Weight, Rear Wheel - 95 Lb. Not compatible on wheels sized 24" or smaller. Maximum of 2 per wheel.	147.40