

SMART TRACTOR | 60 HP

Model 5060 E



5 in 1

- LCD Panel**
- Hour Meter
 - Ground Speed KMPH
 - Service Reminder
 - Trip Meter
 - Battery Volt Meter

Reverse PTO Indicator

Clutch Over Riding Indicator

Mobile Charging Point



MFD
Multi Function Display

...The new generation of Smart tractors is here!




Tilt Steering

For operator comfort adjustable up to 25° tilt, with lock latch



Deluxe Seat

Attractive, adjustable, comfortable seat with armrest



EQRL

Easy hitching and usage of implement through EQRL switches



Smart Brakes

Self adjusting, self equalising hydraulically actuated, oil immersed disc brakes



Go Home Feature

Reach home safely in the dark



JOHN DEERE

SMART TRACTOR 60 HP

Model 5060 E



ENGINE

- Type** : 60 HP, 2400 RPM, 3 cylinder
: Direct injection, Turbo charged, Rotary F.I.P., liquid cooled with overflow reservoir
- Air filter** : Dry type, dual element

TRANSMISSION

- Clutch** : Dual
- Gear Box** : 9 Forward + 3 Reverse
- Speeds** : Forward 2.3 to 32.8 kmph
Reverse 3.9 To 25.4 kmph

BRAKES

Self Adjusting, Self equalising,
Hydraulically Actuated oil immersed disk brakes

HYDRAULICS

- Lifting capacity** : 1800 kgf at lower link ends
- 3 Point linkage** : Category II
- Automatic depth & draft control

STEERING

- Type** : Power
- Steering Column** : Tiltable up to 25° with lock latch

POWER TAKE OFF

- Type** : Independent , 6 splines
- RPM** : 540 @ 2376 ERPM

FUEL TANK CAPACITY

: 68 lit

WHEELS AND TYRES

- Front** : 6.5 X 20 , 8 PR
- Rear** : 16.9 X 30, 12 PR

ELECTRICAL SYSTEM

- 88Ah, 12 volt battery
40 Amp. alternator
2.5 KW starter motor

DIMENSIONS AND WEIGHT OF TRACTOR

- Total weight** : 2130 kg
- Wheel base** : 2050 mm
- Overall length** : 3540 mm
- Overall width** : 1885 mm
- Ground clearance** : 470 mm
- Turning radius with brakes** : 3181 mm

ACCESSORIES

- Ballast Weight
- Canopy
- Canopy Holder
- Wagon Hitch
- Drawbar

OPTIONS

- Adjustable front axle
- Heavy duty front axle
- Reverse PTO- (Std + Reverse)
- Dual PTO- (Std + Economy)
- EQRL System
- Synchronmesh Transmission- (TSS)

Note: Some of the options may not be available in all combinations.
For variants please check with your nearest dealer:

ADDITIONAL FEATURES

- Single Piece Hood with Gas Strut Mechanism
- Side Bar, Exhaust Muffler Guard & Finger Guard
- Viscous Fan
- Water Bottle Holder
- Mobile Holder



For more information, please contact our authorized dealer or nearest area office.

Factory,
off Pune-Nagar road,
Sanaswadi,
Pune – 412 208. Maharashtra



JOHN DEERE

Please note: Improvement in the product is a continuous process.
Hence the information given in this brochure is subject to change without prior notice.

Accessories shown are not the part of standard equipment.

www.johndeere.co.in