

	POWER	FEEDING	CYLINDER/CONCAVE THRESHING		SEPARATING	QuadraFloPlus CLEANING	CAPACITY		WEIGHT	
9560	Engine/Drive 220 hp (164 kW), 240 hp (179 kW) optional; 414 cu. in. (6.8L); hydrostatic variable, 3-spd. transmission	Type all-crop variable with Air-Flow System or fixed; 55-in. (1,397 mm) wide; 78-in. (1,981 mm) long; undershot slat conveyor; electrohydraulic-controlled reverser; dump-type stone trap	Drive Speed fixed (520 rpm) or variable (520-780 rpm) or heavy-duty variable (520-780 rpm)	Rasp-Bar Cylinder Size/Speed 26 in. (660 mm) diameter, 55 in. (1,397 mm) wide; single-range (grain) 470- 960 rpm, dual-range (corn) 240-980 rpm	Generation II Concave 1,255 sq. ft. (0.81 m ²) area; 13-bar	Walker Area 9,703 sq. in. (6.26 m ²)	Area/Speed 6,371 sq. in. (4.11 m ²); 750 to 1,600 rpm	Fuel 150 U.S. gal. (565 L)	Grain Tank/ Unload Rate 204 bu. (7,200 L), 2.2 bu./sec. (77 L/sec)	Base (less head) 26,078 lb. (11,829 kg)
9660	275 hp (205 kW) 496 cu. in. (8.1L); hydrostatic variable, 3-spd. transmission	all-crop variable with Air-Flow System or fixed; 65-in. (1,664 mm) wide; 78-in. (1,981 mm) long; undershot slat conveyor; electrohydraulic-controlled reverser; dump-type stone trap	fixed (520 rpm) or variable (520-780 rpm) or heavy-duty variable (520-780 rpm)	26 in. (660 mm) diameter, 65.5 in. (1,664 mm) wide; single-range (grain) 470- 960 rpm, dual-range (corn) 240-980 rpm	1,504 sq. ft. (0.97 m ²) area; 13-bar	11,625 sq. in. (7.5 m ²)	7,719 sq. in. (4.98 m ²); 750 to 1,600 rpm	150 U.S. gal. (565 L)	220 bu. (8,500 L), 2.2 bu./sec. (77 L/sec)	28,323 lb. (12,847 kg)