



AUGERS

PA15 | PA30



WORKSITE PRO™

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

PA15 / PA30

- Heavy-duty unit drives the auger through a planetary gear reduction. All moving components run in oil for constant lubrication. Spring-loaded double-lip seals guard against contamination.
- Reverse rotation allows quick back-out when obstructions are encountered. Also helps shed dirt from the auger when working in wet conditions.
- Choose from a variety of auger bit styles and diameters including standard 4–6 inch (102–914 mm), 9–12-inch rock and frost (220–305 mm), and 18–36-inch (457–914 mm) tree and shrub.
- Like all Worksite Pro™ attachments, these augers are optimized to work with John Deere Skid Steers, Compact Track Loaders, Compact Excavators, Compact 4WD Loaders, and 110 Tractor Loader Backhoe. In addition, they're compatible with most competitive models. See your local John Deere skid steer dealer for details.

	PA15	PA30
Maximum Auger Bit Diameter	24 in. (610 mm)	36 in. (914 mm)
Overall Auger Bit Length	48 in. (1219 mm)	48 in. (1219 mm)
Minimum Hydraulic Flow	6 gpm (23 L/min.)	14 gpm (53 L/min.)
Maximum Hydraulic Flow	15 gpm (57 L/min.)	30 gpm (114 L/min.)
Maximum Continuous Operating psi	3,100 psi (20 684 kPa)	3,100 psi (20 684 kPa)
Output Shaft Options	2-in. (51 mm) Hex	2-in. (51 mm) Hex
Output Torque	1,433 lb.-ft. (1942 Nm)	2,791 lb.-ft. (3784 Nm)
Output Speed:		
6 gpm (23 L/min.)	38 rpm	N/A
8 gpm (30 L/min.)	51 rpm	N/A
10 gpm (38 L/min.)	64 rpm	N/A
12 gpm (45 L/min.)	77 rpm	N/A
15 gpm (57 L/min.)	96 rpm	49 rpm
18 gpm (68 L/min.)		59 rpm
20 gpm (76 L/min.)		66 rpm
28 gpm (106 L/min.)		92 rpm
Vehicle Compatibility	313, 315, 17D, and 27D	317, 320, 325, 328, 332, CT322, CT332, 35D, 50D, 60D, 110 TLB, and 244J

www.JohnDeere.com



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

