

100 C
50 C
100 M
50 M
100 Y
50 Y
100 K
50 K
25 3C
50 3C
75 3C



JOHN DEERE



BACKHOES

BH7 | BH8 | BH9 | BH11



WORKSITE PRO

COMMERCIAL WORKSITE PRODUCTS

BACKHOES

SPECIFICATIONS BH7 / BH8 / BH9 / BH11

- Powerful Worksite Pro™ backhoes offer a combination of productivity, ease of operation, and unmatched durability.
- One-hundred-eighty-degree swing allows maximum efficiency in confined areas.
- For extreme digging conditions, heavy-duty buckets are available with tapered sides for greater dump-and-fill performance. Large teeth and tooth shanks add durability.
- Optional quick-couplers are also utilized on Deere 17-, 27-, and 35-Series Compact Excavators.
- Low-profile console offers excellent visibility.
- Operator station is easy to enter and exit, thanks to a convenient grab rail and open design. Seat with fore-and-aft adjustment and large footrests with non-slip surfaces also ensure comfortable operation for extended periods.
- Metered hydraulic spools and centralized two-lever control of boom lift, swing, dipperstick, and bucket allow precise control of backhoe movement.
- All Worksite Pro backhoes are equipped with a connect-under-pressure male coupler.
- Single lever locks the boom in place for secure transport. Can be engaged or disengaged from the seat.
- Worksite Pro backhoes are optimized to work with John Deere skid steers and compact track loaders. They're backed by a one-year warranty and one-of-a-kind parts and service. See your local John Deere skid steer dealer for details.

	BH7	BH8	BH9	BH11
Transport Height	81 in. (2057 mm)	90 in. (2286 mm)	94 in. (2388 mm)	115 in. (2921 mm)
Overall Transport Length:				
313	166 in. (4216 mm)	N/A	N/A	N/A
315, 317, 320, and CT322	172 in. (4369 mm)	179 in. (4547 mm)	184 in. (4674 mm)	189 in. (4801 mm)
325, 328, 332, and CT332	N/A	193 in. (4902 mm)	198 in. (5029 mm)	203 in. (5156 mm)
Digging Depth:				
Maximum	94 in. (2388 mm)	107 in. (2718 mm)	117 in. (2972 mm)	134 in. (3404 mm)
2-ft. (0.6 m) Flat Bottom	92 in. (2337 mm)	105 in. (2667 mm)	115 in. (2921 mm)	132 in. (3353 mm)
8-ft. (2.3 m) Flat Bottom	66 in. (1676 mm)	84 in. (2134 mm)	98 in. (2489 mm)	115 in. (2921 mm)
Straight Wall	47 in. (1194 mm)	60 in. (1524 mm)	68 in. (1727 mm)	92 in. (2337 mm)
Reach From Swing Pivot	124 in. (3150 mm)	142 in. (3607 mm)	155 in. (3937 mm)	173 in. (4394 mm)
Loading Height	79 in. (2007 mm)	88 in. (2235 mm)	95 in. (2413 mm)	107 in. (2718 mm)
Loading Reach	43 in. (1092 mm)	46 in. (1168 mm)	61 in. (1549 mm)	68 in. (1727 mm)
Stabilizer Spread:				
Transport	61 in. (1549 mm)	54 in. (1372 mm)	64 in. (1626 mm)	64 in. (1626 mm)
Operating	89 in. (2261 mm)	99 in. (2515 mm)	116 in. (2946 mm)	116 in. (2946 mm)
Bucket Rotation	180 deg.	180 deg.	180 deg.	180 deg.
Swing Arc	180 deg.	180 deg.	180 deg.	180 deg.
Attachment Weight:				
With 16-in. (406 mm) Bucket	1,220 lb. (553 kg)	N/A	N/A	N/A
With 18-in. (457 mm) Bucket	N/A	1,610 lb. (732 kg)	1,796 lb. (816 kg)	2,061 lb. (937 kg)
Craning Capacity	595 lb. (270 kg)	820 lb. (372 kg)	905 lb. (410 kg)	985 lb. (447 kg)
Digging Force				
Using Bucket Cylinder	2,840 lb. (1288 kg)	3,730 lb. (1692 kg)	6,000 lb. (2721 kg)	6,200 lb. (2812 kg)
Using Dipperstick Cylinder	2,005 lb. (909 kg)	2,435 lb. (1104 kg)	3,250 lb. (1474 kg)	4,000 lb. (1814 kg)
Backhoe System Relief Setting	2,075 psi (14 306 kPa)	2,425 psi (16 720 kPa)	2,425 psi (16 720 kPa)	2,425 psi (16 720 kPa)

BH7 BUCKETS AND CAPACITIES

Standard Pin-On Buckets:	9 in. (228 mm)	13 in. (330 mm)	16 in. (406 mm)
Heaped Capacity	0.64 cu. ft. (0.018 m³)	1.04 cu. ft. (0.029 m³)	1.33 cu. ft. (0.038 m³)
Weight	46 lb. (21 kg)	52 lb. (24 kg)	57 lb. (26 kg)
Optional Heavy-Duty Quick-Coupler Buckets:	9 in. (228 mm)	12 in. (305 mm)	16 in. (406 mm)
Heaped Capacity	0.606 cu. ft. (0.017 m³)	0.855 cu. ft. (0.024 m³)	1.194 cu. ft. (0.034 m³)
Weight	83 lb. (38 kg)	87 lb. (39 kg)	99 lb. (45 kg)

BH8, BH9, and BH11 BUCKETS AND CAPACITIES

Heavy-Duty Pin-On Buckets:	14 in. (356 mm)	18 in. (457 mm)	24 in. (610 mm)	36 in. (914 mm)
Heaped Capacity	1.74 cu. ft. (0.049 m³)	2.68 cu. ft. (0.076 m³)	3.71 cu. ft. (0.105 m³)	5.76 cu. ft. (0.163 m³)
Weight	106 lb. (48 kg)	126 lb. (57 kg)	146 lb. (66 kg)	195 lb. (88 kg)
Heavy-Duty Quick-Coupler Buckets:	12 in. (305 mm)	18 in. (457 mm)	24 in. (610 mm)	
Heaped Capacity	1.33 cu. ft. (0.038 m³)	2.33 cu. ft. (0.066 m³)	3.29 cu. ft. (0.093 m³)	
Weight	124 lb. (56 kg)	152 lb. (69 kg)	175 lb. (80 kg)	

WORKSITE PRO™



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.



NOTHING RUNS LIKE A DEERE™

DKABHCWP Litho in U.S.A. (08-01)

