

SPECIFICATIONS

ROUND / SQUARE

- Tapered design of the round bale spear provides reduced drag resistance for easier inserting or removing. Multiple-point support gives extra bale stability.
- Low-profile design provides unrestricted visibility to the spear and tine tips.
- Round bale main spear and square bale tines are retained with bolts, making them easier to replace. Helps eliminate weld fractures, too.
- Quick-Tatch™ mounting provides quick and easy hookup and removal.
- Like all Worksite Pro™ attachments, these bale spears are optimized to work with John Deere 300-Series Skid Steers, and are compatible with most competitive models. See your local John Deere dealer for details.

ROUND BALE SPEAR

SQUARE BALE SPEAR

| | | |
|--|-------------------------------|---------------------|
| Weight | 193 lb. (87.82 kg) | 375 lb. (171 kg) |
| Height | 19 in. (485 mm) | 22 in. (561 mm) |
| Width | 44.5 in. (1132 mm) | 65 in. (1652 mm) |
| Length: | | |
| Overall | 48.25 in. (1226 mm) | 44 in. (1118 mm) |
| Main Spear | 40 in. (1015 mm) | N/A |
| Lower Tines | 15 in. (383 mm) | N/A |
| Center Spear | | 35 in. (889 mm) |
| Outside Spears | | 25 in. (635 mm) |
| Capacity* (without weight kit): | | |
| 313 | 680 lb. (308 kg) | 690 lb. (313 kg) |
| 315 | 860 lb. (390 kg) | 910 lb. (413 kg) |
| 317 | 1,005 lb. (456 kg) | 1,105 lb. (501 kg) |
| 320 | 1,070 lb. (485 kg) | 1,185 lb. (537 kg) |
| 325 | 1,585 lb. (719 kg) | 1,800 lb. (816 kg) |
| 328 | 1,765 lb. (800 kg) | 2,015 lb. (914 kg) |
| 332 | 2,070 lb. (939 kg) | 2,390 lb. (1084 kg) |
| CT322 | 1,505 lb. (683 kg) | 1,775 lb. (805 kg) |
| CT332 | 2,150 lb. (975 kg) | 2,565 lb. (1163 kg) |
| Capacity* (with weight kit): | | |
| 313 | 780 lb. (354 kg) | 815 lb. (370 kg) |
| 315 | 970 lb. (440 kg) | 1,045 lb. (474 kg) |
| 317 | 1,185 lb. (537 kg) | 1,330 lb. (603 kg) |
| 320 | 1,255 lb. (569 kg) | 1,415 lb. (642 kg) |
| 325 | 1,795 lb. (814 kg) | 2,050 lb. (930 kg) |
| 328 | 1,970 lb. (893 kg) | 2,270 lb. (1029 kg) |
| 332 | 2,280 lb. (1034 kg) | 2,645 lb. (1200 kg) |
| CT322** | 1,670 lb. (757 kg) | 1,990 lb. (902 kg) |
| CT332** | 2,345 lb. (1063 kg) | 2,810 lb. (1274 kg) |

*50% of maximum stable load at maximum reach and 30-in. (763 mm) load center.
 **35% of maximum stable load at maximum reach.

www.JohnDeere.com



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

