



# MULCHING HEAD

MH60



**WORKSITE PRO™**

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

MH60

- Remove up to 8-inch trees and 12-inch stumps. Shred underbrush and woody materials into beneficial mulch in just minutes.
- Severe-duty design utilizes oversize 2½-inch sealed rotor bearings and double carbide-tipped teeth for long-term durability. Heavy-duty push bar is useful for toppling trees or brush, and helps protect the carrier.
- Hydraulic system maximizes available hydraulic horsepower. For extra protection, an internal valve eliminates return-oil pressure spikes during stalls. Prominently positioned gauge lets an operator easily monitor hydraulic operating pressure. For increased efficiency and reduced stalling.
- Hydraulic brake stops the rotor in less than 10 seconds, eliminating the “freewheeling” common with other designs. Allows an operator to exit quickly, if necessary.
- In-line cooler reduces hydraulic system heat for efficient operation in high-ambient-temperature conditions.
- With a 60-inch opening and 36 teeth, high-capacity rotor takes big bites out of trees and stumps. Rotor torque is balanced to deliver superior large-material knockdown and shredding performance. Also works well below soil level, for chewing out stumps.
- Smooth rotor reduces material drag and horsepower requirements. Internal counter-combs help shatter incoming material, creating a finer mulch.
- Like all Worksite Pro™ attachments, this mulching head is optimized to work with John Deere skid steers and compact track loaders. See your local John Deere skid steer dealer for details.

MH60

<b>Overall Width</b> .....	74 in. (1880 mm)
<b>Maximum Cutting Width</b> .....	60 in. (1524 mm)
<b>Height</b> .....	64 in. (1625 mm)
<b>Length</b> .....	40 in. (1016 mm)
<b>Weight</b> .....	2,497 lb. (1133 kg)
<b>Recommended Flow</b> .....	35–345 gpm (132–170 lpm)
<b>Maximum Hydraulic Pressure</b> .....	4,000 psi
<b>Flow</b> (standard or high) .....	high
<b>Number of Cutting Tools</b> .....	36 double-carbide tipped
<b>Vehicle Compatibility</b> .....	328, 332, and CT332

www.JohnDeere.com



**WORKSITE PRO™**

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

