



ROTARY CUTTERS

RC60L | RC72L
RC72 | RC78



WORKSITE PRO™

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

RC60L / RC72L / RC72 / RC78

- Rigid quarter-inch (6 mm) steel deck, formed side plates, and heavy-duty skid shoes provide solid strength and durability.
- Operates forward or reverse. Double-edge blades, fast blade-tip speed, and tapered side-discharge chute ensure clean cutting and maximum material shredding. Cuts and mulches up to 4-inch-diameter saplings and heavy brush.
- Front chain shield helps prevent flying debris, allows material to easily pass into the cutter with minimal interruption.
- Blade-stall indicator allows the operator to monitor blade speed; standard stump jumper helps protect the gearbox from sudden impacts.
- Optional front wheel helps keep deck level to prevent ground gouging. Tire is non-pneumatic.
- Like all Worksite Pro™ attachments, these rotary cutters are optimized to work with John Deere skid steers and compact track loaders. In addition, they're compatible with most comparable competitive models. See your local John Deere skid steer dealer for details.

	RC60L	RC72L	RC72	RC78
Overall Height	22.5 in. (572 mm)	22.5 in. (572 mm)	22.5 in. (572 mm)	22.5 in. (572 mm)
Overall Length	6 ft. 6 in. (1.99 m)	7 ft. 6 in. (2.30 m)	7 ft. 6 in. (2.30 m)	8 ft. 0 in. (2.44 m)
Overall Width	6 ft. 0 in. (1.83 m)	7 ft. 1 in. (2.16 m)	7 ft. 1 in. (2.16 m)	7 ft. 7 in. (2.31 m)
Weight	1,230 lb. (558.0 kg)	1,610 lb. (730.3 kg)	1,610 lb. (730.3 kg)	1,666 lb. (755.7 kg)
Minimum Cutting Height	2 in. (51 mm)	2 in. (51 mm)	2 in. (51 mm)	2 in. (51 mm)
Cutting Width	5 ft. 0 in. (1.52 m)	6 ft. 0 in. (1.83 m)	6 ft. 0 in. (1.83 m)	6 ft. 6 in. (1.98 m)
Cutting Capacity	4 in. (102 mm)	4 in. (102 mm)	4 in. (102 mm)	4 in. (102 mm)
Recommended Output	15–19 gpm (57–72 L/m)	15–19 gpm (57–72 L/m)	22–24 gpm (83–91 L/m)	22–24 gpm (83–91 L/m)
Flow (standard or high)	standard	standard	standard	standard
Required Skid Steer Lift Capacity	1,300 lb. (589.7 kg)	1,700 lb. (771.1 kg)	1,700 lb. (771.1 kg)	1,800 lb. (816.5 kg)
Vehicle Compatibility	313, 315, 317, 320, and CT322	313, 315, 317, 320, and CT322	325, 328, 332, and CT332	325, 328, 332, and CT332

Front Wheel Kit (if equipped):

- Weight** 20 lb. (9 kg)
- Cutter Compatibility** RC60L, RC72L, RC72, and RC78

www.JohnDeere.com



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

