



JOHN DEERE



BUCKETS

CONSTRUCTION | UTILITY
FOUNDRY | TOOTH




WORKSITE **PRO**[™]

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

- **Worksite Pro™ buckets** have much greater capacity than competitive buckets, so they can carry and do more. They're simply the best way to take advantage of 300-Series Skid Steers' steep dump angle and high bucket rollback. (Not surprisingly, they also enhance the performance of many competitive skid steers.)
- **Construction bucket:** Offers a low back plate for better operator visibility of cutting edge and a rounded interior for improved fill-and-dump performance. Cutting edge and toothbar holes are pre-drilled.
- **Utility bucket:** Perfect for light, high-volume materials. Bolt-on cutting edge holes are pre-drilled.
- **Foundry bucket:** Made especially for loosening compacted soil or grubbing out rocks. Unlike a bucket with a toothbar kit added, this bucket offers a flat bottom, making it an excellent tool for back-dragging.
- **Tooth bucket:** Is shorter from bucket heel to cutting edge to provide maximum breakout force for tough digging conditions. Bolt-on toothbar holes are pre-drilled.



CONSTRUCTION

FOUNDRY

UTILITY

TOOTH

Buckets and Capacities	Width	Depth	Height	Shipping Weight	Struck	Heaped
56-in. Construction	56.0 in. (1422 mm)	34.2 in. (869 mm)	20.8 in. (528 mm)	326 lb. (148 kg)	9.3 cu. ft. (0.26 m ³)	12.3 cu. ft. (0.35 m ³)
60-in. Construction	60.0 in. (1524 mm)	34.2 in. (869 mm)	20.8 in. (528 mm)	343 lb. (156 kg)	9.9 cu. ft. (0.28 m ³)	13.2 cu. ft. (0.37 m ³)
60-in. Tooth	60.0 in. (1524 mm)	40.2 in. (1020 mm)	20.8 in. (528 mm)	393 lb. (179 kg)	9.9 cu. ft. (0.28 m ³)	13.2 cu. ft. (0.37 m ³)
66-in. Construction	66.0 in. (1676 mm)	37.0 in. (940 mm)	20.8 in. (528 mm)	429 lb. (195 kg)	11.9 cu. ft. (0.34 m ³)	16.2 cu. ft. (0.46 m ³)
66-in. Foundry	66.0 in. (1676 mm)	27.1 in. (689 mm)	25.8 in. (655 mm)	394 lb. (179 kg)	11.2 cu. ft. (0.32 m ³)	14.6 cu. ft. (0.41 m ³)
66-in. Utility	66.0 in. (1676 mm)	35.3 in. (896 mm)	27.6 in. (700 mm)	479 lb. (217 kg)	15.9 cu. ft. (0.45 m ³)	20.5 cu. ft. (0.58 m ³)
66-in. Tooth	66.0 in. (1676 mm)	43.0 in. (1092 mm)	20.8 in. (528 mm)	472 lb. (215 kg)	11.9 cu. ft. (0.34 m ³)	16.2 cu. ft. (0.46 m ³)
66-in. Multi-Purpose	66.0 in. (1676 mm)	36.0 in. (914 mm)	28.0 in. (711 mm)	866 lb. (394 kg)	8.6 cu. ft. (0.24 m ³)	12.0 cu. ft. (0.34 m ³)
72-in. Construction	72.0 in. (1829 mm)	37.0 in. (940 mm)	20.8 in. (528 mm)	475 lb. (216 kg)	13.0 cu. ft. (0.37 m ³)	17.8 cu. ft. (0.50 m ³)
72-in. Foundry	72.0 in. (1829 mm)	27.1 in. (689 mm)	25.8 in. (655 mm)	429 lb. (195 kg)	12.3 cu. ft. (0.35 m ³)	16.0 cu. ft. (0.45 m ³)
72-in. Utility	72.0 in. (1829 mm)	35.3 in. (896 mm)	27.6 in. (700 mm)	507 lb. (230 kg)	16.6 cu. ft. (0.47 m ³)	21.6 cu. ft. (0.61 m ³)
72-in. Tooth	72.0 in. (1829 mm)	43.0 in. (1092 mm)	20.8 in. (528 mm)	515 lb. (234 kg)	13.0 cu. ft. (0.37 m ³)	17.8 cu. ft. (0.50 m ³)
72-in. Multi-Purpose	72.0 in. (1829 mm)	36.0 in. (914 mm)	28.0 in. (711 mm)	918 lb. (417 kg)	9.4 cu. ft. (0.27 m ³)	13.1 cu. ft. (0.37 m ³)
76-in. Heavy-Duty Construction	76.0 in. (1930 mm)	37.0 in. (940 mm)	20.8 in. (711 mm)	583 lb. (264 kg)	13.7 cu. ft. (0.39 m ³)	18.5 cu. ft. (0.53 m ³)
76-in. Heavy-Duty Tooth	76.0 in. (1930 mm)	37.0 in. (940 mm)	20.8 in. (711 mm)	641 lb. (291 kg)	13.7 cu. ft. (0.39 m ³)	18.5 cu. ft. (0.53 m ³)
78-in. Heavy-Duty Construction	78.0 in. (1981 mm)	37.0 in. (940 mm)	20.8 in. (528 mm)	521 lb. (237 kg)	13.6 cu. ft. (0.39 m ³)	19.4 cu. ft. (0.55 m ³)
78-in. Heavy-Duty Foundry	78.0 in. (1981 mm)	27.1 in. (689 mm)	25.8 in. (655 mm)	536 lb. (243 kg)	14.4 cu. ft. (0.41 m ³)	17.8 cu. ft. (0.50 m ³)
78-in. Heavy-Duty Utility	78.0 in. (1981 mm)	35.3 in. (896 mm)	27.6 in. (700 mm)	535 lb. (243 kg)	18.8 cu. ft. (0.53 m ³)	24.5 cu. ft. (0.69 m ³)
78-in. Heavy-Duty Tooth	78.0 in. (1981 mm)	43.0 in. (1092 mm)	20.8 in. (528 mm)	583 lb. (265 kg)	13.6 cu. ft. (0.39 m ³)	19.4 cu. ft. (0.55 m ³)
78-in. Multi-Purpose	78.0 in. (1981 mm)	36.0 in. (914 mm)	28.0 in. (711 mm)	998 lb. (454 kg)	10.0 cu. ft. (0.28 m ³)	14.1 cu. ft. (0.40 m ³)
84-in. Heavy-Duty Construction	84.0 in. (2134 mm)	37.0 in. (940 mm)	20.8 in. (528 mm)	549 lb. (250 kg)	15.3 cu. ft. (0.43 m ³)	21.0 cu. ft. (0.60 m ³)
84-in. Heavy-Duty Utility	84.0 in. (2134 mm)	35.3 in. (896 mm)	27.6 in. (700 mm)	563 lb. (255 kg)	19.5 cu. ft. (0.55 m ³)	25.4 cu. ft. (0.72 m ³)
84-in. Heavy-Duty Tooth	84.0 in. (2134 mm)	43.0 in. (1092 mm)	20.8 in. (528 mm)	611 lb. (278 kg)	15.3 cu. ft. (0.43 m ³)	21.0 cu. ft. (0.60 m ³)
84-in. Multi-Purpose	84.0 in. (2134 mm)	36.0 in. (914 mm)	28.0 in. (711 mm)	1,030 lb. (468 kg)	10.5 cu. ft. (0.29 m ³)	15.4 cu. ft. (0.43 m ³)

WORKSITE PRO™



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

