

Get More Out Of Your Land With Frontier Landscape Equipment



**Rear Blades • Box Blades • Soil Pulverizers
Core Aerators • Turf Renovators • Landscape Rakes**

Keep your land looking clean

Landscape Rakes

Your needs for landscape equipment change with every job, but one thing that doesn't change is your need for equipment that's **rugged, reliable, and ready to go when you are.**

With Frontier landscape equipment, you can choose from a variety of high-quality attachments that suit the specific needs of your job:

landscape rakes, rear blades, box blades, pulverizers, core aerators, and turf renovators. Whether you're grading a hillside, cleaning up a construction site, preparing a yard for seeding, or restoring a sports field, Frontier landscape equipment gives you exceptional strength, performance, and dependability.

With all these attachments to choose from, **make Frontier Equipment your source for all your landscape equipment needs.**

To help you choose the right Frontier tool for the job, talk to your John Deere dealer, your exclusive distributor of Frontier Equipment.

www.BuyFrontier.com

LR1060L • LR1072 • LR1172 • LR1184 • LR1196



Nothing handles tough clean-up and grooming jobs better than Frontier landscape rakes. Whether you're removing debris, rocks, and brush, or simply smoothing an area for planting seed or sod, count on Frontier landscape rakes to simplify the job.

Medium-duty models feature high-strength, formed box-type tine beams, constructed with a slotted bolt-in mounting system. This mounting not only ensures positive spacing and alignment over each tine, but it also makes replacement fast and easy, saving you time and money.

The spring steel tines are spaced at 1-inch intervals for exceptional performance in pick-up, grooming, and material distribution.

Core Aerators

CA1048 • CA1060 • CA1072



Frontier core aerators have heavy-duty, reinforced frames that are designed to reduce hard, layered soil compaction and increase turf vitality. Each spoon wheel holds eight case-hardened spoons. All aerators come with a 1-1/4-inch diameter shaft and independently acting gangs of spoon wheels which ensure performance in tough soil conditions.

Plus, Frontier core aerators come with a rack that holds up to 1,000 pounds of additional weight, allowing greater control over the depth of spoon penetration in a variety of soil types.

and professional

Rear Blades

RB1060L



RB1060



RB1072



RB1084



RB1172



RB1184



RB1196

Frontier rear blades are designed for maximum versatility and performance in your light utility chores. Whether you're shaping ground around your estate, or installing professional landscaping, you can choose from two duty classes – standard or medium – and seven models to suit your needs.

Both classes are manually adjustable, providing greater control of blade angle, tilt, and offset positions. (*RB1060 does not have offset capability.*)

Frontier offers three standard-duty rear blades that are specifically designed to offer versatility and performance in the compact tractor horsepower range, 12 to 40 PTO horsepower.

Three medium-duty models are designed with the landscape professional in mind. They fit tractors up to 75 PTO horsepower.



Turf Renovators

The Frontier manually driven turf renovator is a great addition to any rental or commercial operation, designed for seeding fresh soil as well as renovating existing lawns and pastures. Available in three sizes, each model is equipped with two 8-inch diameter front rollers and one 8-inch diameter rear roller.

These turf renovators are easily adjusted and simple to operate, featuring rollers with 2-inch tapered steel pins that provide positive soil aeration without excessive turf damage. The front rollers control the level of aeration and regulate crabbing. The rear roller provides the ground drive for the precision-metered seed box. For added convenience, the unit comes standard with a self-cleaning seed box.

TR1048 • TR1060 • TR1072



Soil Pulverizers

**SP1048 • SP1060
SP1272 • SP1284**

Frontier soil pulverizers boast a rugged design that has made them the standard. Available in two duty classes, Frontier pulverizers are designed to tackle a variety of professional landscape applications.

All models are designed with two 150-pound compression springs, providing ample down-pressure to force the pins into soil up to an inch deep. The 6-5/8-inch diameter rollers include 1-inch bearings and up to 126 heat-treated pins for superior quality and performance.

Frontier pulverizers also feature a quick-hitch compatible, heavy-plate-style mast and clevis hitch. All models are available with an optional second roller,* which is easily installed in the field.

**Shown with optional dual roller kit.*



variety of landscaping chores

Box Blades

**BB1354 • BB1360 • BB1365
BB1372 • BB1472 • BB1484**

Looking for an affordable solution for grading and leveling chores? Check out the rugged BB13 and BB14 Series Box Blades. A reinforced heavy steel A-frame provides durability for tough jobs. Plus, reversible cutting edges and replaceable scarifiers keep you productive for long hours of work.

The standard-duty BB13 Series offers a 54- to 72-inch working width. Team one up with your utility tractor of up to 45 horsepower for light grading around your home or to level your driveway. Best of all, the BB13 Series feature 3/8-inch end plates – thicker than many comparable models in the industry.

And for more challenging jobs, try the medium-duty BB14 Series. Available in 72- or 84-inch working widths, these tools are designed to handle backfilling, gardening, and other ground maintenance tasks. They hook-up easily to your 40 to 65 horsepower tractors. 1/4-inch wear plate is welded to the bottom of each 1/2-inch end plate for longer life.



Heavy-Duty Box Blades

Frontier heavy-duty box blades deliver impressive versatility for backfilling, leveling, and precision grading applications. They're construction grade, and the perfect complement to 40- to 80-horsepower tractors with a Category I or Category II three-point hitch.

Each sturdy box blade features a balanced A-frame design that's manufactured from heavy-duty plate steel, then solid welded and reinforced with structural supports to provide durability even in the most severe-use environments.

If that's not enough, the BB1284 helps to simplify your tough landscaping jobs further. Equipped with eight hydraulically controlled scarifiers, the BB1284 easily breaks through compacted ground. A high rising scarifier bar keeps teeth clear of debris and provides a clear view of the cutting edge.



Specifications

Specifications • Rear Blades

Model	RB1060L	RB1060	RB1072
Duty	Standard-duty	Standard-duty	Standard-duty
Moldboard length	60 in. (152 cm)	60 in. (152 cm)	72 in. (183 cm)
Moldboard height	10 in. (25 cm)	14 in. (36 cm)	14 in. (36 cm)
Moldboard thickness	.1875 in. (5 mm)	.1875 in. (5 mm)	.25 in. (6 mm)
Approximate weight	182 lb. (83 kg)	262 lb. (119 kg)	283 lb. (128 kg)
Tractor hp	12 - 25 hp (8.9-18.6 kW)	12 - 30 hp (8.9-22.3 kW)	12 - 40 hp (8.9-29.8 kW)
Angle	360°	360°	360°
Angle – forward	0, 15, & 30° ea. side	0, 15, & 30° ea. side	0, 15, & 30° ea. side
Angle – reverse	0, 15, & 30° ea. side	0 & 15° ea. side	0 & 15° ea. side
Tilt	–	3-position	3-position
Offset	12 in. (31 cm), left or right	NA	12 in. (31 cm), left or right
Cutting edge	.5 x 6 in. (13 mm x 15 cm), reversible	.5 x 6 in. (13 mm x 15 cm), reversible	.5 x 6 in. (13 mm x 15 cm), reversible
3-point hitch	Category 0 / Limited Category 1	Category 1	Category 1
iMatch™ Compatible	Yes	Yes	Yes

Specifications • Box Blades

Model	BB1354	BB1360	BB1365
Duty	Standard-duty	Standard-duty	Standard-duty
Working width	54 in. (137 cm)	60 in. (152 cm)	65 in. (165 cm)
End plate thickness	.375 in. (10 mm)	.375 in. (10 mm)	.375 in. (10 mm)
Approximate weight	486 lb. (220 kg)	514 lb. (233 kg)	528 lb. (239 kg)
Tractor hp (maximum)	Up to 45 hp (36.6 kW)	Up to 45 hp (36.6 kW)	Up to 45 hp (36.6 kW)
Shanks	(4) replaceable	(5) replaceable	(5) replaceable
Tailgate	Fixed	Fixed	Fixed
Cutting edges	(2) .5 x 6 in. (13 mm x 15 cm), reversible	(2) .5 x 6 in. (13 mm x 15 cm), reversible	(2) .5 x 6 in. (13 mm x 15 cm), reversible
3-point hitch	Category 1	Category 1	Category 1
iMatch™ Compatible	Yes	Yes	Yes

Specifications • Soil Pulverizers

Model	SP1048	SP1060	SP1272	SP1284
Duty	Standard-duty	Standard-duty	Heavy-duty	Heavy-duty
Working width	48 in. (122 cm)	60 in. (152 cm)	72 in. (183 cm)	84 in. (213 cm)
Height	36.5 in. (93 cm)	36.5 in. (93 cm)	36.5 in. (93 cm)	36.5 in. (93 cm)
Spike – scarifying teeth – front	(9), 0.625 x 8 in. (16 x 203 mm)	(11), 0.625 x 8 in. (16 x 203 mm)	(14), .375 x 8 in. (10 mm)	(16), .375 x 8 in. (10 mm)
Spike – scarifying teeth – rear	(8), 0.625 x 8 in. (16 x 203 mm)	(10), 0.625 x 8 in. (16 x 203 mm)	(13), .375 x 8 in. (10 mm)	(15), .375 x 8 in. (10 mm)
Bar – scarifying teeth – front	NA	NA	(14), .5 x 2 x 13 in. (13 x 50.8 x 330 mm)	(16), .5 x 2 x 13 in. (13 x 50.8 x 330 mm)
Bar – scarifying teeth – rear	NA	NA	(13), .5 x 2 x 13 in. (13 x 50.8 x 330 mm)	(15), .5 x 2 x 13 in. (13 x 50.8 x 330 mm)
Roller pins	72	90	108	126
H beam dimensions	10 x 10 in. (25 x 25 cm)	10 x 10 in. (25 x 25 cm)	10 x 12 in. (25 x 30 cm)	10 x 12 in. (25 x 30 cm)
Springs	(2) 150 lb. (68 kW)	(2) 150 lb. (68 kW)	(2) 150 lb. (68 kW)	(2) 150 lb. (68 kW)
Tractor hp (max.)	15 - 45 hp (11.2-33.6 kW)	20 - 45 hp (14.9-33.6 kW)	30 - 65 hp (22.3-48.5 kW)	30 - 65 hp (22.3-48.5 kW)
3-point hitch	Category 1	Category 1	Category 1	Category 1
iMatch™ Compatible	Yes	Yes	Yes	Yes

- Rugged. Reliable. Ready.

RB1084	RB1172	RB1184	RB1196
Standard-duty	Medium-duty	Medium-duty	Medium-duty
84 in. (213 cm)	72 in. (183 cm)	84 in. (213 cm)	96 in. (244 cm)
14 in. (36 cm)	18 in. (46 cm)	18 in. (46 cm)	18 in. (46 cm)
.25 in. (6 mm)	.3125 in. (8 mm)	.3125 in. (8 mm)	.3125 in. (8 mm)
304 lb. (138 kg)	530 lb. (240 kg)	565 lb. (256 kg)	600 lb. (272 kg)
12- 40 hp (8.9-29.8 kW)	75 hp (55.9 kW) maximum	75 hp (55.9 kW) maximum	75 hp (55.9 kW) maximum
360°	360°	360°	360°
0, 15, & 30°ea. side	0, 15, 30, & 45°ea. side	0, 15, 30, & 45°ea. side	0, 15, 30, & 45°ea. side
0 & 15°ea. side	0, 15, 30, & 45°ea. side	0, 15, 30, & 45°ea. side	0, 15, 30, & 45°ea. side
3-position	4-position	4-position	4-position
12 in. (31 cm), left or right	Up to 45°	Up to 45°	Up to 45°
.5 x 6 in. (13 mm x 15 cm), reversible	.5 x 6 in. (13 mm x 15 cm), reversible	.5 x 6 in. (13 mm x 15 cm), reversible	.5 x 6 in. (13 mm x 15 cm), reversible
Category 1	Category 1 & 2	Category 1 & 2	Category 1 & 2
Yes	Yes	Yes	Yes

BB1372	BB1472	BB1484	BB1284
Standard-duty	Medium-duty	Medium-duty	Heavy-duty
72 in. (183 cm)	72 in. (183 cm)	84 in. (213 cm)	84 in. (213 cm)
.375 in. (10 mm)	.5 in. (13 mm)	.5 in. (13 mm)	.5 in. (13 mm)
551 lb. (250 kg)	680 lb. (308 kg)	750 lb. (340 kg)	1,259 lb. (571 kg)
Up to 45 hp (36.6 kW)	Up to 65 hp (48.5 kW)	Up to 65 hp (48.5 kW)	40-80 hp (29.8-59.7 kW)
(6) replaceable	(6) replaceable	(7) replaceable	(8) replaceable/hydraulic
Fixed	Optional floating	Optional floating	Hinged adjustable
.5 x 6 in. (13 mm x 15 cm), reversible	(2) .5 x 6 in. (13 mm x 15 cm), reversible	(2) .5 x 6 in. (13 mm x 15 cm), reversible	(2) .5 x 6 in. (13 mm x 15 cm), reversible
Category 1	Category 1	Category 1	Category 1 & 2
Yes	Yes	Yes	No

iMatch Quick-Attach Hitch System

Frontier landscape attachments can be configured to utilize the iMatch™. This innovative and affordable device converts a 3-point hitch to fixed hooks and attaching points, which allows for easy connection to iMatch-compatible landscape rakes, core aerators, rear blades, box blades, soil pulverizers, and turf renovators. iMatch is a welcome alternative to the sometimes challenging and awkward task of lining up 3-point hitch implements.



Specifications

Specifications • Core Aerators

Model	CA1048	CA1060	CA1072
Working width	48 in. (122 cm)	60 in. (152 cm)	72 in. (183 cm)
Overall width	56 in. (142 cm)	67.5 in. (171 cm)	78.5 in. (199 cm)
Approximate weight	437 lb. (198 kg)	539 lb. (245 kg)	561 lb. (255 kg)
Tractor hp	20 - 65 hp (14.9 - 48.5 kW)	30 - 65 hp (22.3 - 48.5 kW)	30 - 65 hp (22.3 - 48.5 kW)
Weight tray	(2) 22 x 14.5 in. (56 x 37 cm)	(2) 22 x 20 in. (56 x 51 cm)	(2) 22 x 25.5 in. (56 x 65 cm)
Spoons	(64) .75 in. (2 cm), case-hardened steel	(96) .75 in. (2 cm), case-hardened steel	(96) .75 in. (2 cm), case-hardened steel
Spoon penetration	4.5 in. (11 cm)	4.5 in. (11 cm)	4.5 in. (11 cm)
3-point hitch	Category 1	Category 1	Category 1
iMatch™ Compatible	Yes	Yes	Yes

Specifications • Turf Renovators

Model	TR1048	TR1060	TR1072
Working width	48 in. (122 cm)	60 in. (152 cm)	72 in. (183 cm)
Overall width	58 in. (147 cm)	70 in. (178 cm)	82 in. (208 cm)
Height	44 in. (112 cm)	44 in. (112 cm)	44 in. (112 cm)
Approximate weight	820 lb. (372 kg)	920 lb. (417 kg)	1052 lb. (477 kg)
Tractor hp	65 hp (48.5 kW) maximum	65 hp (48.5 kW) maximum	65 hp (48.5 kW) maximum
Wind guard	Standard	Standard	Standard
Roller diameter (front)	(2) 8 in. (20 cm), angled	(2) 8 in. (20 cm), angled	(2) 8 in. (20 cm), angled
Roller diameter (rear)	(1) 8 in. (20 cm), straight	(1) 8 in. (20 cm), straight	(1) 8 in. (20 cm), straight
Seedbox capacity	3 bushel	4 bushel	5 bushel
3-point hitch	Category 1	Category 1	Category 1
iMatch™ Compatible	Yes	Yes	Yes

Specifications • Landscape Rakes

Model	LR1060L	LR1072	LR1172	LR1184	LR1196
Duty	Standard-duty	Standard-duty	Medium-duty	Medium-duty	Medium-duty
Rake width	60 in. (152 cm)	72 in. (183 cm)	72 in. (183 cm)	84 in. (213 cm)	96 in. (244 cm)
Approximate weight	177 lb. (80 kg)	270 lb. (123 kg)	305 lb. (138 kg)	332 lb. (151 kg)	359 lb. (163 kg)
Tractor hp	12 - 25 hp (8.9 - 18.6 kW)	12 - 40 hp (8.9 - 29.8 kW)	12 - 40 hp (8.9 - 29.8 kW)	20 - 40 hp (14.9 - 29.8 kW)	20 - 40 hp (14.9 - 29.8 kW)
Rake Positions	5 forward, 5 reverse	5 forward, 3 reverse	5 forward, 3 reverse	5 forward, 3 reverse	5 forward, 3 reverse
Tines	.3125 x 1 in. (8 x 25 mm), spring steel	.3125 x 1 in. (8 x 25 mm), spring steel	.3125 x 1 in. (8 x 25 mm), spring steel	.3125 x 1 in. (8 x 25 mm), spring steel	.3125 x 1 in. (8 x 25 mm), spring steel
3-point hitch	Category 0 / Limited Category 1	Category 1	Category 1	Category 1	Category 1
iMatch™ Compatible	Yes	Yes	Yes	Yes	Yes



This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL JOHN DEERE DEALER FOR DETAILS. Frontier Equipment reserves the right to change specifications, design and price of products described in this literature without notice. John Deere, the leaping deer symbol, and John Deere's green and yellow trade dress are the trademarks of Deere & Company. Copyright 2010, Frontier Equipment.

www.BuyFrontier.com