

New Frontier Rear Blades



5-foot to 10-foot working widths

From light utility work to heavy grading,

the wide line of Frontier Rear Blades are designed for maximum versatility and performance. Whether you're shaping ground or installing professional landscaping, you can choose from four duty classes — medium, medium plus, heavy, and heavy plus — and 14 different models to meet your needs.

These blades are built tough to work tough. It starts with a tubular steel frame to handle your biggest jobs. The dozer-type, full-radius moldboard is professional grade to handle heavy loads. And cutting edges are reversible to give your blade twice the work life.

Sure they're tough, but they're also adaptable to your conditions. A 360-degree swing angle lets you adapt the blade to your job. Go with optional hydraulic offset, angle, and tilt to make adjustments in minimal time.

You get all this at an affordable price. Just check out the entire line of Frontier Rear Blades to find the one that's right for you.

www.BuyFrontier.com

DETAILS - REAR BLADES



Optional end plates hold in extra material while dragging it from one place to another. Perfect for filling.



Optional skid shoes protect the moldboard cutting edge from hitting low-lying obstructions while cleaning corrals or removing snow.



The turn-table on the 21 and 22 Series allows you to adjust the angle to three different positions in both forward and reverse.



Optional hydraulics on the 23 and 24 Series allow you to control offset, angle, and tilt from the tractor seat.

SPECIFICATIONS

Model Number	RB2160	RB2172	RB2184	RB2196
Angle, tilt, & offset adjustments	Manual	Manual	Manual	Manual
Hitch compatibility	Category 1 (iMatch compatible)	Category 1 (iMatch compatible)	Category 1 (iMatch compatible)	Category 2 (Quick-Coupler compatible)
Grading & leveling	Fine, precision grading & leveling	Fine, precision grading & leveling	Fine, precision grading & leveling	Fine, precision grading & leveling
Moldboard	0.25-in. full-radius moldboard	0.25-in. full-radius moldboard	0.25-in. full-radius moldboard	0.25-in. full-radius moldboard
Frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame
Cutting edge	0.5x6 in., reversible	0.5x6 in., reversible	0.5x6 in., reversible	0.5x6 in., reversible
Angle/pivot	360 degrees	360 degrees	360 degrees	360 degrees
Forward angle positions	3, up to 53 degrees each side	3, up to 53 degrees each side	3, up to 53 degrees each side	3, up to 53 degrees each side
Reverse angle positions	3, up to 53 degrees each side	3, up to 53 degrees each side	3, up to 53 degrees each side	3, up to 53 degrees each side
Tilt positions	3, up to 22 degrees up or down	3, up to 22 degrees up or down	3, up to 22 degrees up or down	3, up to 22 degrees up or down
Moldboard thickness	0.25 in.	0.25 in.	0.25 in.	0.25 in.
Moldboard length	60 in.	72 in.	84 in.	96 in.
Moldboard height	17 in.	17 in.	17 in.	17 in.
Offset	6 or 12 in., left or right	6 or 12 in., left or right	6 or 12 in., left or right	6 or 12 in., left or right
Duty	Medium	Medium	Medium	Medium
Tractor horsepower	2WD: 65 hp max.; 4WD: 60 hp max.	2WD: 65 hp max.; 4WD: 60 hp max.	2WD: 65 hp max.; 4WD: 60 hp max.	2WD: 65 hp max.; 4WD: 60 hp max.
Parking stand	Standard	Standard	Standard	Standard
Skid shoe bundle	Optional	Optional	Optional	Optional
Operating weight	392 lb.	422 lb.	448 lb.	476 lb.
Warranty	1 year	1 year	1 year	1 year

built tough to work tough

DUTY CLASSES



21 Series Medium-Duty Rear Blades – for tractors up to 65 horsepower – are great for light road maintenance, lawn care, gardening, and other light-duty landscaping. Also great for year-round ground leveling, roadside clearing, and snow removal. Available with manual adjustments only. (Shown with optional skid shoes and end plates.)



22 Series Medium-Duty-Plus Rear Blades – for tractors up to 80 horsepower – are ideal for leveling, gardening, road maintenance, and feedlots. The blade design allows you to cut and roll the soil rather than drag it, saving you time, horsepower, and fuel. Manual adjustments are standard; hydraulic offset adjustment is optional.



23 Series Heavy-Duty Rear Blades – for tractors up to 120 horsepower – have rugged construction great for ditching and terracing. Manual adjustments are standard. Or, to complete your work quickly and easily, go with the optional hydraulic adjustments for tilt, offset, and angle. (Shown with optional full hydraulic controls, skid shoes and end plates.)



24 Series Heavy-Duty-Plus Rear Blades – for tractors up to 160 horsepower – are built extra tough for a wide range of material handling...from landscaping to heavy-duty dam-building. The enhanced curved moldboard gives you maximum penetration and added precision to cut and roll the soil rather than drag it. Hydraulic angle is standard; fully hydraulic is optional. (Shown with optional full hydraulic controls and end plates.)

SPECIFICATIONS

New Frontier Rear Blades – Medium and Heavy Duty

Model Number	RB2272	RB2284	RB2296
Angle, tilt, & offset adjustments	Manual; optional hydraulic offset (up to 1 hydraulic remote required)	Manual; optional hydraulic offset (up to 1 hydraulic remote required)	Manual; optional hydraulic offset (up to 1 hydraulic remote required)
Hitch compatibility	Category 2 (Quick-Coupler compatible)	Category 2 (Quick-Coupler compatible)	Category 2 (Quick-Coupler compatible)
Grading & leveling	Landscaping & moderate grading	Landscaping & moderate grading	Landscaping & moderate grading
Moldboard	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction
Frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame
Cutting edge	0.5x6 in., reversible	0.5x6 in., reversible	0.5x6 in., reversible
Angle/pivot	360 degrees	360 degrees	360 degrees
Forward angle positions	3, up to 45 degrees each side	3, up to 45 degrees each side	3, up to 45 degrees each side
Reverse angle positions	3, up to 45 degrees each side	3, up to 45 degrees each side	3, up to 45 degrees each side
Tilt positions	3, up to 23 degrees up or down	3, up to 23 degrees up or down	3, up to 23 degrees up or down
Moldboard thickness	0.25 in.	0.25 in.	0.25 in.
Moldboard length	72 in.	84 in.	96 in.
Moldboard height	19 in.	19 in.	19 in.
Offset	9 or 18 in., left or right	9 or 18 in., left or right	9 or 18 in., left or right
Duty	Medium plus	Medium plus	Medium plus
Tractor horsepower	2WD: 80 hp max.; 4WD: 70 hp max.	2WD: 80 hp max.; 4WD: 70 hp max.	2WD: 80 hp max.; 4WD: 70 hp max.
Parking stand	Standard	Standard	Standard
Skid shoe bundle	Optional	Optional	Optional
Operating weight	738 lb.	755 lb.	772 lb.
Warranty	1 year	1 year	1 year

Model Number	RB2307	RB2308	RB2309	RB2310
Angle, tilt, & offset adjustments	Manual; optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)	Manual; optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)	Manual; optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)	Manual; optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)
Hitch compatibility	Category 2 (Quick-Coupler compatible)	Category 2 (Quick-Coupler compatible)	Category 2 (Quick-Coupler compatible)	Category 2 (Quick-Coupler compatible)
Grading & leveling	Heavy grading and snow removal	Heavy grading and snow removal	Heavy grading and snow removal	Heavy grading and snow removal
Moldboard	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction
Frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame
Cutting edge	0.5x6 in., reversible	0.5x6 in., reversible	0.5x6 in., reversible	0.5x6 in., reversible
Angle/pivot	360 degrees	360 degrees	360 degrees	360 degrees
Forward angle positions	3, up to 45 degrees each side (0-45 degrees each side*)	3, up to 45 degrees each side (0-45 degrees each side*)	3, up to 45 degrees each side (0-45 degrees each side*)	3, up to 45 degrees each side (0-45 degrees each side*)
Reverse angle positions	3, up to 45 degrees each side (0-45 degrees each side*)	3, up to 45 degrees each side (0-45 degrees each side*)	3, up to 45 degrees each side (0-45 degrees each side*)	3, up to 45 degrees each side (0-45 degrees each side*)
Tilt positions	3, up to 23 degrees up or down (0-15 degrees up or down*)	3, up to 23 degrees up or down (0-15 degrees up or down*)	3, up to 23 degrees up or down (0-15 degrees up or down*)	3, up to 23 degrees up or down (0-15 degrees up or down*)
Moldboard thickness	5/16 in.	5/16 in.	5/16 in.	5/16 in.
Moldboard length	84 in.	96 in.	108 in.	120 in.
Moldboard height	19 in.	19 in.	19 in.	19 in.
Offset	9 or 18 in., left or right (0-19 in., left or right*)	9 or 18 in., left or right (0-19 in., left or right*)	9 or 18 in., left or right (0-19 in., left or right*)	9 or 18 in., left or right (0-19 in., left or right*)
Duty	Heavy	Heavy	Heavy	Heavy
Tractor horsepower	2WD: 120 hp max.; 4WD: 110 hp max.	2WD: 120 hp max.; 4WD: 110 hp max.	2WD: 120 hp max.; 4WD: 110 hp max.	2WD: 120 hp max.; 4WD: 110 hp max.
Parking stand	Standard	Standard	Standard	Standard
Skid shoe bundle	Optional	Optional	Optional	Optional
Operating weight	1,060 lb. (1,162 lb.*)	1,139 lb. (1,241 lb.*)	1,240 lb. (1,342 lb.*)	1,300 lb. (1,402 lb.*)
Warranty	1 year	1 year	1 year	1 year

*—Fully hydraulic model

Model Number	RB2408	RB2409	RB2410
Angle, tilt, & offset	Manual tilt & offset, hydraulic angle (1 hydraulic remote required); optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)	Manual tilt & offset, hydraulic angle (1 hydraulic remote required); optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)	Manual tilt & offset, hydraulic angle (1 hydraulic remote required); optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)
Hitch compatibility	Category 2/3 (Quick-Coupler compatible)	Category 2/3 (Quick-Coupler compatible)	Category 2/3 (Quick-Coupler compatible)
Grading & leveling	Heavy grading and snow removal	Heavy grading and snow removal	Heavy grading and snow removal
Moldboard	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction
Frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame
Cutting edge	0.5x6 in., reversible	0.5x6 in., reversible	0.5x6 in., reversible
Angle/pivot	360 degrees	360 degrees	360 degrees
Forward angle positions	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side*)	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side*)	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side*)
Reverse angle positions	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side*)	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side*)	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side*)
Tilt positions	2, up to 15 degrees up or down (0-12 degrees, up or down*)	2, up to 15 degrees up or down (0-12 degrees, up or down*)	2, up to 15 degrees up or down (0-12 degrees, up or down*)
Moldboard thickness	5/16 in.	5/16 in.	5/16 in.
Moldboard length	96 in.	108 in.	120 in.
Moldboard height	19 in.	19 in.	19 in.
Offset	Right: 0-28 in.; left: 0-26 in. (0-19 in. left or right*)	Right: 0-28 in.; left: 0-26 in. (0-19 in. left or right*)	Right: 0-28 in.; left: 0-26 in. (0-19 in. left or right*)
Duty	Heavy plus	Heavy plus	Heavy plus
Tractor horsepower	2WD: 160 hp max.; 4WD: 145 hp max.	2WD: 160 hp max.; 4WD: 145 hp max.	2WD: 160 hp max.; 4WD: 145 hp max.
Parking stand	Standard	Standard	Standard
Skid shoe bundle	Optional	Optional	Optional
Operating weight	1,451 lb. (1,499 lb.*)	1,501 lb. (1,549 lb.*)	1,550 lb. (1,598 lb.*)
Warranty	1 year	1 year	1 year

*—Fully hydraulic model

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. Frontier Equipment reserves the right to change specifications, design, and price of products described in this literature without notice. Copyright 2005, Frontier Equipment.

DSFE35901 Litho in U.S.A. (05-06)

FRONTIER
EQUIPMENT™
Rugged. Reliable. Ready.

www.BuyFrontier.com