

New Frontier 20-"L" Series

Landscape Tools for Limited Category 1 Hitches



Box Blade • Rear Blade • Landscape Rake



Are you ready to take on more chores and see what you and your tractor can do? Then take a look at the rugged and reliable 20-“L” Series landscape tools from Frontier. Use the landscape rake for removing rocks, brush, and debris, or use it to prepare soil for seed or sod. For precision grading and filling low spots, go with the box blade. It delivers impressive versatility for scraping, leveling, and backfilling. Hitch up the easy-to-use rear blade and tackle a variety of scraping and leveling chores.

These 20-“L” Series tools are designed specifically for tractors with Limited Category 1 hitches, such as the John Deere 2210 and 2305. Best of all, these tools are iMatch™ compatible, making hookup a breeze. Just back up your tractor to the implement’s attaching points, lock the safety handles, and you’re good to go. Their rugged design and sturdy construction ensures years of dependable use. Plus, they’re backed with a one-year warranty and the best dealer network in the industry — John Deere.

The possibilities of what you can do with these tools are endless. Visit your local John Deere dealer to learn more about the 20-“L” Series landscape tools from Frontier. See how John Deere has the products, support, and know-how you need for everything you do on your land.

www.BuyFrontier.com

DETAILS - BOX BLADE



Increase or decrease the amount of ground penetration by adjusting the steel scarifiers. Choose from three scarifier depth settings, or store them in the scarifier beam when using the box blade for other tasks. Scarifiers are heat-treated for durability and longer life.



Cutting edges are positioned 3/4-inch below the end plates to ensure precise leveling and a fine finish. They’re also reversible for extended life.

Versatile Frontier landscape tools

DETAILS - REAR BLADE



Adjust the angle of the blade to five different positions in forward and three positions in reverse. Simply remove the pin and rotate the blade to the desired position. Use your tractor's 3-point hitch to tilt the blade for precision scraping.



The tough cutting edge takes on any challenge and is reversible for longer life.

DETAILS - LANDSCAPE RAKE



High-strength steel tines are spaced at 1-inch intervals for exceptional performance in pick-up, grooming, and material distribution. The underside waffle-plate ensures positive spacing and alignment, plus makes tine replacement fast and easy.



Five different raking positions let you move soil or gravel through the rake for the precise surface profile you demand. Simply remove the pin and rotate the rake beam to the desired setting.

New Frontier 20-"1" Series: Rugged. Reliable. Ready.

SPECIFICATIONS

Model Number

BB2048L

Working width	48 in. (1.22 m)
Tractor compatibility	Tractor weight: 2,250 lb. max.; horsepower: 25 hp max.
Hitch compatibility	Limited Category 1 (iMatch compatible) (Category 0 lift pins available through Frontier Parts)
Shanks	3 positions, with holes
Scarifier points	Replaceable, hardened steel
Tailgate	Fixed
Endplate	3/16 in. (4.8 mm) thick
Moldboard	7 gauge
Cutting edge	2; 1/2x6 in. (12.7x152 mm) reversible
Mast	Bolt-up with 1/4 in. (6.35 mm) plates
Weight	275 lb. (125 kg)
Warranty	1 year



Model Number

RB2060L

Working width	60 in. (1.52 m)
Tractor compatibility	Tractor weight: 2,250 lb. max.; horsepower: 25 hp max.
Hitch compatibility	Limited Category 1 (iMatch compatible) (Category 0 lift pins available through Frontier Parts)
Moldboard	7 gauge, 60 in. (1.52 m) wide
Cutting edge	1/2x6 in. (12.7x152 mm) reversible
Frame	Tubular steel
Angle pivot	360 degrees
Angle positions, forward	0, 15, 30 degrees each side
Angle positions, reverse	0, 15 degrees each side
Parking stand	Standard
Weight	155 lb. (70 kg)
Warranty	1 year



Model Number

LR2060L

Working width	60 in. (1.52 m)
Tractor compatibility	Tractor weight: 2,250 lb. max.; horsepower: 25 hp max.
Hitch compatibility	Limited Category 1 (iMatch compatible) (Category 0 lift pins available through Frontier Parts)
Tines	5/16x1x12 in. (7.9x25.4x304.8 mm) spring steel
Tine beam	Angle
Frame	Tubular steel
Angle pivot	360 degrees
Raking positions, forward	0, 15, 30 degrees each side
Raking positions, reverse	0, 15 degrees each side
Parking stand	Standard
Weight	168 lb. (76 kg)
Warranty	1 year



All models are John Deere iMatch™ compatible. The iMatch quick-hitch system converts the tractor's 3-point hitch to fixed hooks and attaching points for a super-quick connection. (iMatch hitch sold separately.)



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. Frontier Equipment reserves the right to change specifications, design, and price of products described in this literature without notice. Copyright 2005, Frontier Equipment.