



JOHN DEERE



\* Optional equipment shown.

## 6330 Optional Government Bid Configuration

### ENGINE:

85 PTO Horsepower @ 2300 RPM  
105 Engine Horsepower @ 2300 RPM  
4 Cylinder—John Deere Diesel Engine  
4.53 liters  
Air Cleaner w/ PreCleaner  
Underhood Muffler w/ Vertical Exhaust

### TRANSMISSION:

16F/16R PowerQuad PLUS  
Park Lock  
Hydraulic "Wet" Clutch

### STEERING AND BRAKES:

Hydrostatic Steering  
Dual Stage Disk Brakes

### HYDRAULICS:

Load Sensing Constant Flow Pressure Compensated System  
17.5 GPM Pump Capacity @ 2300 RPM  
Two SCVs with ISO Couplers

### POWER TAKE-OFF SHAFT:

Independent 540 RPM Rear with Shields  
Hydraulic Clutch  
Neutral Start  
Seat Activated PTO Warning

### ELECTRICAL:

12-Volt Electrical System  
Battery (830 CCA, 110 Ah)  
7 Terminal ASAE Outlet Socket  
90 Amp Alternator

### ROCKSHAFT AND DRAWBAR:

Cat. 2 Hitch  
LH Telescopic Draft Link  
Electronic Hitch and Control  
Swinging Drawbar  
Left Hand Stabilizer Bar

### LIGHTS:

Two Front Grille  
Two Rear Work Lights  
Flashing Warning Lights  
Combination Tail and Implement

### REAR AXLE WHEELS AND TIRES:

Rack and Pinion Axle  
18.4R30 In. Radial Rear Tires

### FRONT AXLE WHEELS AND TIRES:

2WD – 10.00-16 In 10PR Tires

### COMFORTGARD CAB:

Two Doors  
Two Front Roof Working Lights  
Air Conditioning  
Tilt Steering Wheel  
Console Mounted Shift Levers  
Super Comfort Seat w/ Air Suspension  
Radio Prep Package  
Hand and Foot Throttle  
Power Outlet Socket  
Viscous Drive Fan  
Front Windshield Wiper  
A-Post mounted Cup holder

### MISCELLANEOUS:

Hydraulic Differential Lock  
SMV Emblem  
Full Length Structural Frame  
43.6 Gallon Fuel Tank Capacity  
Tiltable Engine Enclosure  
Horn  
Vandal Protection  
Toolbox  
Fuel Tank Guard  
Front and Rear Window Wash

### WEIGHT:

10,151 lbs

\* Specifications are good through 1 July 2008. Prices and specifications are subject to change without notice.