



JOHN DEERE

GATOR™

UTILITY VEHICLES

HPX SERIES

HPX 4X4



The Gator™ HPX 4x4.

Pick a direction. Go.

- On-demand true 4WD for the ultimate traction
- The most stable vehicle in its class with the lowest center of gravity
- Built for long life with industry-exclusive hydroformed steel frames
- Offer best-in-class load height and high hauling capacity
- Occupant Protection System is SAE/ANSI/OSHA ROPS certified
- Over 100 attachments and accessories — including a deluxe high-quality glass cab

See dealer or www.JohnDeere.com/Vehicles for more.

	Gator HPX 4x4 Gas	Gator HPX 4x4 Diesel
Engine and Electrical		
Type	2-cylinder, 4-cycle OHV gas	3-cylinder, 4-cycle OHV diesel
Displacement/HP	617 cc/20 HP**	854 cc / 20.8 HP **
Maximum Torque	32 ft.-lb. (44.4 kg-m @ 2,500 rpm)	33 ft.-lb. (4.5 kg-m @ 3,350 rpm)
Ignition Type	Solid state 12V	Compression Ignition
Lubrication	Full pressure	Full pressure
Cooling System	Liquid	Liquid
Air Cleaner	Dry replaceable single-element w/remote intake	Dry replaceable single-element w/remote intake
Battery	340 CCA	480 CCA
Alternator	21 amp @ 3,200 rpm – regulated, 252 watts	40 amp @ 3,200 rpm – regulated, 540 watt
Headlights	Two 37.5 watt halogen	Two 37.5 watt halogen
Fuel Capacity	5.3 U.S. Gal. (20.0 L)	5.3 U.S. Gal. (20.0 L)
Transmission		
Type	Continuously variable transmission (CVT)	Continuously variable transmission (CVT)
4WD		
System Type	On-Demand "True" 4WD	On-Demand "True" 4WD
Front Differential (Engagement)	Auto locking (on/off rocker switch)	Auto locking (on/off rocker switch)
Rear Differential (Engagement)	Positive locking, mechanically actuated (hand operated)	Positive locking, mechanically actuated (hand operated)
Ground Speed		
High Range	0–25 mph (0–40 km/h)	0–25 mph (0–40 km/h)
Low Range	0–12 mph (0–19 km/h)	0–12 mph (0–19 km/h)
Transaxle	Two-speed, oil bath	Two-speed, oil bath
Gear Selection	Forward (high-low), neutral, reverse	Forward (high-low), neutral, reverse
Brakes	Front/rear hydraulic disk	Front/rear hydraulic disk
Park Brake	Rear mechanical disk, hand operated	Rear mechanical disk, hand operated
Suspension and Steering		
Suspension, Front	Independent with MacPherson strut	Independent with MacPherson strut
Suspension, Rear	Coil over shock	Coil over shock
Ground Clearance:		
Under Transaxle	6 in. (152 mm)	6 in. (152 mm)
Under Foot Platform	12 in. (305 mm)	12 in. (305 mm)
Steering	Rack and pinion	Rack and pinion
Occupant Protection System	SAEJ2194/OSHA ROPS standard certified steel tubular structure with 3-pt. belts and multiple handholds	SAEJ2194/OSHA ROPS standard certified steel tubular structure with 3-pt. belts and multiple handholds
Dimensions		
Length (With Bumper)	113.0 in. (2870 mm)	113.0 in. (2870 mm)
Width	59.3 in. (1506 mm)	59.3 in. (1506 mm)
Front-Tread Centers	49.5 in. (1257.3 mm)	49.5 in. (1257.3 mm)
Rear-Tread Centers	48 in. (1219.3 mm)	48 in. (1219.3 mm)
Height (Overall With OPS)	73.5 in. (1867 mm)	73.5 in. (1867 mm)
Wheelbase	75.2 in. (1910 mm)	75.2 in. (1910 mm)
Weight (Including Fuel/Fluids)	1,296 lb. (589 kg)	1,473 lb. (668 kg)
Turning Radius	12 ft. (3.7 m)	12 ft. (3.7 m)
Seating Capacity, Type	2, Professional high-back	2, Professional high-back
Towing/Payload Capacity*	1,300 lb. (590 kg)/ 1,400 lb. (635 kg)	1,300 lb. (590 kg)/ 1,400 lb. (635 kg)
Cargo Box		
Load Height	Heavy-duty steel	Heavy-duty steel
Dimensions	31 in.	31 in.
Volume	43.9Lx49Wx9D (1116Lx1244Wx229D)	43.9Lx49Wx9D (1116Lx1244Wx229D)
Max Box Weight	11.2 cu. ft.	11.2 cu. ft.
Front Tires	1,000 lb. (554 kg)	1,000 lb. (554 kg)
Rear Tires	24x9.50-10	24x9.50-10
All Trail II	24x10.5-10	24x10.5-10
Turf & AT 489	24x12-10	24x12-10
Available Tread Types	Standard (All Trail II), Aggressive (AT489), Turf/Hard Surface	Standard (All Trail II), Aggressive (AT489), Turf/Hard Surface
Available Colors	John Deere Yellow & Green	John Deere Yellow & Green

*Includes 200-lb. (91 kg) operator and 200-lb. (91 kg) passenger and maximum box capacity. **The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification, design and price of the products described in this literature without notice. John Deere's green and yellow color scheme, the leaping deer symbol, and JOHN DEERE are trademarks of Deere & Company.

