

High temperature (**Extreme-Temp™ batteries**)



PART NUMBER				
U.S.	TY24794		TY24784	
CAN.	CXTY24794		CXTY24784	
BCI	31 (Pillar post)		31 (Pillar post)	
<hr/>				
VOLTS	12		12	
<hr/>				
CCA	750		925	
<hr/>				
CA	900		1110	
<hr/>				
RC	150		180	
<hr/>				
SIZE	(in.)	(mm)	(in.)	(mm)
Length:	13	330	13	330
Width:	6 <sup>13</sup> / <sub>16</sub>	173	6 <sup>13</sup> / <sub>16</sub>	173
Height:	9 <sup>7</sup> / <sub>16</sub>	240	9 <sup>7</sup> / <sub>16</sub>	240
<hr/>				
ELECTROLYTE CAPACITY	(qt.)	(L)	(qt.)	(L)
	5.8	5.5	5.6	5.3
<hr/>				
PLATES/CELL	17		21	
<hr/>				
TERMINAL TYPE	A		A	
<hr/>				
VENT CAP	PT20040		PT20040	
<hr/>				
FEATURES	Envelope separators Polypropylene case Epoxy-anchored plates Super radial grids		Envelope separators Polypropylene case Epoxy-anchored plates Super radial grids	
<hr/>				
WARRANTY CODE*	B		B	

\*B = 90 days free exchange/48 months pro rata (auto/truck under one ton)/36 months pro rata (all other applications)