

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

## 4005 and 4105 Compact Utility Tractors

### FILTER PAK

(4105) – [LVA21202](#)

Kit contains M806419, MIU800645, RE68048, LVA13065 offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

### TRANSMISSION / HYDRAULIC

#### OIL FILTER

(4105) – [LVA13065](#)  
(4005) – [RE27284](#)

Replace after initial 50 hours, then every 200 hours.

(Click here for [capacity](#))




#### ENGINE OIL FILTER

– [M806419](#)

Replace every 200 hours or annually, whichever occurs first.

(Click here for [capacity](#))



#### ENGINE PRIMARY AIR FILTER

(4105) – [RE68048](#)  
(4005) – [M131802](#)

#### SECONDARY AIR FILTER

(4105) – [RE68049](#)  
(4005) – [M131803](#)

Replace as required.



#### ENGINE FUEL FILTER

– [MIU800645](#) and [M811032](#)

Replace every 500 hours.



**JOHN DEERE**

Genuine Parts and Service

# CAPACITIES

## 4005 and 4105 Compact Utility Tractors

### CAPACITIES (Approximate):

#### **Fuel Tank:**

4005.....	32 L (8.5 gal)
4105.....	43.5 L (11.5 gal)

#### **Cooling System: Cool-Gard™ II**

4005.....	5.8 L (1.53 gal)
4105.....	5.3 L (1.4 gal)

#### **Crankcase with Filter: Plus-50™ II**

4005.....	5.3 L (1.4 gal)
4105.....	4.3 L (1.13 gal)

#### **Transmission and Hydraulic System:**

##### **Low Viscosity Hy-Gard™**

4005.....	26 L (6.9 gal)
4105.....	31.4 L (8.3 gal)

#### **Front Axle:**

##### **GL-5 Lubricant 80W-90**

4005.....	7.5 L (1.98 gal)
-----------	------------------

##### **Low Viscosity Hy-Gard™**

4105.....	4.5 L (1.19 gal)
-----------	------------------

[Return to Filter Overview](#)

