

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

5 Series Tractors - 5225, 5325, 5425, 525 and 5625



CAB
FRESH AIR FILTER
[RE198488](#)

Clean after every 300 hours and replace as per filter condition.




CAB
RECIRCULATION AIR FILTER -
[RE195491](#)

Clean after every 300 hours and replace as per filter condition.



ENGINE
FUEL FILTER
[RE508202](#) (5225, 5325)
[RE522868](#) (5425, 5525, 5625)
Replace after 300 hours.



ENGINE
PRIMARY AIR FILTER
[KV16429](#)
SECONDARY AIR FILTER
[AT171854](#)
Replace after every 1800 hours or annually.



ENGINE
OIL FILTER
[RE519626](#) (5225, 5325)
[RE504836](#) (5425, 5525, 5625)

Replace initially after 300 hours for models 5225 and 5325.
Replace initially after 100 hours for models 5425, 5525 and 5625.
Service interval can be extended to 450 hours if John Deere PLUS-50 oil and John Deere filter are used.



HYDRAULIC
OIL FILTER - [RE197065](#)
Replace initially after 100 hours and after every 600 hours.



http://www.deere.com/en_US/parts/service/support/filter/overviews

CAPACITIES

5 Series Tractors - 5225, 5325, 5425, 525 and 5625

CAPACITIES (Approximate):

Fuel Tank:

Straddle Mount and Hi-Crop 94.6 L (25 gal)
 Cab and IOOS 126.8 L (33.5 gal)

Cooling System:

Cool-Gard™ II

(5225, 5325) 9.5 L (2.5 gal)
 (5425, 5525, 5625) 11.4 L (3 gal)

Crankcase W/ Filter:

(5225, 5325) 10 L (2.64 gal)
 (5425, 5525, 5625) 8.5 L (2.24 gal)

**Transmission and Hydraulic System:
 Hy-Gard™**

9/3 SyncShuttle™ 39 L (10.3 gal)
 12/12 PowrReverser™ 43.4 L (11.5 gal)
 24/24 PowrReverser™ 45.4 L (12 gal)

MECHANICAL FRONT-WHEEL DRIVE (MFWD) AXLE:

Differential Housing 4.5 L (1.18 gal)
 Wheel Hub (Each) 0.7 L (0.185 gal)

[Return to Filter Overview](#)

