

# REPLACEMENT PARTS GUIDE

5M Series - 5075M(ME000001-), 5090M(ME000001-), 5100M(ME000001-), 5115M(ME000001-) Tractors

## CAB



**RECIRCULATION AIR FILTER**  
[RE195491](#) (QUANTITY 2)

Clean after every 600 hours or annually and as required per conditions.



**FRESH AIR FILTER**  
[RE198488](#)

Clean after every 600 hours or annually and as required per conditions.



**PRIMARY AIR FILTER**  
[SU20768](#)  
**SECONDARY AIR FILTER**  
[RE253519](#)

Service after every 1200 hours or annually as required per conditions.

## HYDRAULIC



**OIL FILTER**  
[SJ11784](#)

Replace after first 100 hours and 600 hours then replace after at 1200 hrs intervals.

(Click here for [capacity](#))

## ENGINE



**DIESEL PARTICULATE FILTER (DEF)**  
[DZ104592](#) (5075M)

(Click here for [capacity](#))

## OIL FILTER

[RE519626](#) (5075M)  
[DZ114256](#) (5075M)  
[RE504836](#) (5090M, 5100M, 5115M)

For 2.9 Liter 3 Cylinder Engine  
Replace the filter after first 100 hours and then every 500 hours.

For 4.5 Liter 4 Cylinder Engine  
Replace the filter after every 500 hours.

(Click here for [capacity](#))



**OPEN CRANKCASE VENTILATION (OCV) FILTER**

[DZ105100](#) (5090M, 5100M, 5115M)

Clean after every 600 hours. Replace annually.



**FUEL FILTER**  
[DZ114096](#) (5075M)

**PRIMARY FUEL FILTER**  
[RE546336](#) (5090M, 5100M, 5115M)

**FINAL FUEL FILTER**  
[DZ115390](#) (5090M, 5100M, 5115M)

Replace after every 500 hours of usage.



# CAPACITIES

5M Series - 5075M(ME000001-), 5090M(ME000001-), 5100M(ME000001-), 5115M(ME000001-) Tractors

## CAPACITIES (Approximate):

### Fuel Tank:

5075M	
(Cab).....	165L (43.6 gal)
(Cab, High Capacity) .....	196L (51.8 gal)
5090M/5100M	
(Cab).....	140 L (37 gal)
(Cab, High Capacity), 5115M (Cab) .....	170 L (44.9 gal)
5075M	
(OOS) .....	148 L (39.1 gal)
(OOS, High Capacity).....	177 L (46.8 gal)
5090M/5100M	
(OOS) .....	112 L (29.6 gal)
(OOS, High Capacity), 5115M (OOS).....	141 L (37.2 gal)

### Cooling System:

#### Cool-Gard™ II

5075M (Cab).....	16 L (4.2 gal)
5090M/5100M/5115M (Cab).....	22 L (5.8 gal)
5075M (OOS) .....	13.5 L (3.6 gal)
5090M/5100M/5115M (OOS) .....	19.5 L (5.2 gal)

### Crankcase with Filter:

#### Plus-50™ II

(2.9L 3 Cylinder) .....	8.5 L (2.2 gal)
(4.5L 4 Cylinder) .....	13 L (3.4 gal)

### Transmission and Hydraulic System:

#### Hy-Gard™

.....	39.5 L (10.4 gal)
-------	-------------------

### Mechanical Front Wheel Drive (MFWD) Differential Housing:

#### Hy-Gard™

.....	5 L (1.3 gal)
-------	---------------

### Mechanical Front Wheel Drive (MFWD) Hubs (Each):

#### Hy-Gard™

.....	0.8 L (0.2 gal)
-------	-----------------

[Return to Filter Overview](#)

\*Parts located in front with respect to model image.


# REPLACEMENT PARTS GUIDE

5M Series - 5075M(ME000001-), 5090M(ME000001-), 5100M(ME000001-), 5115M(ME000001-) Tractors

## ENGINE



**BRAKE DISK**  
[SJ27050](#)



**CLUTCH DISK**  
[SJ20988](#)



**BATTERY**  
[TY25879B](#) (12V)



**ALTERNATOR**  
[RE555751](#) (200A)  
[RE544809](#) (90A)  
[RE554568](#) (120A)



## CAB

### SEAT

[RE251273](#) (W/ Mechanical Suspension)  
(OOS)(ALL)

[SJ21703](#) (W/ Air Suspension)  
(OOS)(ALL)

[SJ16332](#) (W/ Mechanical Suspension)  
(Cab)(ALL)

[SJ20768](#) (Air Suspension,W/ Swivel)  
(Cab)(ALL)

[SJ18912](#) (W/ Air Suspension,low Frequency)  
(Cab)(ALL)

[SJ39281](#) (Instructional Seat) (ALL)

[TCA18457](#) (Back)

[TCA18456](#) (Bottom)



### FAN DRIVE BELT

[SU23542](#) (5090M,5100M,5115M) (CAB)

[DZ118827](#) (5090M,5100M,5115M) (OOS)

[SU39383](#) (5075M) (W/O AC)

[SU28901](#) (5075M) (A/C Compressor)



## AXLE

### TIE ROD

[RE271437](#)

[RE271440](#) (Ball Joint)

[RE271441](#) (90 Degree)



**JOHN DEERE**  
Genuine Parts and Service

CLICK PART NUMBER TO BUY