

REPLACEMENT PARTS GUIDE

T660 Combine (115000-)

ENGINE

**TIER 4
PRIMARY AIR FILTER**



[HXE11090](#)

SECONDARY AIR FILTER



[HXE11091](#)

Change as require or when Diagnostic Trouble Code (DTC) is generated.

OIL FILTER



[RE509672](#)

Change after every 250 hours or every year.

DIESEL EXHAUST FLUID DOSING



[DZ114640](#)

Change every 4500 hours or Diagnostic Trouble Code (DTC) generated

MAIN ENGINE GEARCASE FILTER



[CE19990](#)

Change after every 400 hours or every year

DIESEL PARTICULATE FILTER



[DZ100174](#)

Check Every 4500 hours or Diagnostic Trouble Code (DTC) is generated..

**LONG FILTER
AIR CLEANER FILTER**



[AH164062](#)

SECONDARY AIR FILTER

[AH164063](#)

Change as require or when Diagnostic Trouble Code (DTC) is generated.

**FUEL FILTER
PRIMARY FUEL FILTER**



[RE520906](#)

PRIMARY AND SECONDARY FUEL FILTER



[RE525523](#)

Change as require or when Diagnostic Trouble Code (DTC) is generated..

**MAIN ENGINE GEARCASE FILTER
(PRODRIVE™ TRANSMISSION)**



[AH128449](#)

Change after first 100 hours.



CAB

FRESH AIR FILTER

[RE284091](#)

Clean or replace every 50 hours and as required

RECIRCULATION AIR FILTER

[L214634](#)

Clean and Replace as required

ENGINE

FUEL PRECLEANER FILTER

[R502778](#)

PREMIUM FUEL PRECLEANER FILTER

[N378886](#)

Drain every 50 hours or weekly

DIESEL EXHAUST FLUID LINE

[DZ100304](#)

Change every 4500 hours or Diagnostic Trouble Code (DTC) generated

**FINAL TIER 4
PRIMARY FUEL FILTER**

[RE539465](#)

SECONDARY FUEL FILTER

[DZ112918](#)

Change as require or when Diagnostic Trouble Code (DTC) is generated

**OIL RESERVOIR FILTER
W/ FAN DRIVE**

[AXE43821](#)

W/O FAN DRIVE

[AXE43820](#)

Change after every 400 hours or ever year.

CAPACITIES

T660 Combine (115000-)

CAPACITIES (Approximate):

Fuel Tank:

..... 800 L (210 gal)

Grain Tank

..... 9000 L (2378 gal)

Cooling System with Heater: (Cool-Gard II)

..... 45 L (11.88 gal)

Engine Crankcase with Filter (Plus-50™ II)

..... 29 L (7.6 gal)

Transmission

**(3-Speed Mechanical Shift and Push Button Shift) -
(GL-5)**

..... 9.6 L (2.53 gal)

Transmission

(Prodrive™) – (GI-5)

..... 13 L (3.43 gal)

Final Drive (GL-5)

Standard (130000-)

..... 8 L (2.11 gal)

HillMaster™

..... 7 L (1.85 gal)

Dual Wheel

.....23.5 (6.20 gal)

Engine Gearcase with Transfer

**(3-Speed Mechanical Shift and Push Button Shift Machines) –
(Hy-Gard™)**

..... 16 L (4.22 gal)

Engine Gearcase with Transfer

(ProDrive™ Machines) –(Hy-Gard™)

..... 20 L (5.25 gal)

Hydraulic System Reservoir (Hy-Gard™)

..... 45 L (11.88 gal)

Feeder house reverser gear case (ISO VG 460 Fully Synthetic)

..... 2 L (0.5 gal)

Countershaft drive gear case

(GL-5)

..... 1.2 L (0.32 gal)

Loading Auger Gearcase (GL-5)

.....3 L(0.5 gal)

REPLACEMENT PARTS GUIDE

T660 COMBINE

THRESHING

MY11-22

[AZ58905](#) – RASP BARS

Paired by weight with deep heat treatment for excellent threshing, good drum balancing and long lifetime.

MY11-15

[AXE53048](#) - UNIVERSAL CONCAVE

MY16-18

[AXE68051](#) - HIGH-DIVERSITY UNIVERSAL CONCAVE

Perfect fit and versatility with the adjustable booster bar.

[AXE53100](#) - SMALL GRAIN CONCAVE

MY16-18

[AXE68168](#) - HIGH-DIVERSITY SMALL GRAIN CONCAVE

Exactly welded for easy adjustment and perfect threshing.

MY19-22

[AXE59411](#) - HIGH VERSATILITY CONCAVE

[AXE59409](#) - CONCAVE INSERT SMALL GRAIN

[BXE10909](#) - ROUND BAR CONCAVE INSERT KIT

High versatility with easy-to-exchange inserts.



STRAW CHOPPER

PREMIUM KNIVES

Induction hardened to resist wear and tear at the punched hole and the cutting edge.

MY11-15

[Z103205](#) - PREMIUM CHOPPER SERRATED KNIFE

[Z75874](#) - PREMIUM CHOPPER STATIONARY KNIFE

MY11-22

[Z105500](#) - PREMIUM HEAVY-DUTY SERRATED KNIFE

STANDARD KNIVES

Induction hardened to resist wear and tear at the punched hole and the cutting edge.

MY11-15

[Z77601](#) - STANDARD CHOPPER SERRATED KNIFE

[Z42176](#) - STANDARD CHOPPER CORN KNIFE

MY11-15, MY11-15

[HXE13024](#) - STANDARD CHOPPER STATIONARY KNIFE SMOOTH

MY11-22

[Z53454](#) - STANDARD CHOPPER SMOOTH KNIFE

[HXE13023](#) - STANDARD CHOPPER STATIONARY KNIFE SERRATED

REPLACEMENT PARTS GUIDE

T660 COMBINE

FEEDERHOUSE

OUTER CHAIN

Made for smooth running, resisting load spikes and minimal elongation.



MY11-15

[AZ63336](#)



[AZ102573](#) (HEAVY DUTY)



MY16-22

[AXE41939](#)

INNER CHAIN

Made for smooth running, resisting load spikes and minimal elongation.



MY11-15

[AZ63337](#)



[AZ102574](#) (HEAVY DUTY)



MY16-22

[AXE41940](#)



GRAIN HANDLING

[AZ101808](#) - CLEAN GRAIN ELEVATOR CHAIN

Made for smooth running, resisting load spikes and minimal elongation.



STRAW WALKER

MY16-22

[AZ45586](#) - BEARING

Original John Deere bearings don't warp, open, crack or break, nor will they seize on the shaft.

