

# RENTAL PRODUCT COMPARISON



JOHN DEERE

## Excavators

| DEERE          | Max. Digging Depth     |                        | SAE Operating Weight                 | Maximum Blade/Transport Width           | CAT                  | KUBOTA                         | BOBCAT | TAKEUCHI | KOMATSU                            | VOLVO                | CASE      | LINK-BELT |
|----------------|------------------------|------------------------|--------------------------------------|---|----------------------|--------------------------------|--------|----------|------------------------------------|----------------------|-----------|-----------|
|                | Short Arm              | Long Arm               |                                      |   |                      |                                |        |          |                                    |                      |           |           |
| 17G            | 7 ft. 2 in. (2.19 m)   | —                      | 3,790 lb. (1,720 kg)                 | 4 ft. 2 in. (1.28 m)                    | 301.7 CR             | U17, KX018-4                   | E20    | TB216    | —                                  | ECR18E, EC20E        | CX17C     | —         |
| 26G            | 8 ft. 6 in. (2.59 m)   | —                      | 5,780–6,110 lb. (2,620–2,770 kg)     | 4 ft. 11 in. (1.50 m)                   | 302.7D CR            | U25S, KX71-3S                  | E26    | TB225    | —                                  | ECR25D, EC27D        | CX26C     | —         |
| 30G            | 9 ft. 2 in. (2.79 m)   | —                      | 6,850–7,220 lb. (3,105–3,275 kg)     | 5 ft. 9 in. (1.74 m)                    | 303E CR              | KX033-4                        | E32    | TB230    | PC30MR-5                           | —                    | CX30C     | —         |
| 35G            | 10 ft. 0 in. (3.06 m)  | 11 ft. 4 in. (3.46 m)  | 7,760–8,135 lb. (3,520–3,690 kg)     | 5 ft. 9 in. (1.74 m)                    | 303.5E2 CR           | U35-4, KX040-4                 | E35    | TB235    | PC35MR-5                           | EC35D, ECR40D        | CX37C     | —         |
| 50G            | 11 ft. 7 in. (3.53 m)  | 12 ft. 7 in. (3.83 m)  | 10,560–10,847 lb. (4,790–4,920 kg)   | 6 ft. 7 in. (2.00 m)                    | 305E2 CR             | U55-4, U55-5, KX057-4, KX057-5 | E50    | TB250    | PC45MR-5                           | ECR50, ECR58, ECR58D | CX57C     | —         |
| 60G            | 12 ft. 4 in. (3.77 m)  | 13 ft. 6 in. (4.12 m)  | 13,250–13,620 lb. (6,010–6,180 kg)   | 6 ft. 7 in. (2.00 m)                    | 305.5E2 CR           | KX057-4, KX057-5               | E60    | TB260    | PC55MR-5                           | EC60E                | CX60C     | —         |
| 75G            | 15 ft. 1 in. (4.61 m)  | —                      | 17,952 lb. (8,143 kg)                | 7 ft. 9 in. (2.36 m)                    | 307.5                | KX080-4                        | —      | TB280FR  | PC78US                             | —                    | CX75C SR  | 75 X3     |
| 85G            | 14 ft. 10 in. (4.51 m) | —                      | 19,244 lb. (8,729 kg)                | 7 ft. 3 in. (2.20 m)                    | 308 CR               | KX080-4                        | E85    | TB290    | PC88MR-10, PC88MR-11               | ECR88D               | CX80C     | 80 X3     |
| 130G           | 18 ft. 2 in. (5.54 m)  | 19 ft. 9 in. (6.03 m)  | 29,601–30,801 lb. (13,439–13,984 kg) | 8 ft. 10 in. (2.69 m)                   | 313, 313 GC, 313F GC | —                              | —      | —        | PC130-11                           | EC140E               | CX130D    | 130 X4    |
| 135G           | 18 ft. 4 in. (5.49 m)  | 20 ft. 0 in. (5.98 m)  | 31,500–33,920 lb. (14,300–15,400 kg) | 8 ft. 10 in. (2.69 m)                   | 315, 315 GC, 315F L  | —                              | E145   | —        | PC138US                            | ECR145E              | CX145D SR | 145 X4    |
| 160G LC        | 19 ft. 7 in. (5.98 m)  | 21 ft. 4 in. (6.49 m)  | 39,526 lb. (17,945 kg)               | 8 ft. 10 in. (2.69 m)                   | 316, 317, 317 GC     | —                              | E165   | —        | PC170LC                            | E160E                | CX160D    | 160 X4    |
| 190G W Wheeled | 19 ft. 2 in. (5.83 m)  | 19 ft. 5 in. (5.93 m)  | 43,431–45,300 lb. (19,700–20,500 kg) | 8 ft. 11 in. (2.73 m)                   | M318F/320F           | —                              | —      | —        | —                                  | EW180E               | —         | —         |
| 200G           | 21 ft. 7 in. (6.57 m)  | 23 ft. 2 in. (7.07 m)  | 45,789 lb. (20,788 kg)               | 9 ft. 10 in. (3.00 m)                   | 320, 320 GC          | —                              | —      | —        | —                                  | —                    | —         | 210 X4    |
| 210G/210G LC   | 21 ft. 11 in. (6.67 m) | —                      | 51,061–52,097 lb. (23,161–23,631 kg) | 9 ft. 11 in.–10 ft. 6 in. (3.02–3.19 m) | 320, 323             | —                              | —      | —        | PC210LCI-11, PC210LC-11, HB215LC-3 | EC220E               | CX210D    | —         |
| 245G LC        | 21 ft. 8 in. (6.62 m)  | —                      | 56,170–56,830 lb. (25,500–25,800 kg) | 10 ft. 6 in. (3.19 m)                   | 325                  | —                              | —      | —        | PC238USLC                          | ECR235E              | CX245D SR | 245 X4    |
| 250G LC        | 21 ft. 4 in. (6.50 m)  | 25 ft. 0 in. (7.61 m)  | 56,100 lb. (25,463 kg)               | 11 ft. 1 in. (3.39 m)                   | 326                  | —                              | —      | —        | PC240LC                            | EC250E               | CX250D    | 250 X4    |
| 300G LC        | 23 ft. 8 in. (7.22 m)  | 25 ft. 10 in. (7.87 m) | 69,223 lb. (31,399 kg)               | 11 ft. 1 in. (3.39 m)                   | 330, 330 GC          | —                              | —      | —        | PC290LC                            | EC300E               | CX300D    | 300 X4    |
| 345G LC        | 22 ft. 8 in. (6.92 m)  | 24 ft. 10 in. (7.57 m) | 78,710 lb. (35,700 kg)               | 11 ft. 1 in. (3.39 m)                   | 335                  | —                              | —      | —        | —                                  | ECR335E              | —         | —         |
| 350G LC        | 18 ft. 5 in. (5.62 m)  | 26 ft. 10 in. (8.18 m) | 79,655 lb. (36,131 kg)               | 11 ft. 2 in. (3.39 m)                   | 336 GC               | —                              | —      | —        | PC360LC-11, PC360LCI-11            | EC350E               | CX350D    | 350 X4    |

## Compact Wheel Loaders

| DEERE | Loader Dump Clearance                  | Bucket Capacity              | CASE       | CAT        | VOLVO      | JCB |
|-------|--|------------------------------|------------|------------|------------|-----|
| 204L  | 7 ft. 9 in.–8 ft. 0 in. (2.38–2.43 m)  | 1.0–1.4 cu. yd. (0.8–1.1 m³) | 21F, 121F  | 906M       | L25H       | 407 |
| 244L  | 8 ft. 0 in.–8 ft. 3 in. (2.45–2.52 m)  | 1.0–1.4 cu. yd. (0.8–1.1 m³) | 121F, 221F | 906M, 907M | L25H, L30G | 409 |
| 304L  | 8 ft. 2 in.–8 ft. 7 in. (2.49–2.62 m)  | 1.0–2.1 cu. yd. (0.8–1.6 m³) | 221F, 321F | 907M, 908M | L30G       | 409 |
| 324L  | 8 ft. 0 in.–10 ft. 3 in. (2.45–3.13 m) | 1.0–2.1 cu. yd. (0.8–1.6 m³) | 321F       | 908M       | L35G       | —   |
| 344L  | 9 ft. 0 in.–10 ft. 3 in. (2.75–3.12 m) | 2.0–2.6 cu. yd. (1.5–2.0 m³) | —          | 910M, 914M | L45H       | —   |

## Wheel Loaders

| DEERE      | Loader Dump Clearance                   | Bucket Capacity                | CASE  | CAT           | VOLVO | KOMATSU |
|------------|---|--------------------------------|-------|---------------|-------|---------|
| 444 P Tier | 8 ft. 5 in.–9 ft. 9 in. (2.56–2.96 m)   | 2.5–4.5 cu. yd. (1.9–3.4 m³)   | 521G  | 918M, 920     | L50H  | WA200-8 |
| 524 P Tier | 9 ft. 1 in.–11 ft. 1 in. (2.78–3.39 m)  | 2.5–4.5 cu. yd. (1.9–3.4 m³)   | —     | 926M          | L60H  | WA200-8 |
| 544 P Tier | 9 ft. 2 in.–11 ft. 2 in. (2.80–3.41 m)  | 2.5–5.25 cu. yd. (1.9–4.0 m³)  | 621G  | 930M          | L70H  | WA270-8 |
| 624 P Tier | 9 ft. 4 in.–11 ft. 4 in. (2.84–3.46 m)  | 2.5–5.25 cu. yd. (1.9–4.0 m³)  | 721G  | 938M          | L90H  | WA320-8 |
| 644 G Tier | 9 ft. 3 in.–9 ft. 9 in. (2.83–2.98 m)   | 4.0–4.25 cu. yd. (3.1–3.25 m³) | 821G  | 950 GC, 950M  | L110H | WA380-8 |
| 644 P Tier | 9 ft. 5 in.–10 ft. 9 in. (2.87–3.28 m)  | 4.0–4.75 cu. yd. (3.1–3.6 m³)  | 821G  | 950 GC, 950M  | L110H | WA380-8 |
| 644 X Tier | 9 ft. 2 in.–10 ft. 8 in. (2.81–3.25 m)  | 4.0–4.75 cu. yd. (3.1–3.6 m³)  | 821G  | 950M, 962M    | L110H | WA380-8 |
| 724 P Tier | 9 ft. 5 in.–10 ft. 7 in. (2.87–3.21 m)  | 4.0–5.0 cu. yd. (3.1–3.8 m³)   | 921G  | 962M          | L120H | —       |
| 744L       | 9 ft. 2 in.–20 ft. 10 in. (2.80–6.34 m) | 5.0–5.85 cu. yd. (3.8–4.5 m³)  | 1021G | 966M, 966M XE | L150H | WA470-8 |

## Skid Steers

| DEERE | Class              | Rated Operating Capacity at 50% Tipping Load | Gross/Net Power          | BOBCAT       | CAT               | KUBOTA   | NEW HOLLAND  |
|-------|--------------------|--|--------------------------|--------------|-------------------|----------|--------------|
| 312GR | 1,351–1,600 lb.    | 1,550 lb. (704 kg)                           | 51/48 hp (37.8/35.8 kW)  | S510*        | 226D3             | —        | L216         |
| 314G* | 1,751–2,000 lb.    | 1,760 lb. (799 kg)                           | 51/48 hp (37.8/35.8 kW)  | S530         | —                 | —        | L218*        |
| 316GR | 1,601–1,750 lb.    | 1,750 lb. (795 kg)                           | 65/61 hp (48.5/45.6 kW)  | S62          | 236D3             | —        | —            |
| 318G* | 1,751–2,000 lb.    | 1,945 lb. (883 kg)                           | 65/61 hp (48.5/45.6 kW)  | S570*        | 232D3*            | SSV65-2* | L218*, L220* |
| 320G* | 2,001–2,200 lb.    | 2,190 lb. (994 kg)                           | 69/66 hp (51.7/49.4 kW)  | —            | 242D3*, 246D3     | —        | L221         |
| 324G* | 2,201–2,700 lb.    | 2,690 lb. (1,221 kg)                         | 74/70 hp (55.0/52.5 kW)  | S64*, S66*   | 262D3*            | SSV75-2* | L228*        |
| 330G* | 2,701–3,150 lb.    | 3,000 lb. (1,362 kg)                         | 91/89 hp (68.0/66.0 kW)  | S76*, S740*  | —                 | —        | L230*        |
| 332G* | 3,151 lb. and over | 3,600 lb. (1,634 kg)                         | 100/97 hp (74.6/72.0 kW) | S770*, S850* | 272D3*, 272D3 XE* | —        | L234*        |

Competitive models are positioned according to size class, not hp.

\*Vertical-lift path.

# Rental Product Comparison

## Compact Track Loaders

| DEERE | Class              | Rated Operating Capacity | Gross/Net Power          | BOBCAT              | CAT               | KUBOTA    | TAKEUCHI |
|-------|--------------------|--------------------------|--------------------------|---------------------|-------------------|-----------|----------|
| —     | Under 2,000 lb.    | —                        | —                        | T450                | 239D3, 249D3*     | —         | TL6R     |
| 317G* | 2,001–2,300 lb.    | 2,125 lb. (965 kg)       | 65/61 hp (48.5/45.6 kW)  | T62, T64*           | 259D3*, 279D3     | SVL75-2*  | TL8R2    |
| 325G* | 2,301–2,600 lb.    | 2,590 lb. (1176 kg)      | 74/70 hp (54.8/52.5 kW)  | T66*                | —                 | —         | TL10V2*  |
| 331G* | 3,001 lb. and over | 3,100 lb. (1407 kg)      | 91/89 hp (68.0/66.0 kW)  | T76*                | 289D3*            | SVL95-2s* | TL12R2   |
| 333G* | 3,001 lb. and over | 3,700 lb. (1680 kg)      | 100/97 hp (74.6/72.0 kW) | T740*, T770*, T870* | 299D3*, 299D3 XE* | —         | TL12V2*  |

Competitive models are positioned according to size class, not hp.

\*Vertical-lift path.

## Tractor Loaders

| DEERE   | Net Peak Power             | Operating Weight     | Loader Dump Clearance | Loader Bucket Capacity        | CASE    | CAT       | NEW HOLLAND |
|---------|----------------------------|----------------------|-----------------------|-------------------------------|---------|-----------|-------------|
| 210L EP | 69 hp (51 kW) at 2,010 rpm | 10,569 lb. (4794 kg) | 8 ft. 9 in. (2.66 m)  | 13,822 cu. yd. (0.86–0.96 m³) | 570N EP | 415 F2 IL | U80C        |
| 210L    | 93 hp (69 kW) at 2,240 rpm | 11,326 lb. (5137 kg) | 8 ft. 9 in. (2.66 m)  | 13,822 cu. yd. (0.86–0.96 m³) | —       | —         | —           |

## Backhoes

| DEERE    | Standard               | Maximum Digging Depth Extendable         | Loader Dump Clearance | Operating Weight       | CASE            | CAT                     | NEW HOLLAND   | JCB              |
|----------|------------------------|--|-----------------------|------------------------|-----------------|-------------------------|---------------|------------------|
| 310L EP  | 13 ft. 8 in. (4.16 m)  | 13 ft. 11 in.–17 ft. 4 in. (4.23–5.29 m) | 9 ft. 2 in. (2.80 m)  | 13,822 lb. (6270 kg)   | 580N EP         | 415F2                   | —             | 3CX, 3CX Compact |
| 310L     | 14 ft. 1 in. (4.30 m)  | 14 ft. 4 in.–17 ft. 10 in. (4.38–5.43 m) | 9 ft. 1 in. (2.78 m)  | 14,669 lb. (6654 kg)   | 580N            | 416F2                   | B95C          | 3CX              |
| 310SL    | 14 ft. 3 in. (4.35 m)  | 14 ft. 9 in.–18 ft. 2 in. (4.50–5.55 m)  | 8 ft. 10 in. (2.70 m) | 15,872 lb. (7199 kg)   | 580SN, 580SN WT | 420 XE, 420F2, 420F2-IT | B95C, B95C-TC | 3CX 14           |
| 310SL HL | 15 ft. 1 in. (4.59 m)  | 14 ft. 10 in.–18 ft. 2 in. (4.53–5.53 m) | 8 ft. 10 in. (2.69 m) | 16,571 lb. (7516 kg)   | 580SN, 580SN WT | 420 XE, 420F2, 420F2-IT | B95C, B95C-TC | 3CX 14 Super     |
| 315SL    | 13 ft. 5 in. (4.08 m)  | 13 ft. 11 in.–17 ft. 4 in. (4.24–5.29 m) | 8 ft. 10 in. (2.69 m) | 17,554 lb. (7962 kg)   | —               | —                       | —             | 3CX 14           |
| 410L     | 15 ft. 11 in. (4.85 m) | 15 ft. 11 in.–19 ft. 8 in. (4.85–6.00 m) | 8 ft. 9 in. (2.66 m)  | 17,786 lb. (8068 kg)   | 590SN           | 430F2, 430F2-IT         | B110C         | 3CX 15           |
| 710L     | 17 ft. 3 in. (5.26 m)  | 17 ft. 3 in.–21 ft. 9 in. (5.26–6.63 m)  | 9 ft. 6 in. (2.89 m)  | 25,588 lb. (11 607 kg) | —               | 450F                    | —             | —                |

## Crawler Dozers

| DEERE                       | Operating Weight                     | Blade Width                | Power           | CASE             | CAT  | KOMATSU   |
|-----------------------------|--------------------------------------|----------------------------|-----------------|------------------|--|---|
| 450K STD/LGP                | 17,510–18,752 lb. (7959–8522 kg)     | 97–124 in. (2464–3150 mm)  | 80 hp (60 kW)   | 650M LT/WT/LGP   | D1 XL/LGP                                    | —   |
| 550K STD/LGP                | 19,758–21,000 lb. (8981–9544 kg)     | 105–124 in. (2667–3150 mm) | 92 hp (69 kW)   | 750M LT/WT/LGP   | D2 XL/LGP                                    | D37EX/PX-24   |
| 650K XLT/LGP/SmartGrade™    | 21,320–22,343 lb. (9691–10 156 kg)   | 105–128 in. (2667–3251 mm) | 104 hp (78 kW)  | 850M LT/WT/LGP   | D3 XL/LGP, D3 Cat Grade with 3D              | D39EX/PX-24, D39EXi/PXi-24                                |
| 700L XLT/LGP/SmartGrade     | 30,900–32,088 lb. (14 016–14 555 kg) | 121–145 in. (3077–3688 mm) | 135 hp (101 kW) | 1150M LT/WT/LGP  | D4 XL/LGP, D4 Cat Grade with 3D              | D51EX/PX-24, D51EXi/PXi-24                                |
| 750L STD/XLT/LGP/SmartGrade | 37,569–40,040 lb. (17 041–18 162 kg) | 129–162 in. (3265–4083 mm) | 175 hp (131 kW) | 1650M XLT/WT/LGP | D5 XL/LGP, D5 Cat Grade with 3D              | D61EX/PX-24, D61EXi/PXi-24                                |
| 850L XLT/WLT/LGP/SmartGrade | 47,578–51,365 lb. (21 581–23 299 kg) | 129–194 in. (3266–4935 mm) | 225 hp (168 kW) | 2050M XLT/WT/LGP | D6, D6XE STD/LGP, D6, D6XE Cat Grade with 3D | D65EX/PX/WX-18, D65EXi/PXi-18, D71EX/PX-24, D71EXi/PXi-24 |

## Compact Utility Tractors

| DEERE | Engine Power      | Loader Lift Capacity* | Operating Weight     | KUBOTA                | MAHINDRA       |
|-------|-------------------|-----------------------|----------------------|-----------------------|----------------|
| 1023E | 22.4 hp (16.5 kW) | 681 lb. (309 kg)      | 1,345 lb. (610 kg)   | BX2370, BX2380        | eMax22         |
| 1025R | 23.9 hp (17.8 kW) | 681 lb. (309 kg)      | 1,444 lb. (655 kg)   | BX2670, BX2680, BX25D | eMax24, eMax25 |
| 2025R | 24.2 hp (17.8 kW) | 915 lb. (415 kg)      | 1,793 lb. (814 kg)   | B2601                 | Max24, Max26XL |
| 2032R | 31.2 hp (23.3 kW) | 1,356 lb. (615 kg)    | 2,436 lb. (1,105 kg) | B3350                 | —              |
| 2038R | 37.2 hp (27.4 kW) | 1,356 lb. (615 kg)    | 2,436 lb. (1,105 kg) | B3350                 | —              |
| 3025E | 24.7 hp (18.2 kW) | 1,356 lb. (615 kg)    | 2,222 lb. (1,008 kg) | L2501                 | 1526           |
| 3032E | 31.1 hp (22.9 kW) | 1,356 lb. (615 kg)    | 2,222 lb. (1,008 kg) | L3301                 | 1533           |
| 3038E | 37.2 hp (27.4 kW) | 1,356 lb. (615 kg)    | 2,222 lb. (1,008 kg) | L3901                 | 1538           |
| 3033R | 32.2 hp (23.7 kW) | 2,200 lb. (998 kg)    | 2,900 lb. (1316 kg)  | L3650                 | 1533           |
| 3039R | 38.7 hp (28.5 kW) | 2,200 lb. (998 kg)    | 2,900 lb. (1316 kg)  | L4060                 | 1538, 2540     |
| 3046R | 45.3 hp (33.3 kW) | 2,200 lb. (998 kg)    | 2,900 lb. (1316 kg)  | L4760                 | 2545           |
| 4044M | 43.1 hp (31.7 kW) | 2,500 lb. (1135 kg)   | 3,770 lb. (1710 kg)  | L4701, MX4800         | 4540 4WD       |
| 4044R | 43.1 hp (32.1 kW) | 2,500 lb. (1135 kg)   | 3,770 lb. (1710 kg)  | L4060                 | 3540           |
| 4052M | 51.5 hp (37.9 kW) | 2,500 lb. (1135 kg)   | 3,770 lb. (1710 kg)  | MX5200                | 4550 4WD       |
| 4052R | 51.5 hp (37.9 kW) | 2,500 lb. (1135 kg)   | 3,770 lb. (1710 kg)  | L4760, L5460          | 3550           |
| 4066M | 65.9 hp (48.5 kW) | 2,500 lb. (1135 kg)   | 3,770 lb. (1710 kg)  | MX5800                | —              |
| 4066R | 65.9 hp (48.5 kW) | 2,500 lb. (1135 kg)   | 3,770 lb. (1710 kg)  | L6060                 | —              |

\*Loader measured at full height, at pivot

## Gator™ Utility Vehicles

| DEERE      | Engine Power      | Payload Capacity   | Speed            | POLARIS           | KAWASAKI             | KUBOTA    | CUB CADET           | CLUB CAR      |
|------------|-------------------|--------------------|------------------|-------------------|----------------------|-----------|---------------------|---------------|
| HPX815E    | 18.2 hp (13.7 kW) | 1,400 lb. (635 kg) | 25 mph (40 km/h) | ProXD 2000D       | Mule 4010 4x4 Diesel | RTVx900   | 4x4 Trail           | XRT1500       |
| XUV560E    | 16.0 hp (11.9 kW) | 800 lb. (363 kg)   | 28 mph (45 km/h) | Ranger 500        | Mule SX 4x4          | RTV500    | Challenger 500      | XRT1550       |
| XUV560E S4 | 16.0 hp (11.9 kW) | 1,200 lb. (544 kg) | 28 mph (45 km/h) | Ranger Crew 570-4 | Mule 4010 Trans 4x4  | RTV X1140 | Challenger 750 Crew | XRT1550SE     |
| XUV855M S4 | 23.0 hp (17.0 kW) | 1,297 lb. (588 kg) | 32 mph (51 km/h) | ProXD 4000D       | Mule Pro-DXT         | RTV X1140 | —                   | CarryAll 1700 |