


FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

6010 Series Self-Propelled Forage Harvester - 6610, 6710, 6810, 6910


CAB RECIRCULATION AIR FILTER [Z62223](#)

Clean after every 250 hours and replaced as required.



CAB FRESH AIR FILTER [AZ43412](#)

Clean after every 250 hours and replaced as required.



HYDRAULICS HYDROSTATIC CHARGE FILTER, ALL - [AH128449](#)

Replace after the first 100 hours, then every 500 hours thereafter.

(Click here for [capacity](#))



HYDRAULICS HYDRAULIC OIL FILTER ALL - [AT120444](#)

Replace after the first 100 hours, then every 500 hours thereafter.

(Click here for [capacity](#))




ENGINE

SECONDARY AIR FILTER (6610) - [AT166136](#)

SECONDARY AIR FILTER (6710-6910) - [AZ45867](#)

Replace after every 1,500 hours and as required.



ENGINE

PRIMARY AIR FILTER
(6610) - [AZ39761](#)
(6710-6910) - [AZ45868](#)

Replace after every 1,500 hours and as required.

ENGINE

COOLANT FILTER
(6710) - [RE11992](#)
(6810-6910) W/ ENGINE N14 - [PMWF2075](#)
(6810-6910) W/ ENGINE NTA855A - [RE42052](#)

Replace after every 250 hours.

(Click here for [capacity](#))




ENGINE

OIL FILTER
(6610) - [DZ101880](#)
(6710 SN -500277) - [RE21748](#)
(6710 SN -500277) - [RE21058](#)
(6710 SN 500278-) - [RE44647](#)
(6810-6910) - [RE21058](#)
(6810-6910) - [RE42051](#)

Replace after first 100 hours and every 250 hours, thereafter.

(Click here for [capacity](#))



ENGINE

FUEL FILTER
(6610-6710) - [AR86745](#)
(6610-6710) - [AR86755](#)
(6810-6910) W/ ENGINE N14 - [PMFS1212](#)
(6810-6910) W/ ENGINE NTA855A - [RE42050](#)

Replace after every 250 hours.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

6010 Series Self-Propelled Forage Harvester - 6610, 6710, 6810, 6910

CAPACITIES (Approximate):

Fuel Tank:

6610-6910 (Standard) 700 L (185 gal)

Cooling System (Complete):

John Deere™ Low Silicate Antifreeze

6610 47 L (12.4 gal)

6710 55 L (14.4 gal)

6810-6910 64 L (16.9 gal)

Engine with Filter:

Plus-50™

6610 24 L (6.3 gal)

6710 35.5 L (9.4 gal)

6810-6910 42 L (11.1 gal)

Transmission:

Hy-Gard™

..... 9.5 L (2.5 gal)

Final Drives (Each):

Hy-Gard™

..... 5.1 L (1.34 gal)

Hydraulic System:

Hy-Gard™

Hydraulic System 46 L (12.2 gal)

Hydraulic System (with Rear Wheel Drive) 39 L (10.3 gal)

[Return to Filter Overview](#)

