


FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

7050 Series Self-Propelled Forage Harvesters 7250, 7350, 7450, 7550, 7750, 7850



CAPACITIES

7050 Series Self-Propelled Forage Harvesters 7250, 7350, 7450, 7550, 7750, 7850

CAPACITIES (Approximate):

Fuel Tank:

7250-7350 (Standard)	700 L (185 gal)
7250-7350 (Optional).....	1100 L (290 gal)
7450-7550-7750-7850 (Standard).....	1100 L (290 gal)

Cooling System (Complete):

Cool-Gard™ II

7250.....	48 L (12.7 gal)
7350.....	60 L (15.9 gal)
7450-7550-7750	71 L (18.7 gal)
7850.....	98 L (25.8 gal)

Engine with Filter:

Plus-50™ II

7250.....	28 L (7.4 gal)
7350-7450-7550-7750	60 L (18.9 gal)
7850.....	45 L (11.9 gal)

3-Speed Transmission:

GL-5

.....	7 L (1.84 gal)
-------	----------------

ProDrive™ Transmission:

Hy-Gard™

.....	13 L (3.4 gal)
-------	----------------

Final Drives (Each):

GL-5

.....	8.5 L (2.24 gal)
-------	------------------

Rear Wheel Drive Rear Axle:

GL-5

Differential-Narrow Axle	15 L (3.7 gal)
Differential-Wide Axle	19.5 L (5.2 gal)
Reduction Gear	0.7 L (0.18 gal)

Heavy-Duty Rear Axle:

GL-5

Reduction Gear	0.5 L (0.13 gal)
----------------------	------------------

Hydraulic System:

Hy-Gard™

3-Speed Transmission (Complete System).....	90 L (23.8 gal)
ProDrive™ Transmission (Complete System)	97 L (25.6 gal)
Hydraulic Tank	44.5 L (11.75 gal)

IVLOC:

Hy-Gard™

.....	19 L (5 gal)
-------	--------------

Brake System 3-Speed Transmission:

DOT3 or DOT4

Brake Fluid	1 L (0.26 gal)
Reservoir	0.5 L (0.13 gal)

AC System:

R134a

Refrigerant.....	2350 g (5.18 lb)
------------------	------------------

[Return to Filter Overview](#)

