


FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

8030 Series Track Tractors - 8230T, 8330T, 8430T

CAB RECIRCULATION AIR FILTER [RE187966](#)

Clean after every 250 hours or as required.
Replace annually and as required.
(Interval may vary according to operating conditions.)




HYDRAULIC/TRANSMISSION OIL FILTER [RE174130](#)

Replace after 100 hours and then every 750 hours.


SCREEN [RE45369](#)

Clean after every 1500 hours.
(Click here for [capacity](#))




ENGINE STEERING FILTER [RE69054](#)

Replace after every 750 hours.
(Click here for [capacity](#))



CAB AIR FILTER, STANDARD [R119168](#) FRESH AIR FILTER, HIGH EFFICEICY [RE67828](#) AIR FILTER, CARBON [RE219782](#)

Clean after every 250 hours and as required.
Replace annually and as required.
(Interval may vary according to operating conditions.)




ENGINE FUEL, FILTER KIT [RE525523](#)

Replace after every 500 hours or annually whichever occurs first.



ENGINE SECONDARY AIR FILTER [RE587794](#)

Clean after every 250 hours and as required.
Replace annually or every second replacement of primary filter.




ENGINE PRIMARY AIR FILTER [RE587793](#)

Replace annually, after six cleanings or as indicated.
(Interval may vary according to operating conditions.)

ENGINE OIL FILTER [RE509672](#)

Initial oil and filter change at 100 hours, then after every 250 hours or as required, whichever occurs first.



The extended 50 percent service interval is only allowed if using John Deere Plus-50 oil with a John Deere filter. If diesel fuel with sulfur content is 0.2 - 0.5% used, then regular interval of 250 hours between oil changes will reduced to 150 hours.

If all conditions are not met, change oil and filter at 250 hours of operation.

(Click here for [capacity](#))

ENGINE FUEL TANK VENT FILTER [RE52504](#)

Replace every after 750 hours.
(Interval may vary according to operating conditions.)



JOHN DEERE
Genuine Parts and Service

CAPACITIES

8030 Series Track Tractors - 8230T, 8330T, 8430T

CAPACITIES (Approximate):

Fuel Tank:

..... 492 L (130 gal)

Cooling System:

Cool-Gard™ II

..... 40 L (10.6 gal)

Crankcase:

Plus-50™

8230T-8330T 24 L (6.3 gal)

8430T 25.5 L (6.7 gal)

Transmission and Hydraulic System:

Hy-Gard™

Including Clean Oil Reservoir 246 L (65 gal)

[Return to Filter Overview](#)

