

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

9560 STS, 9560i STS Series Combines

ENGINE AIR FILTER

SECONDARY AIR FILTER (9560)

[RE63932](#)

Used Up To Combine Serial Number (- 720100)

[AH212295](#)

Used From Combine Serial Number (720101 -)

SECONDARY AIR FILTER (9560i)

[AH212295](#)

Change secondary filter only with primary filter.

ENGINE AIR FILTER


PRIMARY AIR FILTER (9560)

[AH148880](#) – Used Up To Combine Serial Number (- 720100)

[AH212294](#) – Used From Combine Serial Number (720101 -)

PRIMARY AIR FILTER (9560i) – [AH212294](#)

Replace every 400 hours or Service filters only when engine air filter light stays ON or change as required.
Note: Replace Secondary Filter also with Primary Filter.



ENGINE OIL FILTER

OIL FILTER (9560)


[RE509672](#) – For Engine 6081HH019-RG31818, 6081HH028-RE531333

[RE504836](#) – For Engine 6068HH058-RE526762

OIL FILTER (9560i)

[RE509672](#) – 6090HH005-RE528457

Replace after first 100 hours and then every 250 hours. Fill crank- case with seasonal viscosity grade oil or Torq-Gard Supreme™ (250 hours change interval). If using Plus-50™ oil and a John Deere filter, the service interval can be extended by 50 percent. Example: 250 hours extends to 375 hours.
Note : Change oil every 100 hours if fuel contains more than 0.5 % sulfur.



ENGINE FUEL FILTER

FINAL FUEL FILTER (9560)

[R502778](#) – For Engine 6081HH019-RG31818 Up To Engine Serial Number (-232462)

[RE522688](#) – For Engine 66081HH019-RG31818 From Engine Serial Number (232463-)

For Engine 6081HH028-RE531333

[RE522878](#) For Engine 6068HH058-RE526762

Replace every 500 hours.



FUEL WATER SEPARATOR FILTER, STANDARD

[R502778](#) – (9560 - For CIS) (9560i)

[RE541922](#) (9560) – Used From Combine Serial Number (720101 -)
Replace after first 50 hours and then every 500 hours.



ENGINE FUEL FILTER

PRIMARY FUEL FILTER (9560)




[RE522372](#) – For Engine 66081HH019-RG31818 Up To Engine Serial Number (-232462)

[RE531703](#) – For Engine 6081HH019-RG31818 From Engine Serial Number (232463-)

PRIMARY AND FINAL FUEL FILTER (9560i)

[RE525523](#)

Replace every 500 hours.



HYDROSTATIC PUMP / ENGINE GEARCASE / MAIN HYDRAULIC FILTER

OIL FILTER – [AH128449](#)

Replace every 400 hours.

Note: Replace all three filters at a time.

(Click here for [capacity](#))



CAB FILTER

RECIRCULATION AIR FILTER

[AH115836](#)

9560 - Used Up To Combine Serial Number(-720100)

9650i - Used Up To Combine Serial Number(-720200)

[H220870](#)

9560 - Used From Combine Serial Number (720101-)

9650i - Used From Combine Serial Number (720201-)

Clean or replace every 200 hours and as required.

CAB

AIR FILTER, HEAVY-DUTY [AH168783](#)

AIR FILTER, STANDARD [AH115833](#)

Clean or replace every 50 hours and as required.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

9560 STS, 9560i STS Series Combines

CAPACITIES (Approximate):

Fuel Tank:

9560, 9560i..... 757 L (199.97 gal)

Cooling System With Heater:

9560 (710251 - 720100)..... 40 L (10.56 gal)

9560 (720101-) (6.8 L Engine) 44 L (11.62 gal)

9560 (720101-) (8.1 L Engine) 53.3 L (14.08 gal)

9560i..... 53.3 L (14.08 gal)

Engine Crankcase With Filter:

9560 (710251 - 720100)..... 29.5 L (7.79 gal)

9560 (720101-) (6.8 L Engine) 32 L (8.45 gal)

9560 (720101-)(8.1 L Engine) 29.5 L (7.79 gal)

9560i..... 29.5 L (7.79 gal)

Transmission:

9560, 9560i..... 9.6 L (2.53 gal)

Final Drives:

9560, 9560i..... 8 L (2.11 gal)

Feeder House Reverser Gearcase Without Cooler:

9560, 9560i..... 2.3 L (0.60 gal)

Feeder House Reverser High Capacity with Cooler:

9560, 9560i..... 3.5 L (0.92 gal)

Countershaft Drive Gearcase:

9560, 9560i..... 1.2 L (0.31 gal)

Loading Auger Gearcase:

9560, 9560i..... 3.8 L (1 gal)

Two Speed Separator Drive Gearcase:

9560..... 2.4 L (0.63 gal)

9560i..... 4.7 L (1.24 gal)

Engine Gearcase with Transfer:

9560, 9560i..... 21.3 L (5.62 gal)

Hydraulic/Hydrostatic Reservoir:

9560..... 34 L (8.98 gal)

9560i..... 35 L (9.24 gal)

[Return to Filter Overview](#)

