

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

9986 Cotton Picker

CAB
FRESH AIR FILTER,
HEAVY DUTY – [AH168783](#)
AIR FILTER, STANDARD – [AH115833](#)
Replace every 200 hours
and as required.

CAB
RECIRCULATION AIR FILTER – [H115836](#)
Clean or replace every 200 hours
and as required.

HYDRAULICS
HYDRAULIC FILTER – [LVA10419](#)
HYDRAULIC FILTER – [AH128449](#)
HYDRAULIC RESERVOIR – [AE43494](#)
Replace every 400 hours
and as required.

ENGINE
SECONDARY AIR FILTER – [AR95759](#)
Replace every year and as required.
Note: Change only with primary filter.

ENGINE
PRIMARY AIR FILTER – [AR95758](#)
Replace every year and as required.

ENGINE
OIL FILTER – [DZ101880](#)
Replace after first 100 and 250 hours,
then every 250 hours. If John Deere
Plus-50™ oil is used, along with a
John Deere oil filter, the oil change
interval may be extended by
50 percent.

ENGINE
FUEL FILTER – [RE508633](#)
FUEL FILTER – [AR86745](#)
Replace every 250 hours and
as required.



CAPACITIES

9986 Cotton Picker

CAPACITIES (Approximate):

Cotton Basket, Full Height:

..... 33.6 m³ (1400 cu. ft)

Fuel Tank:

..... 568 L (150.05 gal)

Water Solution Tank:

..... 1040.8 L (274.95 gal)

Lubrication Reservoir:

John Deere Spindle Lubricant

..... 303 L (80.04 gal)

Cooling System:

Cool-Gard™

..... 42 L (11.09 gal)

Engine Crankcase including Filter:

Plus-50™

..... 29 L (7.66 gal)

Hydraulic and Hydrostatic System:

Hy-Gard™

..... 96.5 L (25.5 gal)

Hydraulic and Hydrostatic Reservoir:

Hy-Gard™

..... 66 L (17.43 gal)

Transmission:

Hy-Gard™

..... 6.6 L (1.74 gal)

Final Drive:

GL-5

..... 8.5 L (2.25 gal)

Row Unit Gear Case:

Hy-Gard™

..... 3.7 L (0.98 gal)

[Return to Filter Overview](#)

