


FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

W155 Windrower


CAB
FRESH AIR INTAKE FILTER [AFH208659](#)
 Clean after every 50 hours and change as required.



ENGINE
DIESEL PARTICULATE FILTER [RE565702](#)
 Replace after every 5500 hours and as required.




ENGINE
SECONDARY AIR FILTER [PMAF55308](#)
 Replace each season and as required.



ENGINE
PRIMARY AIR FILTER [PMAF55005](#)
 Replace after every 250 hours or each season, whichever comes first.

CAB
RETURN AIR FILTER [AFH208656](#)
 Clean every 100 hours and replace as required.




ENGINE
OPEN CRANKCASE VENTILATION (OCV) FILTER [DZ105796](#)
 Replace every 1500 hours.




ENGINE
FUEL STRAINER [AFH212991](#)
 Replace each season.
 (Click here for [capacity](#))



ENGINE
PRIMARY FUEL FILTER [RE551507](#)
SECONDARY FUEL FILTER [RE551508](#)
 Replace after every 500 hours or each season, whichever comes first.



HYDRAULIC
HYDRAULIC FILTER [AFH208689](#)
[RE45864](#)
 Replace after 500 hours or each season, whichever comes first.
 (Click here for [capacity](#))



ENGINE
OIL FILTER [RE504836](#)
 Replace after every 250 hours or each season, whichever comes first.
 (Click here for [capacity](#))



ENGINE
DIESEL EXHAUST FLUID (DEF) DOSING UNIT FILTER [DZ114640](#) USE FOR [DZ111283](#) (DOSING UNIT PUMP)
[RE554498](#) USE FOR [RE552175](#) (DOSING UNIT PUMP)
 Replace after every 4500 hours or every three years of operation, whichever comes first.
 (Click here for [capacity](#))



CAPACITIES

W155 Windrower

CAPACITIES (Approximate):

Fuel Tank:

..... 367 L (97 gal)

Cooling System:

Cool-Gard™ II

..... 27.2 L (7.18 gal)

Engine Oil with Filter:

Plus-50™ II

..... 11.9 L (3.1 gal)

Hydraulic System (Reservoir):

Windrower and Platform Drive Lubricant 15W - 40

..... 65 L (17.2 gal)

Diesel Exhaust Fluid (DEF) Tank:

John Deere™ Diesel Exhaust Fluid

..... 14.1 L (3.75 gal)

Final Drives Each:

GL-5 85W-140, Before Initial Change

GL-5 Fully Synthetic Gear Lubricant 75W-90, After Initial Change

..... 1.4 L (0.36 gal)

Pump Drive Gear Case:

GL-5 Fully Synthetic Gear Lubricant 75W-90

..... 2.1 L (0.55 gal)

Air-conditioning System:

Air Conditioning Refrigerant 2270 g (5 lb)

Air Conditioning Compressor Oil 240 ml (8.1 fl. oz.)

[Return to Filter Overview](#)

