

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

## 800 Series 870, 900 Series 970, 1070 Series 1070 Tractors

### HYDRAULIC OIL FILTER

[RE27284](#) (ALL)

Change after every 500 hours.

(Click here for [capacity](#))

### ENGINE

FUEL FILTER  
[T111383](#) (ALL)

Clean after every 200 hours.

### ENGINE

PRIMARY AIR FILTER  
[UC11955](#) (ALL)

SECONDARY AIR FILTER  
[CH12881](#) (ALL)

Change after every 400 hours. Change as required.

### ENGINE

OIL FILTER  
[M806419](#) (ALL)

Replace after first 50 hours, then every 200 hours.

(Click here for [capacity](#))



**JOHN DEERE**

Genuine Parts and Service

# CAPACITIES

## 800 Series 870, 900 Series 970, 1070 Series 1070 Tractors

### CAPACITIES (Approximate):

#### Fuel Tank:

870, 970.....	32 L (8.5 gal)
1070.....	40 L (10.6 gal)

#### Cooling System:

##### Cool-Gard™ II

870.....	5.2 L (1.14 gal)
970, 1070.....	5.8 L (1.27 gal)

#### Crankcase w/ Filter:

870.....	4.8 L (1.05 gal)
970, 1070.....	5.3 L (1.16 gal)

#### Transmission and Hydraulic System:

##### Hy-Gard™

870, 970.....	21 L (5.5 gal)
---------------	----------------

[Return to Filter Overview](#)

