

BUCKETS



JOHN DEERE

CONSTRUCTION | DIRT | FOUNDRY | GRADING HEEL |
LIGHT MATERIAL | TOOTH | UTILITY




BUCKETS

CONSTRUCTION | DIRT | FOUNDRY | GRADING HEEL |
LIGHT MATERIAL | TOOTH | UTILITY



Specifications


- John Deere buckets have significantly greater capacities than many competitive buckets, enabling them to carry and do more. They capably take advantage of the steep dump angles and high bucket rollbacks of G-Series Skid Steers and Compact Track Loaders. They also enhance the performance of many competitive models.
- Construction bucket:** Offers a low-profile backplate for better operator visibility to the cutting edge and a rounded interior for excellent fill-and-dump performance. This design provides maximum visibility and reach as well as lower breakout forces versus shorter dirt or grading buckets. Cutting edge and bolt-on toothbar holes are pre-drilled for easy assembly.
- Dirt bucket:** Easily move and dump gravel, mulch, manure, brush, or dirt.
- Foundry bucket:** Is shorter from bucket heel to cutting edge, to provide maximum breakout force for tough digging conditions. Bolt-on toothbar holes are pre-drilled.
- Grading-heel bucket:** Featuring a smooth bottom free of lifts or edges, this bucket is ideal for land shaping, dirt leveling, and installation of new landscape for sodding, irrigation, and drainage.
- Light-material bucket:** Is designed for handling woodchips, sawdust, snow, grain, fertilizer, or a myriad of loosely compacted low-density materials.
- Tooth bucket:** Is made especially for loosening compacted soil or grubbing out rocks. Unlike one with a toothbar kit added, this bucket offers a flat bottom, making it an excellent tool for back-dragging.
- Utility bucket:** Is perfect for light, high-volume materials. Bolt-on cutting edge holes are pre-drilled.




CONSTRUCTION




FOUNDRY



UTILITY



TOOTH



GRADING HEEL

Buckets	Width	Length	Height	Weight	Struck Capacity	Heaped Capacity
C66 Construction	1675 mm (66 in.)	940 mm (37.0 in.)	540 mm (21.3 in.)	200 kg (440 lb.)	0.34 m ³ (0.44 cu. yd.)	0.46 m ³ (0.60 cu. yd.) (16.2 cu. ft.)
C72 Construction	1830 mm (72 in.)	940 mm (37.0 in.)	540 mm (21.3 in.)	220 kg (485 lb.)	0.36 m ³ (0.47 cu. yd.)	0.50 m ³ (0.65 cu. yd.) (17.7 cu. ft.)
C78 Construction	1980 mm (78 in.)	940 mm (37.0 in.)	545 mm (21.4 in.)	272 kg (600 lb.)	0.40 m ³ (0.52 cu. yd.)	0.54 m ³ (0.71 cu. yd.) (19.1 cu. ft.)
C84 Construction	2135 mm (84 in.)	940 mm (37.0 in.)	545 mm (21.4 in.)	284 kg (625 lb.)	0.42 m ³ (0.55 cu. yd.)	0.60 m ³ (0.78 cu. yd.) (21.2 cu. ft.)
C90 Construction	2285 mm (90 in.)	965 mm (37.9 in.)	560 mm (22.1 in.)	442 kg (975 lb.)	0.46 m ³ (0.60 cu. yd.)	0.65 m ³ (0.85 cu. yd.) (23.0 cu. ft.)
D56 Dirt	1420 mm (56 in.)	870 mm (34.2 in.)	540 mm (21.2 in.)	152 kg (335 lb.)	0.26 m ³ (0.34 cu. yd.)	0.34 m ³ (0.44 cu. yd.) (12.0 cu. ft.)
D60 Dirt	1525 mm (60 in.)	870 mm (34.2 in.)	540 mm (21.2 in.)	160 kg (355 lb.)	0.28 m ³ (0.37 cu. yd.)	0.38 m ³ (0.50 cu. yd.) (13.4 cu. ft.)
D60 Dirt With Teeth	1525 mm (60 in.)	1020 mm (40.2 in.)	540 mm (21.2 in.)	186 kg (410 lb.)	0.28 m ³ (0.37 cu. yd.)	0.38 m ³ (0.50 cu. yd.) (13.4 cu. ft.)
D66 Dirt	1675 mm (66 in.)	870 mm (34.2 in.)	540 mm (21.2 in.)	170 kg (375 lb.)	0.30 m ³ (0.39 cu. yd.)	0.42 m ³ (0.55 cu. yd.) (14.8 cu. ft.)
D66 Dirt With Teeth	1675 mm (66 in.)	1020 mm (40.2 in.)	540 mm (21.2 in.)	196 kg (430 lb.)	0.30 m ³ (0.39 cu. yd.)	0.42 m ³ (0.55 cu. yd.) (14.8 cu. ft.)
F66 Foundry	1675 mm (66 in.)	690 mm (27.2 in.)	660 mm (26.0 in.)	178 kg (390 lb.)	0.32 m ³ (0.42 cu. yd.)	0.40 m ³ (0.52 cu. yd.) (14.1 cu. ft.)
F72 Foundry	1830 mm (72 in.)	690 mm (27.2 in.)	660 mm (26.0 in.)	194 kg (430 lb.)	0.34 m ³ (0.44 cu. yd.)	0.44 m ³ (0.58 cu. yd.) (15.5 cu. ft.)
F78 Foundry	1980 mm (78 in.)	690 mm (27.2 in.)	660 mm (26.0 in.)	252 kg (555 lb.)	0.36 m ³ (0.47 cu. yd.)	0.48 m ³ (0.63 cu. yd.) (17.0 cu. ft.)
GH60 Grading Heel	1525 mm (60 in.)	880 mm (34.7 in.)	565 mm (22.2 in.)	230 kg (510 lb.)	0.30 m ³ (0.39 cu. yd.)	0.38 m ³ (0.50 cu. yd.) (13.4 cu. ft.)
GH60 Grading Heel With Teeth	1525 mm (60 in.)	1035 mm (40.7 in.)	565 mm (22.2 in.)	254 kg (560 lb.)	0.30 m ³ (0.39 cu. yd.)	0.38 m ³ (0.50 cu. yd.) (13.4 cu. ft.)
GH66 Grading Heel	1675 mm (66 in.)	880 mm (34.7 in.)	565 mm (22.2 in.)	244 kg (535 lb.)	0.32 m ³ (0.42 cu. yd.)	0.44 m ³ (0.58 cu. yd.) (15.5 cu. ft.)
GH66 Grading Heel With Teeth	1675 mm (66 in.)	1035 mm (40.7 in.)	565 mm (22.2 in.)	258 kg (570 lb.)	0.32 m ³ (0.42 cu. yd.)	0.44 m ³ (0.58 cu. yd.) (15.5 cu. ft.)
GH72 Grading Heel	1830 mm (72 in.)	880 mm (34.7 in.)	575 mm (22.7 in.)	266 kg (590 lb.)	0.36 m ³ (0.47 cu. yd.)	0.48 m ³ (0.63 cu. yd.) (17.0 cu. ft.)
GH72 Grading Heel With Teeth	1830 mm (72 in.)	1035 mm (40.7 in.)	575 mm (22.7 in.)	290 kg (640 lb.)	0.36 m ³ (0.47 cu. yd.)	0.48 m ³ (0.63 cu. yd.) (17.0 cu. ft.)
GH78 Grading Heel	1980 mm (78 in.)	880 mm (34.7 in.)	580 mm (22.8 in.)	328 kg (725 lb.)	0.38 m ³ (0.50 cu. yd.)	0.52 m ³ (0.68 cu. yd.) (18.4 cu. ft.)
GH78 Grading Heel With Teeth	1980 mm (78 in.)	1035 mm (40.8 in.)	580 mm (22.8 in.)	354 kg (780 lb.)	0.38 m ³ (0.50 cu. yd.)	0.52 m ³ (0.68 cu. yd.) (18.4 cu. ft.)
LM90 Light Material	2285 mm (90 in.)	1210 mm (47.6 in.)	945 mm (37.1 in.)	550 kg (1,215 lb.)	1.15 m ³ (1.50 cu. yd.)	1.50 m ³ (1.96 cu. yd.) (53.0 cu. ft.)
T66 Tooth	1675 mm (66 in.)	1090 mm (42.9 in.)	540 mm (21.3 in.)	224 kg (495 lb.)	0.32 m ³ (0.42 cu. yd.)	0.46 m ³ (0.60 cu. yd.) (16.2 cu. ft.)
T72 Tooth	1830 mm (72 in.)	1090 mm (42.9 in.)	540 mm (21.3 in.)	246 kg (540 lb.)	0.36 m ³ (0.47 cu. yd.)	0.50 m ³ (0.65 cu. yd.) (17.7 cu. ft.)
T78 Tooth	1980 mm (78 in.)	1095 mm (43.1 in.)	545 mm (21.4 in.)	298 kg (660 lb.)	0.40 m ³ (0.52 cu. yd.)	0.54 m ³ (0.71 cu. yd.) (19.1 cu. ft.)
T84 Tooth	2135 mm (84 in.)	1095 mm (43.1 in.)	545 mm (21.4 in.)	314 kg (695 lb.)	0.42 m ³ (0.55 cu. yd.)	0.60 m ³ (0.78 cu. yd.) (21.2 cu. ft.)
T90 Tooth	2285 mm (90 in.)	1115 mm (44.0 in.)	560 mm (22.0 in.)	442 kg (975 lb.)	0.46 m ³ (0.60 cu. yd.)	0.65 m ³ (0.85 cu. yd.) (23.0 cu. ft.)
U66 Utility	1675 mm (66 in.)	895 mm (35.3 in.)	705 mm (27.8 in.)	212 kg (465 lb.)	0.46 m ³ (0.60 cu. yd.)	0.60 m ³ (0.78 cu. yd.) (21.2 cu. ft.)
U72 Utility	1830 mm (72 in.)	895 mm (35.3 in.)	705 mm (27.8 in.)	226 kg (500 lb.)	0.50 m ³ (0.65 cu. yd.)	0.65 m ³ (0.85 cu. yd.) (23.0 cu. ft.)
U78 Utility	1980 mm (78 in.)	900 mm (35.4 in.)	710 mm (27.9 in.)	292 kg (645 lb.)	0.54 m ³ (0.71 cu. yd.)	0.70 m ³ (0.92 cu. yd.) (24.7 cu. ft.)
U84 Utility	2135 mm (84 in.)	900 mm (35.4 in.)	710 mm (27.9 in.)	310 kg (685 lb.)	0.58 m ³ (0.76 cu. yd.)	0.75 m ³ (0.98 cu. yd.) (26.5 cu. ft.)

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

