

# PALLET FORKS

STANDARD DUTY | HEAVY DUTY | SEVERE DUTY



JOHN DEERE



# Pallet Forks

STANDARD DUTY | HEAVY DUTY | SEVERE DUTY



## Specifications

- Quik-Tatch™ system allows easy hook-up in seconds.
- Pallet forks are available in lengths of 1067 and 1219 mm (42 and 48 in.) for standard duty, 1219 mm (48 in.) for heavy duty, and 1219 and 1524 mm (48 and 60 in.) for severe duty.
- Skid-resistant steps on both sides of the pallet-fork frame ease vehicle entrance and exit.
- Standard-, heavy-, and severe-duty styles hold forks in a rigid position.
- Single-piece backrest is available on the standard- and heavy-duty options. Severe-duty skid steer loader option has a walk-through backrest with a bolt-on option.
- Standard-duty forks can be positioned in widths from 203–1016 mm (8–40 in.) in 102-mm (4 in.) increments, heavy-duty models in widths from 203–1524 mm (8–60 in.) in 102-mm (4 in.) increments, and severe-duty units in widths to 1143 mm (45 in.) in 127-mm (5 in.) increments or to 1524 mm (60 in.) in 136-mm (5.35 in.) increments.
- Severe-duty pallet forks offer improved visibility, increased capacity, and better durability than the previous fork-frame design.
- Like all Worksite Pro™ attachments, these pallet forks are optimized to work with John Deere G- and E-Series Skid Steers and Compact Track Loaders (CTLs), and K-II and K-Series Compact Wheel Loaders (CWLs), and are compatible with most competitive models. See your local Deere dealer for details.

	STANDARD DUTY	HEAVY DUTY	SEVERE DUTY		
			CWLs	Skid Steers / CTLs	
				PF45	PF60
<b>Frame Width</b>					
<b>With Steps</b>	1353 mm (53.3 in.)	1723 mm (67.8 in.)	N/A	1380 mm (54.0 in.)	1730 mm (68.0 in.)
<b>Less Steps</b>	1149 mm (45.3 in.)	1524 mm (60.0 in.)	1520 mm (60.0 in.)	1140 mm (45.0 in.)	1520 mm (60.0 in.)
<b>Frame Height</b>	986.5 mm (39 in.)	977 mm (38.5 in.)	535 mm (21.1 in.)	940 mm (37.0 in.)	940 mm (37.0 in.)
<b>Overall Length (frame and fork)</b>					
1067 mm (42 in.)	1251 mm (49.3 in.)	N/A	N/A	N/A	N/A
1220 mm (48 in.)	1403 mm (55.3 in.)	1460 mm (57.5 in.)	1445 mm (56.9 in.)	1520 mm (60.0 in.)	1520 mm (60.0 in.)
1520 mm (60 in.)	N/A	N/A	1750 mm (68.9 in.)	1830 mm (72.0 in.)	1830 mm (72.0 in.)
<b>Overall Weight (with 2 fork tines)</b>					
1067 mm (42 in.)	180 kg (397 lb.)	N/A	N/A	N/A	N/A
1220 mm (48 in.)	184 kg (407 lb.)	273 kg (602 in.)	342 kg (754 lb.)	331 kg (729 lb.)	359 kg (790 lb.)
1520 mm (60 in.)	N/A	N/A	370 kg (816 lb.)	360 kg (793 lb.)	388 kg (854 lb.)
<b>Fork Thickness</b>	35 mm (1.4 in.)	45 mm (1.78 in.)	50 mm (2 in.)	50 mm (2 in.)	50 mm (2 in.)
<b>Fork Tine Load Rating at 600-mm (24 in.) Load Center (1 pair of tines)*</b>	1700 kg (3,750 lb.)	2800 kg (6,160 lb.)	4000 kg (8,800 lb.)	4000 kg (8,800 lb.)	4000 kg (8,800 lb.)
<b>Vehicle Compatibility</b>	312GR, 314G, 316GR, 318G, 324E, 330G, and 332G Skid Steers; and 317G, 323E, 331G, and 333G CTLs	330G and 332G Skid Steers; 317G, 323E, 331G, and 333G CTLs	204K, 244K, 244K-II, 304K, and 324K CWLs	330G and 332G Skid Steers; and 331G and 333G CTLs	330G and 332G Skid Steers; and 331G and 333G CTLs

\*Pallet fork capacity listed. Reference machine Operator's Manual for machine capacity.

**WORKSITE PRO**

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

