

ROCK GRAPPLES



JOHN DEERE

GR72B | GR84B



ROCK GRAPPLES

GR72B | GR84B



Specifications

- Rock grapples are designed to be a multipurpose tool for land clearing, brush-removal applications, and jobsite cleanup.
- Cylinder size of 64-mm (2.5 in.) bore diameter and 36-mm (1.4 in.) rod diameter delivers high grapple forces to tackle even the most difficult materials. Grapple arms feature integrated mechanical stop to reduce cylinder load when open.
- 620-mm (24.4 in.)-wide grapple arm and grapple stances of 1540-mm (60.6 in.) on the GR72B and 1660-mm (65.3 in.) on the GR84B help grasp broad, cumbersome loads. Independent-action grapples enable different-sized objects to be picked up with each grapple.
- Durable 90-deg. quick-couplers on the hydraulic cylinder hoses eliminate interference with the grapple. Standard low-profile cylinder guards simplify hose connections.
- Tines are spaced 76 mm (3 in.) apart and fully supported on each side for maximum bend resistance. Weld-in serrated cutting edge easily penetrates difficult ground conditions.
- Solid backplate along the Quik-Tatch™ area protects hydraulic cylinder hoses and the machine from debris and damage. Thickened side cutter, side sheet, and backplate combine with large torque tubes for heavy-duty construction that meets the most demanding applications.
- Like all Worksite Pro™ attachments, these rock grapples are optimized to work with John Deere G-Series Skid Steer Loaders (SSLs) and Compact Track Loaders (CTLs), and L-Series Compact Wheel Loaders (CWLs). They're also compatible with most competitive models. See your local Deere dealer for details.

Rock Grapple Bucket	GR72B	GR84B
Weight	530 kg (1,165 lb.)	570 kg (1,255 lb.)
Width		
Overall	1830 mm (72 in.)	2135 mm (84 in.)
Grapple Arm	620 mm (24.4 in.)	620 mm (24.4 in.)
Grapples	1540 mm (60.6 in.)	1660 mm (65.3 in.)
Length		
Bucket Depth	970 mm (38.2 in.)	970 mm (38.2 in.)
Grapple Closed	1035 mm (40.7 in.)	1035 mm (40.7 in.)
Grapple Opened	1060 mm (41.7 in.)	1060 mm (41.7 in.)
Height		
Grapple Closed	830 mm (32.6 in.)	830 mm (32.6 in.)
Grapple Opened	1170 mm (46 in.)	1170 mm (46 in.)
Grapple Opening		
Tine Tip	950 mm (37.4 in.)	950 mm (37.4 in.)
Grapple Closed	460 mm (18.1 in.)	460 mm (18.1 in.)
Grapple Opened	1035 mm (40.75 in.)	1035 mm (40.75 in.)
Pivot Pin Diameter	35 mm (1.375 in.)	35 mm (1.375 in.)
Hydraulics		
Cylinder Bore Diameter	64 mm (2.5 in.)	64 mm (2.5 in.)
Cylinder Rod Diameter	36 mm (1.4 in.)	36 mm (1.4 in.)
Cylinder Stroke	206 mm (8.1 in.)	206 mm (8.1 in.)
Maximum Operating Pressure	24 000 kPa (3,500 psi)	24 000 kPa (3,500 psi)
Connection		
Hydraulic	12.7-mm (0.5 in.) quick-connect couplers	12.7-mm (0.5 in.) quick-connect couplers
Electrical	None	None
Vehicle Compatibility	312GR, 314G, 316GR, 318G, 320G, 324G, 330G, and 332G SSLs; 317G and 325G CTLs	320G, 324G, 330G, and 332G SSLs; 325G, 331G, and 333G CTLs; 204L, 304L, 244L, and 324L CWLs

WORKSITE PRO™

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

