

# SNOW BLOWERS



JOHN DEERE

*SB60B | SB72B | SB72H | SB78B | SB78H | SB84B | SB84H*



# SNOW BLOWERS

SB60B | SB72B | SB72H | SB78B | SB78H | SB84B | SB84H



## Specifications

- Two-stage hydraulic blower throws snow up to 13 m (45 ft).
- Simplified direct-drive hydraulic motor design eliminates chains and sprockets.
- Case drain hose not required on high-flow models.
- High-volume 635-mm (25 in.) (standard-flow models) or 914-mm (36 in.) (high-flow models) shroud openings enable you to work quickly.
- Electric-over-hydraulic poly-lined chute and deflector make it easy to direct the snow.
- Skid shoes adjust easily, and bolt-on wear-resistant tapered steel edges are easy to replace.
- Like all John Deere attachments, these snow blowers are optimized to work with John Deere skid steer loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs). They're also compatible with many competitive models. See your local Deere dealer for details.

	SB60B	SB72B	SB72H	SB78B	SB78H	SB84B	SB84H
<b>Flow</b>							
Type	Standard	Standard	High	Standard	High	Standard	High
Rate	53–79 lpm (14–21 gpm)	53–79 lpm (14–21 gpm)	72–129 lpm (19–34 gpm)	68–102 lpm (18–27 gpm)	72–129 lpm (19–34 gpm)	68–102 lpm (18–27 gpm)	114–159 lpm (30–42 gpm)
<b>Cutting</b>							
Width	1524 mm (60 in.)	1829 mm (72 in.)	1829 mm (72 in.)	1981 mm (78 in.)	1981 mm (78 in.)	2134 mm (84 in.)	2134 mm (84 in.)
Height	635 mm (25 in.)	635 mm (25 in.)	914 mm (36 in.)	635 mm (25 in.)	914 mm (36 in.)	635 mm (25 in.)	914 mm (36 in.)
Fan Diameter	457 mm (18 in.)	457 mm (18 in.)	660 mm (26 in.)	457 mm (18 in.)	660 mm (26 in.)	457 mm (18 in.)	660 mm (26 in.)
<b>Auger</b>							
Diameter	356 mm (14 in.)	356 mm (14 in.)	457 mm (18 in.)	356 mm (14 in.)	457 mm (18 in.)	356 mm (14 in.)	457 mm (18 in.)
Motor(s)	Single	Single	Dual	Single	Dual	Single	Dual
Approximate Weight	295 kg (650 lb.)	311 kg (685 lb.)	526 kg (1,160 lb.)	319 kg (703 lb.)	544 kg (1,200 lb.)	327 kg (720 lb.)	562 kg (1,240 lb.)
<b>Chute and Deflector Control Connection</b>							
Hydraulic	12.7-mm (0.5 in.) quick-connect couplers	12.7-mm (0.5 in.) quick-connect couplers	12.7-mm (0.5 in.) quick-connect couplers	12.7-mm (0.5 in.) quick-connect couplers	12.7-mm (0.5 in.) quick-connect couplers	12.7-mm (0.5 in.) quick-connect couplers	12.7-mm (0.5 in.) quick-connect couplers
Electrical	14 pin	14 pin	14 pin	14 pin	14 pin	14 pin	14 pin
<b>Vehicle Compatibility</b>							
	316GR and 318G SSLs; 317G CTL	316GR, 318G, 320G, and 324G SSLs; 317G and 325G CTLs; 204L and 304L CWLs	320G* and 324G* SSLs; 325G* CTL	320G, 324G, 330G, and 332G SSLs; 325G, 331G, and 333G CTLs; 244L and 324L CWLs	320G* and 324G*, 325G, 331G, and 333G CTLs; 244L* and 324L* CWLs	330G and 332G SSLs; 325G, 331G, and 333G CTLs; 244L CWL	330G* and 332G* SSLs; 331G* and 333G* CTLs; 324L* CWL

\*Requires high flow.

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

