

# BALE HUGGER



JOHN DEERE

AH80



# BALE HUGGER

AH80



## Specifications

- Designed for large round and rectangular bales. Maximum opening of 279.4 cm (110 in.) squeezes bales together for transport, stacking, and loading.
- Round tubing delivers maximum durability and prevents damage to bale wrappings/coverings.
- Right- and left-hand arms open simultaneously and apply constant pressure, eliminating risk of dropped or damaged bales.
- Ideal for 453.6-kg (1,000 lb.) silage bags, with a maximum load of 1088.62 kg (2,400 lb.).
- Like all John Deere attachments, the bale hugger is optimized to work with John Deere skid steers (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs) equipped with a skid-steer-style Quick-Tatch™ coupler. They're also compatible with most competitive models. See your local Deere dealer for details.

|                       | AH80  |
|-----------------------|---|
| Overall Width         | 120.65 cm (47.5 in.)  |
| Overall Height        | 95.25 cm (37.5 in.)   |
| Overall Depth         | 137.16 cm (54.0 in.)  |
| Maximum Opening       | 279.40 cm (110.0 in.)   |
| Lift Capacity         | 1088.62 kg (2,400.0 lb.)  |
| Operating Weight      | 217.72 kg (480.0 lb.)   |
| Vehicle Compatibility | 312GR, 314G, 316GR, 318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs; and 204L, 244L, 304L, and 324L CWLs |

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

