

Bale Spears

AB21 | AB31 | AB32 | AB42 | AB43 | SQUARE



JOHN DEERE



Bale Spears

AB21 | AB31 | AB32 | AB42 | AB43 | SQUARE



Specifications

- Offering optimal rigidity and capacity, these new John Deere bale spears are built for a long working life and designed for the loading, carrying, and stacking of baled organic materials typically used for livestock feed and bedding in agricultural applications.
- Round bale spears are replaceable and come in three different configurations of single, dual, or triple to help match numerous bale-handling applications.
- Low-profile design provides unrestricted visibility to the bale spear and tine tips.
- Square bale tines are retained with bolts and round bale tines are retained with cross-bolts, making both styles easy to replace.
- Quick-Tatch™ mounting provides quick and easy hookup and removal.
- Like all Worksite Pro™ attachments, bale spears are compatible with all skid steer loaders, compact track loaders (CTLs), and compact wheel loaders (CWLs) equipped with a skid steer-style Quik-Tatch™ coupler. See your local John Deere dealer for details.

	AB21	AB31	AB32	AB42	AB43	SQUARE	
Description	<i>Single Bale</i>	<i>Single Bale, Heavy Duty</i>	<i>Dual Bale</i>	<i>Dual Bale, Heavy Duty</i>	<i>Triple Bale</i>	<i>Square Bale</i>	
Capacity* at Load Center	907 kg (2,000 lb.) at 0.61 m (24 in.)	1361 kg (3,000 lb.) at 0.61 m (24 in.)	1361 kg (3,000 lb.) at 0.61 m (24 in.)	1814 kg (4,000 lb.) at 0.61 m (24 in.)	1814 kg (4,000 lb.) at 0.61 m (24 in.)	1545 kg (3,400 lb.) at 0.46 m (18 in.)	
Width	1.15 m (45.25 in.)	1.24 m (48.75 in.)	1.15 m (45.25 in.)	1.24 m (48.75 in.)	1.42 m (56.00 in.)	1.65 m (65.00 in.)	
Height	0.57 m (22.38 in.)	0.64 m (25.00 in.)	0.59 m (23.13 in.)	0.64 m (25.00 in.)	0.62 m (24.25 in.)	0.56 m (22.00 in.)	
Length	1.28 m (50.50 in.)	1.42 m (55.75 in.)	1.28 m (50.50 in.)	1.42 m (55.75 in.)	1.33 m (52.25 in.)	1.12 m (44.00 in.)	
Spear Length	1.24 m (49.00 in.)	1.35 m (53.00 in.)	1.24 m (49.00 in.)	1.35 m (53.00 in.)	1.24 m (49.00 in.)	0.89 m (35.00 in.)	
Weight	66 kg (145 lb.)	91 kg (200 lb.)	70 kg (155 lb.)	109 kg (240 lb.)	102 kg (225 lb.)	171 kg (375 lb.)	
Vehicle Compatibility	312GR, 314G, 316GR, 318G, 320E, 324E, 330G, and 332G Skid Steers; 317G, 323E, 331G, and 333G CTLs; 204K, 244K-II, 304K, 324K, and 344K CWLs	312GR, 314G, 316GR, 318G, 320E, 324E, 330G, and 332G Skid Steers; 317G, 323E, 331G, and 333G CTLs; 204K, 244K-II, 304K, 324K, and 344K CWLs	312GR, 314G, 316GR, 318G, 320E, 324E, 330G, and 332G Skid Steers; 317G, 323E, 331G, and 333G CTLs; 204K, 244K-II, 304K, 324K, and 344K CWLs	312GR, 314G, 316GR, 318G, 320E, 324E, 330G, and 332G Skid Steers; 317G, 323E, 331G, and 333G CTLs; 204K, 244K-II, 304K, 324K, and 344K CWLs	312GR, 314G, 316GR, 318G, 320E, 324E, 330G, and 332G Skid Steers; 317G, 323E, 331G, and 333G CTLs; 204K, 244K-II, 304K, 324K, and 344K CWLs	312GR, 314G, 316GR, 318G, 320E, 324E, 330G, and 332G Skid Steers; 317G, 323E, 331G, and 333G CTLs; 204K, 244K-II, 304K, 324K, and 344K CWLs	312GR, 314G, 316GR, 318G, 320E, 324E, 330G, and 332G Skid Steers; 317G, 323E, 331G, and 333G CTLs; 204K, 244K-II, 304K, 324K, and 344K CWLs

*Bale spear capacity. See Operator's Manual for machine capacity.

WORKSITE PRO

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

