

# Perfect grades start with new Frontier 32 Series Box Blades

**Knock out big jobs faster with Frontier.** When you're paid by the job, you need rugged, reliable equipment that's ready to work when you are. Plus, you need equipment that's easy to use no matter who is behind the controls. Take the new construction-duty Frontier 32 Series Box Blades — designed and built for simple operation, dependable up time, and maximum performance.

A balanced, heavy-duty welded mast and 4x4-inch tubular steel scarifier beam deliver added strength for the most challenging jobs — there's no need for gussets. Replaceable scarifier points are heat-treated for durability. Scarifiers have three notched positions for breaking or deep digging action and can be stored in the scarifier beam when not needed. Cutting edges are .5x6-inch steel and are reversible for extended life. The high-capacity, smooth-surface steel box has a hinged tailgate — making your leveling and soil finishing easier.

The 32 Series Box Blades are available in working widths of 72, 84, and 96 inches. They're compatible with tractors and backhoe loaders of 40 to 80 horsepower with a Category 1 or 2 three-point hitch (iMatch and Quick-Coupler compatible; bushing kit required).

Frontier Box Blades are backed with a one-year warranty and the best dealer network in the industry — John Deere. To help you choose the right Frontier Box Blade, talk to your John Deere dealer, your exclusive distributor of Frontier Equipment.

[www.BuyFrontier.com](http://www.BuyFrontier.com)



**Construction Grade**

# New Frontier 32 Series Box Blades: Rugged. Reliable. Ready.

## DETAILS



Box blades remove high points and fill in low points by scraping the surface and moving material across the work site. They're perfect for any job that requires precision scraping, leveling, and backfilling.

The hinged tailgate allows for clean material flow for improved leveling and finishing. Plus, it's built for superior performance when backfilling.



Scarifier height is easily adjustable. Simply remove the shank key and raise or lower the scarifier to one of three settings. Use the top notch for deeper ground penetration.



**iMatch™**

All models are iMatch™ compatible. The iMatch quick-hitch system converts the tractor's 3-point hitch to fixed hooks and attaching points for a super-quick connection. (iMatch hitch sold separately.)

## SPECIFICATIONS

| Model                        | BB3272  | BB3284  | BB3296  |
|------------------------------|---|---|---|
| Duty                         | Construction  | Construction  | Construction  |
| Working width                | 72 in. (1.8 m)  | 84 in. (2.1 m)  | 96 in. (2.4 m)  |
| Capacity                     | 21 cubic feet (0.6 m³)                                | 24.50 cubic feet (0.7 m³)                             | 28 cubic feet (0.8 m³)                                |
| Tractor horsepower (maximum) | 80 hp   | 80 hp   | 80 hp   |
| Hitch                        | Category 1, 2 (iMatch & Quick-Coupler compatible)     | Category 1, 2 (iMatch & Quick-Coupler compatible)     | Category 1, 2 (iMatch & Quick-Coupler compatible)     |
| Tailgate                     | Hinged  | Hinged  | Hinged  |
| Scarifier shanks             | Notched, 3 positions                                  | Notched, 3 positions                                  | Notched, 3 positions                                  |
| Scarifier points             | Replaceable, heat-treated steel                       | Replaceable, heat-treated steel                       | Replaceable, heat-treated steel                       |
| Scarifier beam               | 4x4x.375-in. (102x102x10 mm) reinforced tubular steel | 4x4x.375-in. (102x102x10 mm) reinforced tubular steel | 4x4x.375-in. (102x102x10 mm) reinforced tubular steel |
| Tailgate                     | Hinged  | Hinged  | Hinged  |
| Endplate thickness           | .5 in. (12.7 mm)                                      | .5 in. (12.7 mm)                                      | .5 in. (12.7 mm)                                      |
| Moldboard thickness          | .25 in. (6.3 mm)                                      | .25 in. (6.3 mm)                                      | .25 in. (6.3 mm)                                      |
| Cutting edges                | (2) .5x6-in. (12.7x152 mm) reversible                 | (2) .5x6-in. (12.7x152 mm) reversible                 | (2) .5x6-in. (12.7x152 mm) reversible                 |
| Weight                       | 790 lb. (358 kg)                                      | 885 lb. (401 kg)                                      | 1,010 lb. (458 kg)                                    |
| Warranty                     | 1 year  | 1 year  | 1 year  |

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. Frontier Equipment reserves the right to change specifications, design, and price of products described in this literature without notice. Copyright 2005, Frontier Equipment.