

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

2R Series Compact Utility Tractors - 2025R (- HH100000), 2032R (- GH100007)

FILTER PACKS

(2025R (- HH100000)) - [LVA21204](#)

M806418, MIU804763, M131802, AL221066, LVA802810

(2032R (- GH100007)) - [LVA21201](#)

M806419, M131802, LVU800097, MIU800645

Each kit contains above filters, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.




TRANSMISSION OIL FILTER

(2025R (- HH100000)) - [LVA802810](#)

Replace initially after 50 hours, then every 200 hours.

(Click here for [capacity](#))



ENGINE AIR FILTER ELEMENT

PRIMARY - [M131802](#)

SECONDARY - [M131803](#)

Replace as required per conditions.




HYDRAULIC OIL FILTER

(2025R (- HH100000)) - [AL221066](#)

(2032R (- GH100007)) - [LVU800097](#)

Replace initially after 50 hours, then every 200 hours.

(Click here for [capacity](#))



FUEL FILTER

(2025R (- HH100000)) - [MIU804763](#)

Replace after every 400 hours or annually, whichever occurs first.



ENGINE OIL FILTER

(2025R) [M806418](#)

(2032R, 2038R) [M806419](#)

Replace after every 200 hours or annually, whichever occurs first.

(Click here for [capacity](#))



FUEL FILTER

(2032R (- GH100007)) - [MIU800645](#)

Replace after every 400 hours or annually, whichever occurs first.



JOHN DEERE

Genuine Parts and Service

https://www.deere.com/en_US/parts/parts_by_industry/ag/fmi/filter_maintenance_information.page

CAPACITIES

2R Series Compact Utility Tractors - 2025R (- HH100000), 2032R (- GH100007)

CAPACITIES (Approximate):

Fuel Tank:

2025R	23 L (6.1 gal)
2032R	27 L (7.1 gal)

Cooling System:

Cool-Gard™ II

2025R	3.2 L (0.84 gal)
2032R	4.0 L (1.05 gal)

Crankcase with Filter:

Plus-50™

2025R	3.2 L (0.84 gal)
2032R	3.4 L (0.89 gal)

Transmission and Hydraulic System:

Hy-Gard™

2025R	13.1 L (3.5 gal)
2032R	17.5 L (4.6 gal)

Front Axle:

GL-5

2025R	3.4 L (0.89 gal)
2032R	3.9 L (1.03 gal)

[Return to Filter Overview](#)

