

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

2R Series Compact Utility Tractors - 2027R

FILTER PACKS

[LVA21201](#)

M806419, M131802, LVU800097, MIU800645

Each kit contains above filters, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

TRANSMISSION

OIL FILTER - [LVU800097](#)

Replace initially after 50 hours, then every 200 hours.

(Click here for [capacity](#))



ENGINE OIL FILTER

[M806419](#)

Replace initially after 50 hours, then every 200 hours or annually, whichever occurs first.

(Click here for [capacity](#))




ENGINE AIR FILTER ELEMENT

PRIMARY - [M131802](#)

SECONDARY - [M131803](#)

Replace as required per conditions.



ENGINE

SECONDARY FUEL FILTER - [M811032](#)

Replace after every 400 hours or annually, whichever occurs first.



FUEL FILTER

[MIU800645](#)

Replace after every 400 hours or annually, whichever occurs first.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

2R Series Compact Utility Tractors - 2027R

CAPACITIES (Approximate):

Fuel Tank:

..... 27 L (7.1 gal)

Cooling System:

Cool-Gard™ II

..... 4.0 L (1.05 gal)

Crankcase with Filter:

Plus-50™

..... 3.4 L (0.89 gal)

Transmission and Hydraulic System:

Hy-Gard™

..... 17.5 L (4.6 gal)

Front Axle:

GL-5

..... 3.9 L (1.03 gal)

[Return to Filter Overview](#)

