

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

2R Series Compact Utility Tractors - 2032R (LL300001-), 2038R (LL300001-)

TRANSMISSION

OIL FILTER - [LVA16054](#)

Replace initially after 50 hours, then every 200 hours.

(Click here for [capacity](#))



HYDRAULIC

OIL FILTER - [LVA14703](#)

Replace after every 400 hours or annually, whichever occurs first.

(Click here for [capacity](#))



ENGINE

OIL FILTER - [M806419](#)

Replace after every 400 hours or annually, whichever occurs first.

(Click here for [capacity](#))




FILTER PACKS

(2032R, 2038R) - [LVA23615](#)

M806419, M131802, LVA14703, MIU800645, MIU803127, LVA16054, M131803

Each kit contains above filters, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.



ENGINE

PRIMARY AIR FILTER - [M131802](#)

SECONDARY AIR FILTER - [M131803](#)

Replace after every 600 hours or as required

ENGINE

PRIMARY FUEL FILTER - [MIU800645](#)

SECONDARY FUEL FILTER - [MIU803127](#)

Replace after every 400 hours or annually, whichever occurs first.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

2R Series Compact Utility Tractors - 2032R (LL300001-), 2038R (LL300001-)

CAPACITIES (Approximate):

Fuel Tank:

2032R, 2038R 32 L (8.5 gal)

Cooling System:

Cool-Gard™ II

2032R 4.9 L (1.3 gal)

2038R 5.2 L (1.37 gal)

Crankcase with Filter:

Plus-50™

2032R, 2038R 4.3 L (1.13 gal)

Transmission and Hydraulic System:

Hy-Gard™

2032R, 2038R 23.5 L (6.2 gal)

Front Axle:

GL-5

2032R, 2038R 3.8 L (1 gal)

[Return to Filter Overview](#)

