

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

3E Series Compact Utility Tractors - 3025E, 3032E, 3038E

ENGINE

DIESEL PARTICULATE FILTER (DPF)

3032E – [MIA884117](#)

3038E (S/N 610001 -) – [MIA884119](#)

See your John Deere™ dealer or qualified service provider.

FILTER PAK

3032E, 3038E – [LVA21037](#)

M806419, LVA14703, LVA16054, M131802, MIU803127, MIU802421

3025E, 3032E (S/N - 610000), 3038E (S/N - 610000) – [LVA21128](#)

M806419, LVA14703, MIU800645, LVA16054, M131802

Each kit contains above filters, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

ENGINE

PRIMARY AIR FILTER – [M131802](#)

SECONDARY AIR FILTER – [M131803](#)

Check or replace after every 600 hours or as required.

ENGINE

FUEL FILTER – [MIU800645](#)

(3032E, 3038E) – [MIU803127](#)

Replace after every 400 hours or annually, whichever occurs first.

ENGINE

OIL FILTER – [M806419](#)

Replace after every 200 hours or annually, whichever occurs first.

(Click here for [capacity](#))

ENGINE

FUEL/WATER SEPARATOR – [M811032](#)

(3032E, 3036E, 3038E) – [MIU802421](#)

Replace after every 400 hours or annually, whichever occurs first.

TRANSMISSION/HYDRAULIC
OIL FILTER – [LVA16054](#)

Replace after initial 50 hours, then every 400 hours.

(Click here for [capacity](#))

HYDRAULIC

OIL FILTER – [LVA14703](#)

Replace after every 400 hours.

(Click here for [capacity](#))



JOHN DEERE

Genuine Parts and Service

CAPACITIES

3E Series Compact Utility Tractors - 3025E, 3032E, 3038E

CAPACITIES (Approximate):

Fuel Tank:

..... 28.5 L (7.5 gal)

Cooling System:

Cool-Gard™ II

3025E, 3032E 4.9 L (1.29 gal)

3038E 5.2 L (1.37 gal)

Crankcase with Filter:

Plus-50™

..... 4.3 L (1.1 gal)

Transmission and Hydraulic System:

Hy-Gard™

..... 20.8 L (5.49 gal)

Front Axle:

Hy-Gard™

..... 3.8 L (1 gal)

[Return to Filter Overview](#)

